

Package ‘openxlsx2’

May 1, 2024

Type Package

Title Read, Write and Edit 'xlsx' Files

Version 1.6

Language en-US

Description Simplifies the creation of 'xlsx' files by providing a high level interface to writing, styling and editing worksheets.

License MIT + file LICENSE

URL <https://janmarvin.github.io/openxlsx2/>,
<https://github.com/JanMarvin/openxlsx2>

BugReports <https://github.com/JanMarvin/openxlsx2/issues>

Depends R (>= 3.5.0)

Imports R6, Rcpp, grDevices, magrittr, stringi, utils, zip

LinkingTo Rcpp

Suggests ggplot2, knitr, mschart (>= 0.4), rmarkdown, rvg, testthat (>= 3.0.0), waldo

VignetteBuilder knitr

Encoding UTF-8

RoxygenNote 7.3.1

Config/testthat/edition 3

Config/testthat/parallel true

NeedsCompilation yes

Author Jordan Mark Barbone [aut] (<<https://orcid.org/0000-0001-9788-3628>>),
Jan Marvin Garbuszus [aut, cre],
Oliver Roy [ctb],
openxlsx authors [cph] (openxlsx package),
Arseny Kapoulkine [ctb, cph] (Author of included pugixml code)

Maintainer Jan Marvin Garbuszus <jan.garbuszus@ruhr-uni-bochum.de>

Repository CRAN

Date/Publication 2024-05-01 09:30:02 UTC

R topics documented:

active_sheet-wb	4
as_xml	5
base_font-wb	6
clean_worksheet_name	7
col2int	8
col_widths-wb	8
convert_date	10
convert_to_excel_date	11
create_border	12
create_cell_style	13
create_colors_xml	15
create_dxfs_style	16
create_fill	18
create_font	18
create_hyperlink	20
create_numfmt	21
create_sparklines	22
create_tablestyle	24
creators-wb	26
dims_helper	27
filter-wb	28
fmt_txt	29
grouping-wb	31
int2col	33
named_region-wb	34
openxlsx2-deprecated	36
openxlsx2_options	37
person-wb	38
print.pugi_xml	39
properties-wb	39
pugixml	41
read_xml	42
row_heights-wb	43
sheet_names-wb	44
sheet_visibility-wb	45
styles_on_sheet	46
temp_xlsx	46
waivers	47
wbWorkbook	47
wb_add_border	92
wb_add_cell_style	93
wb_add_chartsheet	96
wb_add_chart_xml	97
wb_add_comment	98
wb_add_conditional_formatting	99
wb_add_data	102

<code>wb_add_data_table</code>	105
<code>wb_add_data_validation</code>	107
<code>wb_add_drawing</code>	109
<code>wb_add_dxfs_style</code>	110
<code>wb_add_fill</code>	112
<code>wb_add_font</code>	113
<code>wb_add_formula</code>	115
<code>wb_add_form_control</code>	117
<code>wb_add_ignore_error</code>	118
<code>wb_add_image</code>	119
<code>wb_add_mips</code>	120
<code>wb_add_mschart</code>	121
<code>wb_add_named_style</code>	122
<code>wb_add_numfmt</code>	123
<code>wb_add_page_break</code>	124
<code>wb_add_pivot_table</code>	125
<code>wb_add_plot</code>	127
<code>wb_add_slicer</code>	129
<code>wb_add_sparklines</code>	130
<code>wb_add_style</code>	131
<code>wb_add_thread</code>	132
<code>wb_add_worksheet</code>	133
<code>wb_base_colors</code>	135
<code>wb_cell_style</code>	137
<code>wb_clean_sheet</code>	138
<code>wb_clone_sheet_style</code>	139
<code>wb_clone_worksheet</code>	139
<code>wb_color</code>	140
<code>wb_comment</code>	141
<code>wb_copy_cells</code>	142
<code>wb_data</code>	143
<code>wb_dims</code>	144
<code>wb_freeze_pane</code>	147
<code>wb_get_tables</code>	149
<code>wb_load</code>	149
<code>wb_merge_cells</code>	151
<code>wb_open</code>	152
<code>wb_order</code>	152
<code>wb_page_setup</code>	153
<code>wb_protect</code>	157
<code>wb_protect_worksheet</code>	159
<code>wb_remove_tables</code>	160
<code>wb_remove_worksheet</code>	161
<code>wb_save</code>	162
<code>wb_set_bookview</code>	163
<code>wb_set_grid_lines</code>	164
<code>wb_set_header_footer</code>	165
<code>wb_set_last_modified_by</code>	166

wb_set_sheetview	167
wb_to_df	169
wb_update_table	173
wb_workbook	174
write_xlsx	175
xl_open	177
xml_add_child	178
xml_attr_mod	179
xml_node_create	180
xml_rm_child	181

Index 182

active_sheet-wb	<i>Modify the state of active and selected sheets in a workbook</i>
-----------------	---

Description

Get and set table of sheets and their state as selected and active in a workbook

Multiple sheets can be selected, but only a single one can be active (visible). The visible sheet, must not necessarily be a selected sheet.

Usage

```
wb_get_active_sheet(wb)

wb_set_active_sheet(wb, sheet)

wb_get_selected(wb)

wb_set_selected(wb, sheet)
```

Arguments

wb	a workbook
sheet	a sheet name of the workbook

Value

a data frame with tabSelected and names

Examples

```
wb <- wb_load(file = system.file("extdata", "openxlsx2_example.xlsx", package = "openxlsx2"))
# testing is the selected sheet
wb_get_selected(wb)
# change the selected sheet to Sheet2
wb <- wb_set_selected(wb, "Sheet2")
```

```
# get the active sheet
wb_get_active_sheet(wb)
# change the selected sheet to Sheet2
wb <- wb_set_active_sheet(wb, sheet = "Sheet2")
```

as_xml	<i>loads character string to pugixml and returns an externalptr</i>
--------	---

Description

loads character string to pugixml and returns an externalptr

Usage

```
as_xml(x, ...)
```

Arguments

x	input as xml
...	additional arguments passed to read_xml()

Details

might be useful for larger documents where single nodes are shortened and otherwise the full tree has to be reimported. unsure where we have such a case. is useful, for printing nodes from a larger tree, that have been exported as characters (at some point in time we have to convert the xml to R)

Examples

```
tmp_xlsx <- tempfile()
xlsxFile <- system.file("extdata", "openxlsx2_example.xlsx", package = "openxlsx2")
unzip(xlsxFile, exdir = tmp_xlsx)

wb <- wb_load(xlsxFile)
styles_xml <- sprintf("%s/xl/styles.xml", tmp_xlsx)

# is external pointer
sxml <- read_xml(styles_xml)

# is character
font <- xml_node(sxml, "styleSheet", "fonts", "font")

# is again external pointer
as_xml(font)
```

`base_font-wb`*Set the default font in a workbook*

Description

Modify / get the default font for the workbook. This will alter the latin major and minor font in the workbooks theme.

Usage

```
wb_set_base_font(  
    wb,  
    font_size = 11,  
    font_color = wb_color(theme = "1"),  
    font_name = "Aptos Narrow",  
    ...  
)  
  
wb_get_base_font(wb)
```

Arguments

<code>wb</code>	A workbook object
<code>font_size</code>	Font size
<code>font_color</code>	Font color
<code>font_name</code>	Name of a font
<code>...</code>	Additional arguments

Details

The font name is not validated in anyway. Spreadsheet software replaces unknown font names with system defaults.

The default base font is Aptos Narrow, black, size 11. If `font_name` differs from the name in [wb_get_base_font\(\)](#), the theme is updated to use the newly selected font name.

See Also

Other workbook styling functions: [wb_add_dxfs_style\(\)](#), [wb_add_style\(\)](#), [wb_base_colors](#)

Other workbook wrappers: [col_widths-wb](#), [creators-wb](#), [grouping-wb](#), [row_heights-wb](#), [wb_add_chartsheet\(\)](#), [wb_add_data\(\)](#), [wb_add_data_table\(\)](#), [wb_add_formula\(\)](#), [wb_add_pivot_table\(\)](#), [wb_add_slicer\(\)](#), [wb_add_worksheet\(\)](#), [wb_base_colors](#), [wb_clone_worksheet\(\)](#), [wb_copy_cells\(\)](#), [wb_freeze_pane\(\)](#), [wb_merge_cells\(\)](#), [wb_save\(\)](#), [wb_set_last_modified_by\(\)](#), [wb_workbook\(\)](#)

Examples

```
## create a workbook
wb <- wb_workbook(theme = "Office 2013 - 2022 Theme")
wb$add_worksheet("S1")
## modify base font to size 10 Aptos Narrow in red
wb$set_base_font(font_size = 10, font_color = wb_color("red"), font_name = "Aptos Narrow")

wb$add_data(x = iris)

## font color does not affect tables
wb$add_data_table(x = iris, dims = wb_dims(from_col = 10))

## get the base font
wb_get_base_font(wb)
```

clean_worksheet_name *Clean worksheet name*

Description

Cleans a worksheet name by removing legal characters.

Usage

```
clean_worksheet_name(x, replacement = " ")
```

Arguments

x	A vector, coerced to character
replacement	A single value to replace illegal characters by.

Details

Illegal characters are considered \, /, ?, *, :, [, and]. These must be intentionally removed from worksheet names prior to creating a new worksheet.

Value

x with bad characters removed

col2int *Convert Excel column to integer*

Description

Converts an Excel column label to an integer.

Usage

```
col2int(x)
```

Arguments

x A character vector

Value

An integer column label (or NULL if x is NULL)

Examples

```
col2int(LETTERS)
```

col_widths-wb *Modify column widths of a worksheet*

Description

Remove / set worksheet column widths to specified width or "auto".

Usage

```
wb_set_col_widths(  
  wb,  
  sheet = current_sheet(),  
  cols,  
  widths = 8.43,  
  hidden = FALSE  
)  
  
wb_remove_col_widths(wb, sheet = current_sheet(), cols)
```


Arguments

wb	A wbWorkbook object.
sheet	A name or index of a worksheet, a vector in the case of remove_
cols	Indices of cols to set/remove column widths.
widths	Width to set cols to specified column width or "auto" for automatic sizing. widths is recycled to the length of cols. openxlsx2 sets the default width is 8.43, as this is the standard in some spreadsheet software. See Details for general information on column widths.
hidden	Logical vector recycled to the length of cols. If TRUE, the columns are hidden.

Details

The global min and max column width for "auto" columns is set by (default values show):

- `options("openxlsx2.minWidth" = 3)`
- `options("openxlsx2.maxWidth" = 250)` Maximum width allowed in Excel

NOTE: The calculation of column widths can be slow for large worksheets.

NOTE: The hidden parameter may conflict with the one set in `wb_group_cols()`; changing one will update the other.

NOTE: The default column width varies by spreadsheet software, operating system, and DPI settings used. Setting widths to specific value also is no guarantee that the output will have consistent column widths.

For automatic text wrapping of columns use `wb_add_cell_style(wrap_text = TRUE)`

See Also

Other workbook wrappers: `base_font-wb`, `creators-wb`, `grouping-wb`, `row_heights-wb`, `wb_add_chartsheet()`, `wb_add_data()`, `wb_add_data_table()`, `wb_add_formula()`, `wb_add_pivot_table()`, `wb_add slicer()`, `wb_add_worksheet()`, `wb_base_colors`, `wb_clone_worksheet()`, `wb_copy_cells()`, `wb_freeze_pane()`, `wb_merge_cells()`, `wb_save()`, `wb_set_last_modified_by()`, `wb_workbook()`

Other worksheet content functions: `filter-wb`, `grouping-wb`, `named_region-wb`, `row_heights-wb`, `wb_add_conditional_formatting()`, `wb_add_data()`, `wb_add_data_table()`, `wb_add_formula()`, `wb_add_pivot_table()`, `wb_add slicer()`, `wb_add_thread()`, `wb_freeze_pane()`, `wb_merge_cells()`

Examples

```
## Create a new workbook
wb <- wb_workbook()

## Add a worksheet
wb$add_worksheet("Sheet 1")

## set col widths
wb$set_col_widths(cols = c(1, 4, 6, 7, 9), widths = c(16, 15, 12, 18, 33))

## auto columns
```

```

wb$add_worksheet("Sheet 2")
wb$add_data(sheet = 2, x = iris)
wb$set_col_widths(sheet = 2, cols = 1:5, widths = "auto")

## removing column widths
## Create a new workbook
wb <- wb_load(file = system.file("extdata", "openxlsx2_example.xlsx", package = "openxlsx2"))

## remove column widths in columns 1 to 20
wb_remove_col_widths(wb, 1, cols = 1:20)

```

convert_date

Convert from Excel date, datetime or hms number to R Date type

Description

Convert from Excel date number to R Date type

Usage

```

convert_date(x, origin = "1900-01-01", ...)

convert_datetime(x, origin = "1900-01-01", ...)

convert_hms(x)

```

Arguments

x	A vector of integers
origin	date. Default value is for Windows Excel 2010
...	Arguments passed on to <code>base::as.Date.character</code>

format a `character` string. If not specified when converting from a character representation, it will try `tryFormats` one by one on the first non-NA element, and give an error if none works. Otherwise, the processing is via `strptime()` whose help page describes available conversion specifications.

`tryFormats` `character` vector of format strings to try if format is not specified.

optional `logical` indicating to return NA (instead of signalling an error) if the format guessing does not succeed.

Details

Excel stores dates as number of days from some origin day

Value

A date, datetime, or hms.

See Also[wb_add_data\(\)](#)**Examples**

```
# date --
## 2014 April 21st to 25th
convert_date(c(41750, 41751, 41752, 41753, 41754, NA))
convert_date(c(41750.2, 41751.99, NA, 41753))

# datetime --
## 2014-07-01, 2014-06-30, 2014-06-29
x <- c(41821.8127314815, 41820.8127314815, NA, 41819, NaN)
convert_datetime(x)
convert_datetime(x, tz = "Australia/Perth")
convert_datetime(x, tz = "UTC")

# hms ---
## 12:13:14
x <- 0.50918982
convert_hms(x)
```

convert_to_excel_date *convert back to an Excel Date*

Description

convert back to an Excel Date

Usage

```
convert_to_excel_date(df, date1904 = FALSE)
```

Arguments

df	dataframe
date1904	take different origin

Examples

```
xlsxFile <- system.file("extdata", "openxlsx2_example.xlsx", package = "openxlsx2")
wb1 <- wb_load(xlsxFile)
df <- wb_to_df(wb1)
# conversion is done on dataframes only
convert_to_excel_date(df = df["Var5"], date1904 = FALSE)
```

 create_border

Helper to create a border

Description

Border styles can any of the following: "thin", "thick", "slantDashDot", "none", "mediumDashed", "mediumDashDot", "medium", "hair", "double", "dotted", "dashed", "dashedDotDot", "dashDot"
 Border colors can be created with [wb_color\(\)](#)

Usage

```
create_border(
  diagonal_down = "",
  diagonal_up = "",
  outline = "",
  bottom = NULL,
  bottom_color = NULL,
  diagonal = NULL,
  diagonal_color = NULL,
  end = "",
  horizontal = "",
  left = NULL,
  left_color = NULL,
  right = NULL,
  right_color = NULL,
  start = "",
  top = NULL,
  top_color = NULL,
  vertical = "",
  ...
)
```

Arguments

diagonal_down	x
diagonal_up	x
outline	x
bottom	X
bottom_color, diagonal_color, left_color, right_color, top_color	a color created with wb_color()
diagonal	X
end	x,
horizontal	x
left	x

right	x
start	x
top	x
vertical	x
...	x

See Also[wb_add_border\(\)](#)

Other style creating functions: [create_cell_style\(\)](#), [create_colors_xml\(\)](#), [create_dxfs_style\(\)](#), [create_fill\(\)](#), [create_font\(\)](#), [create_numfmt\(\)](#), [create_tablestyle\(\)](#)

create_cell_style	<i>Helper to create a cell style</i>
-------------------	--------------------------------------

Description

Helper to create a cell style

Usage

```
create_cell_style(  
    border_id = "",  
    fill_id = "",  
    font_id = "",  
    num_fmt_id = "",  
    pivot_button = "",  
    quote_prefix = "",  
    xf_id = "",  
    horizontal = "",  
    indent = "",  
    justify_last_line = "",  
    reading_order = "",  
    relative_indent = "",  
    shrink_to_fit = "",  
    text_rotation = "",  
    vertical = "",  
    wrap_text = "",  
    ext_lst = "",  
    hidden = "",  
    locked = "",  
    ...  
)
```

Arguments

border_id	dummy
fill_id	dummy
font_id	dummy
num_fmt_id	a numFmt ID for a builtin style
pivot_button	dummy
quote_prefix	dummy
xf_id	dummy
horizontal	alignment can be "", "center", "right"
indent	dummy
justify_last_line	dummy
reading_order	dummy
relative_indent	dummy
shrink_to_fit	dummy
text_rotation	dummy
vertical	alignment can be "", "center", "right"
wrap_text	dummy
ext_lst	dummy
hidden	dummy
locked	dummy
...	reserved for additional arguments

Details

"ID"	"numFmt"
"0"	"General"
"1"	"0"
"2"	"0.00"
"3"	"#,##0"
"4"	"#,##0.00"
"9"	"0%"
"10"	"0.00%"
"11"	"0.00E+00"
"12"	"# ?/?"
"13"	"# ??/??"
"14"	"mm-dd-yy"
"15"	"d-mmm-yy"
"16"	"d-mmm"
"17"	"mmm-yy"
"18"	"h:mm AM/PM"

```

"19" "h:mm:ss AM/PM"
"20" "h:mm"
"21" "h:mm:ss"
"22" "m/d/yy h:mm"
"37" "#,##0 ;(#,##0)"
"38" "#,##0 ;[Red](#,##0)"
"39" "#,##0.00;(#,##0.00)"
"40" "#,##0.00;[Red](#,##0.00)"
"45" "mm:ss"
"46" "[h]:mm:ss"
"47" "m:ss.0"
"48" "##0.0E+0"
"49" "@"

```

See Also

[wb_add_cell_style\(\)](#)

Other style creating functions: [create_border\(\)](#), [create_colors_xml\(\)](#), [create_dxfs_style\(\)](#), [create_fill\(\)](#), [create_font\(\)](#), [create_numfmt\(\)](#), [create_tablestyle\(\)](#)

create_colors_xml *Create custom color xml schemes*

Description

Create custom color themes that can be used with [wb_set_base_colors\(\)](#). The color input will be checked with [wb_color\(\)](#), so it must be either a color R from [grDevices::colors\(\)](#) or a hex value. Default values for the dark argument are: black, white, darkblue and lightgray. For the accent argument, the six inner values of [grDevices::palette\(\)](#). The link argument uses blue and purple by default for active and visited links.

Usage

```
create_colors_xml(name = "Base R", dark = NULL, accent = NULL, link = NULL)
```

Arguments

name	the color name
dark	four colors: dark, light, brighter dark, darker light
accent	six accent colors
link	two link colors: link and visited link

See Also

Other style creating functions: [create_border\(\)](#), [create_cell_style\(\)](#), [create_dxfs_style\(\)](#), [create_fill\(\)](#), [create_font\(\)](#), [create_numfmt\(\)](#), [create_tablestyle\(\)](#)

Examples

```
colors <- create_colors_xml()
wb <- wb_workbook()$add_worksheet()$set_base_colors(xml = colors)
```

create_dxfs_style *Create a custom formatting style*

Description

Create a new style to apply to worksheet cells. Created styles have to be assigned to a workbook to use them

Usage

```
create_dxfs_style(
  font_name = NULL,
  font_size = NULL,
  font_color = NULL,
  num_fmt = NULL,
  border = NULL,
  border_color = wb_color(getOption("openxlsx2.borderColor", "black")),
  border_style = getOption("openxlsx2.borderStyle", "thin"),
  bg_fill = NULL,
  fg_color = NULL,
  gradient_fill = NULL,
  text_bold = NULL,
  text_strike = NULL,
  text_italic = NULL,
  text_underline = NULL,
  ...
)
```

Arguments

font_name	A name of a font. Note the font name is not validated. If font_name is NULL, the workbook base_font is used. (Defaults to Calibri), see wb_get_base_font()
font_size	Font size. A numeric greater than 0. By default, the workbook base font size is used. (Defaults to 11)
font_color	Color of text in cell. A valid hex color beginning with "#" or one of colors(). If font_color is NULL, the workbook base font colors is used. (Defaults to black)

num_fmt	Cell formatting. Some custom openxml format
border	NULL or TRUE
border_color	"black"
border_style	"thin"
bg_fill	Cell background fill color.
fg_color	Cell foreground fill color.
gradient_fill	An xml string beginning with <gradientFill> ...
text_bold	bold
text_strike	strikeout
text_italic	italic
text_underline	underline 1, true, single or double
...	Additional arguments

Details

It is possible to override border_color and border_style with {left, right, top, bottom}_color, {left, right, top, bottom}_style.

Value

A dxfs style node

See Also

[wb_add_style\(\)](#) [wb_add_dxfs_style\(\)](#)

Other style creating functions: [create_border\(\)](#), [create_cell_style\(\)](#), [create_colors_xml\(\)](#), [create_fill\(\)](#), [create_font\(\)](#), [create_numfmt\(\)](#), [create_tablestyle\(\)](#)

Examples

```
# do not apply anything
style1 <- create_dxfs_style()

# change font color and background color
style2 <- create_dxfs_style(
  font_color = wb_color(hex = "FF9C0006"),
  bgFill = wb_color(hex = "FFFFC7CE")
)

# change font (type, size and color) and background
# the old default in openxlsx and openxlsx2 <= 0.3
style3 <- create_dxfs_style(
  font_name = "Aptos Narrow",
  font_size = 11,
  font_color = wb_color(hex = "FF9C0006"),
  bgFill = wb_color(hex = "FFFFC7CE")
)

## See package vignettes for further examples
```

create_fill	<i>Create fill pattern</i>
-------------	----------------------------

Description

Create fill pattern

Usage

```
create_fill(
    gradientFill = "",
    patternType = "",
    bgColor = NULL,
    fgColor = NULL,
    ...
)
```

Arguments

gradientFill	complex fills
patternType	various: default is "none", but also "solid", or a color like "gray125"
bgColor	hex8 color with alpha, red, green, blue only for patternFill
fgColor	hex8 color with alpha, red, green, blue only for patternFill
...	...

See Also

[wb_add_fill\(\)](#)

Other style creating functions: [create_border\(\)](#), [create_cell_style\(\)](#), [create_colors_xml\(\)](#), [create_dxfs_style\(\)](#), [create_font\(\)](#), [create_numfmt\(\)](#), [create_tablestyle\(\)](#)

create_font	<i>Create font format</i>
-------------	---------------------------

Description

Create font format

Usage

```

create_font(
    b = "",
    charset = "",
    color = wb_color(hex = "FF000000"),
    condense = "",
    extend = "",
    family = "2",
    i = "",
    name = "Aptos Narrow",
    outline = "",
    scheme = "minor",
    shadow = "",
    strike = "",
    sz = "11",
    u = "",
    vert_align = "",
    ...
)

```

Arguments

b	bold
charset	charset
color	rgb color: default "FF000000"
condense	condense
extend	extend
family	font family: default "2"
i	italic
name	font name: default "Aptos Narrow"
outline	outline
scheme	font scheme: default "minor"
shadow	shadow
strike	strike
sz	font size: default "11",
u	underline
vert_align	vertical alignment
...	...

See Also

[wb_add_font\(\)](#)

Other style creating functions: [create_border\(\)](#), [create_cell_style\(\)](#), [create_colors_xml\(\)](#), [create_dxfs_style\(\)](#), [create_fill\(\)](#), [create_numfmt\(\)](#), [create_tablestyle\(\)](#)

Examples

```
font <- create_font()
# openxml has the alpha value leading
hex8 <- unlist(xml_attr(read_xml(font), "font", "color"))
hex8 <- paste0("#", substr(hex8, 3, 8), substr(hex8, 1, 2))

# # write test color
# col <- crayon::make_style(col2rgb(hex8, alpha = TRUE))
# cat(col("Test"))
```

create_hyperlink	<i>Create Excel hyperlink string</i>
------------------	--------------------------------------

Description

Wrapper to create internal hyperlink string to pass to `wb_add_formula()`. Either link to external URLs or local files or straight to cells of local Excel sheets.

Note that for an external URL, only `file` and `text` should be supplied. You can supply `dims` to `wb_add_formula()` to control the location of the link.

Usage

```
create_hyperlink(sheet, row = 1, col = 1, text = NULL, file = NULL)
```

Arguments

<code>sheet</code>	Name of a worksheet
<code>row</code>	integer row number for hyperlink to link to
<code>col</code>	column number of letter for hyperlink to link to
<code>text</code>	Display text
<code>file</code>	Hyperlink or Excel file name to point to. If NULL, hyperlink is internal.

Examples

```
wb <- wb_workbook()$
  add_worksheet("Sheet1")$add_worksheet("Sheet2")$add_worksheet("Sheet3")

## Internal Hyperlink - create hyperlink formula manually
x <- '=HYPERLINK("#Sheet2!B3", "Text to Display - Link to Sheet2")'
wb$add_formula(sheet = "Sheet1", x = x, dims = "A1")

## Internal - No text to display using create_hyperlink() function
x <- create_hyperlink(sheet = "Sheet3", row = 1, col = 2)
wb$add_formula(sheet = "Sheet1", x = x, dims = "A2")

## Internal - Text to display
x <- create_hyperlink(sheet = "Sheet3", row = 1, col = 2, text = "Link to Sheet 3")
```

```

wb$add_formula(sheet = "Sheet1", x = x, dims = "A3")

## Link to file - No text to display
fl <- system.file("extdata", "openxlsx2_example.xlsx", package = "openxlsx2")
x <- create_hyperlink(sheet = "Sheet1", row = 3, col = 10, file = fl)
wb$add_formula(sheet = "Sheet1", x = x, dims = "A4")

## Link to file - Text to display
fl <- system.file("extdata", "openxlsx2_example.xlsx", package = "openxlsx2")
x <- create_hyperlink(sheet = "Sheet2", row = 3, col = 10, file = fl, text = "Link to File.")
wb$add_formula(sheet = "Sheet1", x = x, dims = "A5")

## Link to external file - Text to display
x <- '=HYPERLINK("[C:/Users]", "Link to an external file")'
wb$add_formula(sheet = "Sheet1", x = x, dims = "A6")

x <- create_hyperlink(text = "test.png", file = "D:/somepath/somepicture.png")
wb$add_formula(x = x, dims = "A7")

## Link to an URL.
x <- create_hyperlink(text = "openxlsx2 website", file = "https://janmarvin.github.io/openxlsx2/")

wb$add_formula(x = x, dims = "A8")
# if (interactive()) wb$open()

```

create_numfmt

Create number format

Description

Create number format

Usage

```
create_numfmt(numFmtId, formatCode)
```

Arguments

numFmtId	an id, the list can be found in the Details of create_cell_style()
formatCode	a format code

See Also

[wb_add_numfmt\(\)](#)

Other style creating functions: [create_border\(\)](#), [create_cell_style\(\)](#), [create_colors_xml\(\)](#), [create_dxfs_style\(\)](#), [create_fill\(\)](#), [create_font\(\)](#), [create_tablestyle\(\)](#)

create_sparklines *Create sparklines object*

Description

Create a sparkline to be added a workbook with [wb_add_sparklines\(\)](#)

Usage

```
create_sparklines(
  sheet = current_sheet(),
  dims,
  sqref,
  type = NULL,
  negative = NULL,
  display_empty_cells_as = "gap",
  markers = NULL,
  high = NULL,
  low = NULL,
  first = NULL,
  last = NULL,
  color_series = wb_color(hex = "FF376092"),
  color_negative = wb_color(hex = "FFD00000"),
  color_axis = wb_color(hex = "FFD00000"),
  color_markers = wb_color(hex = "FFD00000"),
  color_first = wb_color(hex = "FFD00000"),
  color_last = wb_color(hex = "FFD00000"),
  color_high = wb_color(hex = "FFD00000"),
  color_low = wb_color(hex = "FFD00000"),
  manual_max = NULL,
  manual_min = NULL,
  line_weight = NULL,
  date_axis = NULL,
  display_x_axis = NULL,
  display_hidden = NULL,
  min_axis_type = NULL,
  max_axis_type = NULL,
  right_to_left = NULL,
  ...
)
```

Arguments

sheet	sheet
dims	Cell range of cells used to create the sparklines
sqref	Cell range of the destination of the sparklines.

type	Either NULL, stacked or column
negative	negative
display_empty_cells_as	Either gap, span or zero
markers	markers add marker to line
high	highlight highest value
low	highlight lowest value
first	highlight first value
last	highlight last value
color_series	colorSeries
color_negative	colorNegative
color_axis	colorAxis
color_markers	colorMarkers
color_first	colorFirst
color_last	colorLast
color_high	colorHigh
color_low	colorLow
manual_max	manualMax
manual_min	manualMin
line_weight	lineWeight
date_axis	dateAxis
display_x_axis	displayXAxis
display_hidden	displayHidden
min_axis_type	minAxisType
max_axis_type	maxAxisType
right_to_left	rightToLeft
...	additional arguments

Details

Colors are all predefined to be rgb. Maybe theme colors can be used too.

Value

A string containing XML code

Examples

```
# create sparklineGroup
sparklines <- c(
  create_sparklines("Sheet 1", "A3:L3", "M3", type = "column", first = "1"),
  create_sparklines("Sheet 1", "A2:L2", "M2", markers = "1"),
  create_sparklines("Sheet 1", "A4:L4", "M4", type = "stacked", negative = "1")
)

t1 <- AirPassengers
t2 <- do.call(cbind, split(t1, cycle(t1)))
dimnames(t2) <- dimnames(.preformat.ts(t1))

wb <- wb_workbook()$
  add_worksheet("Sheet 1")$
  add_data(x = t2)$
  add_sparklines(sparklines = sparklines)
```

create_tablestyle *Create custom (pivot) table styles*

Description

Create a custom (pivot) table style. These functions are for expert use only. Use other styling functions instead.

Usage

```
create_tablestyle(
  name,
  whole_table = NULL,
  header_row = NULL,
  total_row = NULL,
  first_column = NULL,
  last_column = NULL,
  first_row_stripe = NULL,
  second_row_stripe = NULL,
  first_column_stripe = NULL,
  second_column_stripe = NULL,
  first_header_cell = NULL,
  last_header_cell = NULL,
  first_total_cell = NULL,
  last_total_cell = NULL,
  ...
)

create_pivottablestyle(
  name,
```



```

whole_table = NULL,
header_row = NULL,
grand_total_row = NULL,
first_column = NULL,
grand_total_column = NULL,
first_row_stripe = NULL,
second_row_stripe = NULL,
first_column_stripe = NULL,
second_column_stripe = NULL,
first_header_cell = NULL,
first_subtotal_column = NULL,
second_subtotal_column = NULL,
third_subtotal_column = NULL,
first_subtotal_row = NULL,
second_subtotal_row = NULL,
third_subtotal_row = NULL,
blank_row = NULL,
first_column_subheading = NULL,
second_column_subheading = NULL,
third_column_subheading = NULL,
first_row_subheading = NULL,
second_row_subheading = NULL,
third_row_subheading = NULL,
page_field_labels = NULL,
page_field_values = NULL,
...
)

```

Arguments

name	name
whole_table	wholeTable
header_row, total_row	...Row
first_column, last_column	...Column
first_row_stripe, second_row_stripe	...RowStripe
first_column_stripe, second_column_stripe	...ColumnStripe
first_header_cell, last_header_cell	...HeaderCell
first_total_cell, last_total_cell	...TotalCell
...	additional arguments
grand_total_row	totalRow

```

grand_total_column
    lastColumn
first_subtotal_column, second_subtotal_column, third_subtotal_column
    ...SubtotalColumn
first_subtotal_row, second_subtotal_row, third_subtotal_row
    ...SubtotalRow
blank_row      blankRow
first_column_subheading, second_column_subheading, third_column_subheading
    ...ColumnSubheading
first_row_subheading, second_row_subheading, third_row_subheading
    ...RowSubheading
page_field_labels
    pageFieldLabels
page_field_values
    pageFieldValues

```

See Also

Other style creating functions: [create_border\(\)](#), [create_cell_style\(\)](#), [create_colors_xml\(\)](#), [create_dxfs_style\(\)](#), [create_fill\(\)](#), [create_font\(\)](#), [create_numfmt\(\)](#)

creators-wb

Modify creators of a workbook

Description

Modify and get workbook creators

Usage

```

wb_add_creators(wb, creators)

wb_set_creators(wb, creators)

wb_remove_creators(wb, creators)

wb_get_creators(wb)

```

Arguments

wb	A wbWorkbook object
creators	A character vector of names

Value

- `wb_set_creators()`, `wb_add_creators()`, and `wb_remove_creators()` return the wbWorkbook object
- `wb_get_creators()` returns a character vector of creators

See Also

Other workbook wrappers: [base_font-wb](#), [col_widths-wb](#), [grouping-wb](#), [row_heights-wb](#), [wb_add_chartsheet\(\)](#), [wb_add_data\(\)](#), [wb_add_data_table\(\)](#), [wb_add_formula\(\)](#), [wb_add_pivot_table\(\)](#), [wb_add_slicer\(\)](#), [wb_add_worksheet\(\)](#), [wb_base_colors](#), [wb_clone_worksheet\(\)](#), [wb_copy_cells\(\)](#), [wb_freeze_pane\(\)](#), [wb_merge_cells\(\)](#), [wb_save\(\)](#), [wb_set_last_modified_by\(\)](#), [wb_workbook\(\)](#)

Examples

```
# workbook made with default creator (see [wbWorkbook])
wb <- wb_workbook()
wb_get_creators(wb)

# add a new creator (assuming "test" isn't your default creator)
wb <- wb_add_creators(wb, "test")
wb_get_creators(wb)

# remove the creator (should be the same as before)
wb <- wb_remove_creators(wb, "test")
wb_get_creators(wb)
```

 dims_helper

Helper functions to work with dims

Description

Internal helpers to (de)construct a dims argument from/to a row and column vector. Exported for user convenience.

Usage

```
dims_to_rowcol(x, as_integer = FALSE)

rowcol_to_dims(row, col, single = TRUE)
```

Arguments

x	a dimension object "A1" or "A1:A1"
as_integer	If the output should be returned as integer, (defaults to string)
row	a numeric vector of rows
col	a numeric or character vector of cols
single	argument indicating if rowcol_to_dims() returns a single cell dimension

Value

- A dims string for `_to_dim` i.e "A1:A1"
- A list of rows and columns for `to_rowcol`

See Also[wb_dims\(\)](#)**Examples**

```
dims_to_rowcol("A1:J10")
wb_dims(1:10, 1:10)
```

 filter-wb

Add/remove column filters in a worksheet

Description

Add or remove excel column filters to a worksheet

Usage

```
wb_add_filter(wb, sheet = current_sheet(), rows, cols)
```

```
wb_remove_filter(wb, sheet = current_sheet())
```

Arguments

wb	A workbook object
sheet	A worksheet name or index. In <code>wb_remove_filter()</code> , you may supply a vector of worksheets.
rows	A row number.
cols	columns to add filter to.

Details

Adds filters to worksheet columns, same as `with_filter = TRUE` in [wb_add_data\(\)](#) [wb_add_data_table\(\)](#) automatically adds filters to first row of a table.

NOTE Can only have a single filter per worksheet unless using tables.

See Also

[wb_add_data\(\)](#), [wb_add_data_table\(\)](#)

Other worksheet content functions: [col_widths-wb](#), [grouping-wb](#), [named_region-wb](#), [row_heights-wb](#), [wb_add_conditional_formatting\(\)](#), [wb_add_data\(\)](#), [wb_add_data_table\(\)](#), [wb_add_formula\(\)](#), [wb_add_pivot_table\(\)](#), [wb_add slicer\(\)](#), [wb_add_thread\(\)](#), [wb_freeze_pane\(\)](#), [wb_merge_cells\(\)](#)

Examples

```
wb <- wb_workbook()
wb$add_worksheet("Sheet 1")
wb$add_worksheet("Sheet 2")
wb$add_worksheet("Sheet 3")

wb$add_data(1, iris)
wb$add_filter(1, row = 1, cols = seq_along(iris))

## Equivalently
wb$add_data(2, x = iris, with_filter = TRUE)

## Similarly
wb$add_data_table(3, iris)
wb <- wb_workbook()
wb$add_worksheet("Sheet 1")
wb$add_worksheet("Sheet 2")
wb$add_worksheet("Sheet 3")

wb$add_data(1, iris)
wb_add_filter(wb, 1, row = 1, cols = seq_along(iris))

## Equivalently
wb$add_data(2, x = iris, with_filter = TRUE)

## Similarly
wb$add_data_table(3, iris)

## remove filters
wb_remove_filter(wb, 1:2) ## remove filters
wb_remove_filter(wb, 3) ## Does not affect tables!
```

fmt_txt

format strings independent of the cell style.

Description

format strings independent of the cell style.

Usage

```
fmt_txt(  
  x,  
  bold = FALSE,  
  italic = FALSE,  
  underline = FALSE,  
  strike = FALSE,  
  size = NULL,  
  color = NULL,
```

```

    font = NULL,
    charset = NULL,
    outline = NULL,
    vert_align = NULL
)

## S3 method for class 'fmt_txt'
x + y

## S3 method for class 'fmt_txt'
as.character(x, ...)

## S3 method for class 'fmt_txt'
print(x, ...)

```

Arguments

x, y	an openxlsx2 fmt_txt string
bold	bold
italic	italic
underline	underline
strike	strike
size	the font size
color	a wbColor color for the font
font	the font name
charset	integer value from the table below
outline	TRUE or FALSE
vert_align	baseline, superscript, or subscript
...	additional arguments for default print

Details

The result is an xml string. It is possible to paste multiple `fmt_txt()` strings together to create a string with differing styles.

Using `fmt_txt(charset = 161)` will give the Greek Character Set

charset	"Character Set"
0	"ANSI_CHARSET"
1	"DEFAULT_CHARSET"
2	"SYMBOL_CHARSET"
77	"MAC_CHARSET"
128	"SHIFTJIS_CHARSET"
129	"HANGUL_CHARSET"
130	"JOHAB_CHARSET"
134	"GB2312_CHARSET"

```

136 "CHINESEBIG5_CHARSET"
161 "GREEK_CHARSET"
162 "TURKISH_CHARSET"
163 "VIETNAMESE_CHARSET"
177 "HEBREW_CHARSET"
178 "ARABIC_CHARSET"
186 "BALTIC_CHARSET"
204 "RUSSIAN_CHARSET"
222 "THAI_CHARSET"
238 "EASTEUROPE_CHARSET"
255 "OEM_CHARSET"

```

You can join additional objects into `fmt_txt()` objects using "+". Though be aware that `fmt_txt("sum:") + 2 + 2` is different to `fmt_txt("sum:") + 2 + 2`.

Examples

```

fmt_txt("bar", underline = TRUE)
fmt_txt("foo ", bold = TRUE) + fmt_txt("bar")
as.character(fmt_txt(2))

```

grouping-wb

Group rows and columns in a worksheet

Description

Group a selection of rows or cols

Usage

```

wb_group_cols(
  wb,
  sheet = current_sheet(),
  cols,
  collapsed = FALSE,
  levels = NULL
)

```

```

wb_ungroup_cols(wb, sheet = current_sheet(), cols)

```

```

wb_group_rows(
  wb,
  sheet = current_sheet(),
  rows,
  collapsed = FALSE,
  levels = NULL
)

```

```
)
wb_ungroup_rows(wb, sheet = current_sheet(), rows)
```

Arguments

wb	A wbWorkbook object
sheet	A name or index of a worksheet
collapsed	If TRUE the grouped columns are collapsed
levels	levels
rows, cols	Indices of rows and columns to group

Details

If row was previously hidden, it will now be shown.

See Also

Other workbook wrappers: [base_font-wb](#), [col_widths-wb](#), [creators-wb](#), [row_heights-wb](#), [wb_add_chartsheet\(\)](#), [wb_add_data\(\)](#), [wb_add_data_table\(\)](#), [wb_add_formula\(\)](#), [wb_add_pivot_table\(\)](#), [wb_add slicer\(\)](#), [wb_add_worksheet\(\)](#), [wb_base_colors](#), [wb_clone_worksheet\(\)](#), [wb_copy_cells\(\)](#), [wb_freeze_pane\(\)](#), [wb_merge_cells\(\)](#), [wb_save\(\)](#), [wb_set_last_modified_by\(\)](#), [wb_workbook\(\)](#)

Other worksheet content functions: [col_widths-wb](#), [filter-wb](#), [named_region-wb](#), [row_heights-wb](#), [wb_add_conditional_formatting\(\)](#), [wb_add_data\(\)](#), [wb_add_data_table\(\)](#), [wb_add_formula\(\)](#), [wb_add_pivot_table\(\)](#), [wb_add slicer\(\)](#), [wb_add_thread\(\)](#), [wb_freeze_pane\(\)](#), [wb_merge_cells\(\)](#)

Other workbook wrappers: [base_font-wb](#), [col_widths-wb](#), [creators-wb](#), [row_heights-wb](#), [wb_add_chartsheet\(\)](#), [wb_add_data\(\)](#), [wb_add_data_table\(\)](#), [wb_add_formula\(\)](#), [wb_add_pivot_table\(\)](#), [wb_add slicer\(\)](#), [wb_add_worksheet\(\)](#), [wb_base_colors](#), [wb_clone_worksheet\(\)](#), [wb_copy_cells\(\)](#), [wb_freeze_pane\(\)](#), [wb_merge_cells\(\)](#), [wb_save\(\)](#), [wb_set_last_modified_by\(\)](#), [wb_workbook\(\)](#)

Examples

```
# create matrix
t1 <- AirPassengers
t2 <- do.call(cbind, split(t1, cycle(t1)))
dimnames(t2) <- dimnames(.preformat.ts(t1))

wb <- wb_workbook()
wb$add_worksheet("AirPass")
wb$add_data("AirPass", t2, row_names = TRUE)

# groups will always end on/show the last row. in the example 1950, 1955, and 1960
wb <- wb_group_rows(wb, "AirPass", 2:3, collapsed = TRUE) # group years < 1950
wb <- wb_group_rows(wb, "AirPass", 4:8, collapsed = TRUE) # group years 1951-1955
wb <- wb_group_rows(wb, "AirPass", 9:13) # group years 1956-1960

wb <- wb_group_cols(wb, "AirPass", 2:4, collapsed = TRUE)
wb <- wb_group_cols(wb, "AirPass", 5:7, collapsed = TRUE)
wb <- wb_group_cols(wb, "AirPass", 8:10, collapsed = TRUE)
```



```
wb <- wb_group_cols(wb, "AirPass", 11:13)

### create grouping levels
grp_rows <- list(
  "1" = seq(2, 3),
  "2" = seq(4, 8),
  "3" = seq(9, 13)
)

grp_cols <- list(
  "1" = seq(2, 4),
  "2" = seq(5, 7),
  "3" = seq(8, 10),
  "4" = seq(11, 13)
)

wb <- wb_workbook()
wb$add_worksheet("AirPass")
wb$add_data("AirPass", t2, row_names = TRUE)

wb$group_cols("AirPass", cols = grp_cols)
wb$group_rows("AirPass", rows = grp_rows)
```

int2col

Convert integer to Excel column

Description

Converts an integer to an Excel column label.

Usage

```
int2col(x)
```

Arguments

x A numeric vector.

Examples

```
int2col(1:10)
```

named_region-wb	<i>Modify named regions in a worksheet</i>
-----------------	--

Description

Create / delete a named region. You can also specify a named region by using the name argument in `wb_add_data(x = iris, name = "my-region")`. It is important to note that named regions are not case-sensitive and must be unique.

Usage

```
wb_add_named_region(
  wb,
  sheet = current_sheet(),
  dims = "A1",
  name,
  local_sheet = FALSE,
  overwrite = FALSE,
  comment = NULL,
  hidden = NULL,
  custom_menu = NULL,
  description = NULL,
  is_function = NULL,
  function_group_id = NULL,
  help = NULL,
  local_name = NULL,
  publish_to_server = NULL,
  status_bar = NULL,
  vb_procedure = NULL,
  workbook_parameter = NULL,
  xml = NULL,
  ...
)

wb_remove_named_region(wb, sheet = current_sheet(), name = NULL)

wb_get_named_regions(wb, tables = FALSE, x = NULL)
```

Arguments

<code>wb</code>	A Workbook object
<code>sheet</code>	A name or index of a worksheet
<code>dims</code>	Worksheet cell range of the region ("A1:D4").
<code>name</code>	Name for region. A character vector of length 1. Note that region names must be case-insensitive unique.
<code>local_sheet</code>	If TRUE the named region will be local for this sheet

overwrite	Boolean. Overwrite if exists? Default to FALSE.
comment	description text for named region
hidden	Should the named region be hidden?
custom_menu, description, is_function, function_group_id, help, local_name, publish_to_server, status_b	Unknown XML feature
...	additional arguments
tables	Should included both data tables and named regions in the result?
x	Deprecated. Use wb. For Excel input use <code>wb_load()</code> to first load the xlsx file as a workbook.

Details

You can use the `wb_dims()` helper to specify the cell range of the named region

Value

A workbook, invisibly.

A data frame with the all named regions in wb. Or NULL, if none are found.

See Also

`wb_get_tables()`

Other worksheet content functions: `col_widths-wb`, `filter-wb`, `grouping-wb`, `row_heights-wb`, `wb_add_conditional_formatting()`, `wb_add_data()`, `wb_add_data_table()`, `wb_add_formula()`, `wb_add_pivot_table()`, `wb_add slicer()`, `wb_add_thread()`, `wb_freeze_pane()`, `wb_merge_cells()`

Examples

```
## create named regions
wb <- wb_workbook()
wb$add_worksheet("Sheet 1")

## specify region
wb$add_data(x = iris, start_col = 1, start_row = 1)
wb$add_named_region(
  name = "iris",
  dims = wb_dims(x = iris)
)

## using add_data 'name' argument
wb$add_data(sheet = 1, x = iris, name = "iris2", start_col = 10)

## delete one
wb$remove_named_region(name = "iris2")
wb$get_named_regions()
## read named regions
df <- wb_to_df(wb, named_region = "iris")
head(df)
```

```
# Extract named regions from a file
out_file <- temp_xlsx()
wb_save(wb, out_file, overwrite = TRUE)

# Load the file as a workbook first, then get named regions.
wb1 <- wb_load(out_file)
wb1$get_named_regions()
```

openxlsx2-deprecated *Deprecated functions in package openxlsx2*

Description

These functions are provided for compatibility with older versions of openxlsx2, and may be de-funct as soon as the next release. This guide helps you update your code to the latest standards.

As of openxlsx2 v1.0, API change should be minimal.

Internal functions

These functions are used internally by openxlsx2. It is no longer advertised to use them in scripts. They originate from openxlsx, but do not fit openxlsx2's API.

You should be able to modify

- `delete_data()` -> `wb_clean_sheet()`
- `write_data()` -> `wb_add_data()`
- `write_datatable()` -> `wb_add_data_table()`
- `write_comment()` -> `wb_add_comment()`
- `remove_comment()` -> `wb_remove_comment()`
- `write_formula()` -> `wb_add_formula()`

You should be able to change those with minimal changes

Deprecated functions

First of all, you can set an option that will add warnings when using deprecated functions.

```
options("openxlsx2.soon_deprecated" = TRUE)
```

Argument changes

For consistency, arguments were renamed to snake_case for the 0.8 release. It is now recommended to use `dims` (the cell range) in favor of `row`, `col`, `start_row`, `start_col`

See `wb_dims()` as it provides many options on how to provide cell range

Functions with a new name

These functions were renamed for consistency.

- `convertToExcelDate()` -> `convert_to_excel_date()`
- `wb_grid_lines()` -> `wb_set_grid_lines()`
- `create_comment()` -> `wb_comment()`

Deprecated usage

- `wb_get_named_regions()` will no longer allow providing a file.

```
## Before
wb_get_named_regions(file)

## Now
wb <- wb_load(file)
wb_get_named_regions(wb)
# also possible
wb_load(file)$get_named_regions()`
```

See Also

[.Deprecated](#)

openxlsx2_options *Options consulted by openxlsx2*

Description

The openxlsx2 package allows the user to set global options to simplify formatting:

If the built-in defaults don't suit you, set one or more of these options. Typically, this is done in the .Rprofile startup file

- `options("openxlsx2.borderColor" = "black")`
- `options("openxlsx2.borderStyle" = "thin")`
- `options("openxlsx2.dateFormat" = "mm/dd/yyyy")`
- `options("openxlsx2.datetimeFormat" = "yyyy-mm-dd hh:mm:ss")`
- `options("openxlsx2.maxWidth" = NULL)` (Maximum width allowed in Excel is 250)
- `options("openxlsx2.minWidth" = NULL)`
- `options("openxlsx2.numFmt" = NULL)`
- `options("openxlsx2.paperSize" = 9)` corresponds to a A4 paper size
- `options("openxlsx2.orientation" = "portrait")` page orientation
- `options("openxlsx2.sheet.default_name" = "Sheet")`

- `options("openxlsx2.rightToLeft" = NULL)`
- `options("openxlsx2.soon_deprecated" = FALSE)` Set to TRUE if you want a warning if using some functions deprecated recently in openxlsx2
- `options("openxlsx2.creator")` A default name for the creator of new `wbWorkbook` object with `wb_workbook()` or new comments with `wb_add_comment()`
- `options("openxlsx2.thread_id")` the default person id when adding a threaded comment to a cell with `wb_add_thread()`
- `options("openxlsx2.accountingFormat" = 4)`
- `options("openxlsx2.currencyFormat" = 4)`
- `options("openxlsx2.commaFormat" = 3)`
- `options("openxlsx2.percentageFormat" = 10)`
- `options("openxlsx2.scientificFormat" = 48)`
- `options("openxlsx2.string_nums" = TRUE)` numerics in character columns will be converted. "1" will be written as 1
- `options("openxlsx2.na.strings" = "#N/A")` consulted by `write_xlsx()`, `wb_add_data()` and `wb_add_data_table()`.

 person-wb

Helper for adding threaded comments

Description

Adds a person to a workbook, so that they can be the author of threaded comments in a workbook with `wb_add_thread()`

Usage

```
wb_add_person(wb, name = NULL, id = NULL, user_id = NULL, provider_id = "None")
```

```
wb_get_person(wb, name = NULL)
```

Arguments

<code>wb</code>	a Workbook
<code>name</code>	the name of the person to display.
<code>id</code>	(optional) the display id
<code>user_id</code>	(optional) the user id
<code>provider_id</code>	(optional) the provider id

See Also

[wb_add_thread\(\)](#)

```
print.pugi_xml      print pugi_xml
```

Description

```
print pugi_xml
```

Usage

```
## S3 method for class 'pugi_xml'
print(x, indent = " ", raw = FALSE, attr_indent = FALSE, ...)
```

Arguments

x	something to print
indent	indent used default is " "
raw	print as raw text
attr_indent	print attributes indented on new line
...	to please check

Examples

```
# a pointer
x <- read_xml("<a><b/></a>")
print(x)
print(x, raw = TRUE)
```

```
properties-wb      Modify workbook properties
```

Description

This function is useful for workbooks that are loaded. It can be used to set the workbook title, subject and category field. Use [wb_workbook\(\)](#) to easily set these properties with a new workbook.

Usage

```
wb_get_properties(wb)
```

```
wb_set_properties(
  wb,
  creator = NULL,
  title = NULL,
  subject = NULL,
```

```

category = NULL,
datetime_created = Sys.time(),
modifier = NULL,
keywords = NULL,
comments = NULL,
manager = NULL,
company = NULL,
custom = NULL
)

```

Arguments

<code>wb</code>	A Workbook object
<code>creator</code>	Creator of the workbook (your name). Defaults to login username or <code>options("openxlsx2.creator")</code> if set.
<code>title</code> , <code>subject</code> , <code>category</code> , <code>keywords</code> , <code>comments</code> , <code>manager</code> , <code>company</code>	Workbook property, a string.
<code>datetime_created</code>	The time of the workbook is created
<code>modifier</code>	A character string indicating who was the last person to modify the workbook
<code>custom</code>	A named vector of custom properties added to the workbook

Details

To set properties, the following XML core properties are used.

- `title = dc:title`
- `subject = dc:subject`
- `creator = dc:creator`
- `keywords = cp:keywords`
- `comments = dc:description`
- `modifier = cp:lastModifiedBy`
- `datetime_created = dcterms:created`
- `datetime_modified = dcterms:modified`
- `category = cp:category`

In addition, `manager` and `company` are used.

Value

A `wbWorkbook` object, invisibly.

See Also

[wb_workbook\(\)](#)

Examples

```

file <- system.file("extdata", "openxlsx2_example.xlsx", package = "openxlsx2")
wb <- wb_load(file)
wb$get_properties()

# Add a title to properties
wb$set_properties(title = "my title")
wb$get_properties()

```

pugixml	<i>xml_node</i>
---------	-----------------

Description

returns xml values as character

Usage

```

xml_node(xml, level1 = NULL, level2 = NULL, level3 = NULL, ...)

xml_node_name(xml, level1 = NULL, level2 = NULL, ...)

xml_value(xml, level1 = NULL, level2 = NULL, level3 = NULL, ...)

xml_attr(xml, level1 = NULL, level2 = NULL, level3 = NULL, ...)

```

Arguments

xml	something xml
level1	to please check
level2	to please check
level3	to please check
...	additional arguments passed to read_xml()

Details

This function returns XML nodes as used in openxlsx2. In theory they could be returned as pointers as well, but this has not yet been implemented. If no level is provided, the nodes on level1 are returned

Examples

```

x <- read_xml("<a><b/></a>")
# return a
xml_node(x, "a")
# return b. requires the path to the node
xml_node(x, "a", "b")

```

```

xml_node_name("<a/>")
xml_node_name("<a><b/></a>", "a")
x <- read_xml("<a>1</a>")
xml_value(x, "a")

x <- read_xml("<a><b r='1'>2</b></a>")
xml_value(x, "a", "b")

x <- read_xml("<a a='1' b='2'>1</a>")
xml_attr(x, "a")

x <- read_xml("<a><b r='1'>2</b></a>")
xml_attr(x, "a", "b")
x <- read_xml("<a a='1' b='2'>1</a>")
xml_attr(x, "a")

x <- read_xml("<b><a a='1' b='2'></b>")
xml_attr(x, "b", "a")

```

read_xml

read xml file

Description

read xml file

Usage

```

read_xml(
  xml,
  pointer = TRUE,
  escapes = FALSE,
  declaration = FALSE,
  whitespace = TRUE,
  empty_tags = FALSE,
  skip_control = TRUE
)

```

Arguments

xml	something to read character string or file
pointer	should a pointer be returned?
escapes	bool if characters like "&" should be escaped. The default is no escapes. Assuming that the input already provides valid information.
declaration	should the declaration be imported
whitespace	should whitespace pcdeta be imported
empty_tags	should or be returned
skip_control	should whitespace character be exported

Details

Read xml files or strings to pointer and checks if the input is valid XML. If the input is read into a character object, it will be reevaluated every time it is called. A pointer is evaluated once, but lives only for the lifetime of the R session or once it is gc().

Examples

```
# a pointer
x <- read_xml("<a><b/></a>")
print(x)
print(x, raw = TRUE)
str(x)

# a character
y <- read_xml("<a><b/></a>", pointer = FALSE)
print(y)
print(y, raw = TRUE)
str(y)

# Errors if the import was unsuccessful
try(z <- read_xml("<a><b/>"))

xml <- '<?xml test="yay" ?><a>A & B</a>'
# difference in escapes
read_xml(xml, escapes = TRUE, pointer = FALSE)
read_xml(xml, escapes = FALSE, pointer = FALSE)
read_xml(xml, escapes = TRUE)
read_xml(xml, escapes = FALSE)

# read declaration
read_xml(xml, declaration = TRUE)
```

row_heights-wb

Modify row heights of a worksheet

Description

Set / remove custom worksheet row heights

Usage

```
wb_set_row_heights(
  wb,
  sheet = current_sheet(),
  rows,
  heights = NULL,
  hidden = FALSE
)
```

```
wb_remove_row_heights(wb, sheet = current_sheet(), rows)
```

Arguments

wb	A wbWorkbook object
sheet	A name or index of a worksheet. (A vector is accepted for <code>remove_row_heights()</code>)
rows	Indices of rows to set / remove (if any) custom height.
heights	Heights to set rows to specified in a spreadsheet column height units.
hidden	Option to hide rows. A logical vector of length 1 or length of rows

See Also

Other workbook wrappers: [base_font-wb](#), [col_widths-wb](#), [creators-wb](#), [grouping-wb](#), [wb_add_chartsheet\(\)](#), [wb_add_data\(\)](#), [wb_add_data_table\(\)](#), [wb_add_formula\(\)](#), [wb_add_pivot_table\(\)](#), [wb_add_slicer\(\)](#), [wb_add_worksheet\(\)](#), [wb_base_colors](#), [wb_clone_worksheet\(\)](#), [wb_copy_cells\(\)](#), [wb_freeze_pane\(\)](#), [wb_merge_cells\(\)](#), [wb_save\(\)](#), [wb_set_last_modified_by\(\)](#), [wb_workbook\(\)](#)

Other worksheet content functions: [col_widths-wb](#), [filter-wb](#), [grouping-wb](#), [named_region-wb](#), [wb_add_conditional_formatting\(\)](#), [wb_add_data\(\)](#), [wb_add_data_table\(\)](#), [wb_add_formula\(\)](#), [wb_add_pivot_table\(\)](#), [wb_add_slicer\(\)](#), [wb_add_thread\(\)](#), [wb_freeze_pane\(\)](#), [wb_merge_cells\(\)](#)

Examples

```
## Create a new workbook
wb <- wb_workbook()

## Add a worksheet
wb$add_worksheet("Sheet 1")

## set row heights
wb <- wb_set_row_heights(
  wb, 1,
  rows = c(1, 4, 22, 2, 19),
  heights = c(24, 28, 32, 42, 33)
)

## overwrite row 1 height
wb <- wb_set_row_heights(wb, 1, rows = 1, heights = 40)
## remove any custom row heights in row 1
wb$remove_row_heights(sheet = 1, rows = 1)
```

sheet_names-wb

Get / Set worksheet names for a workbook

Description

Gets / Sets the worksheet names for a [wbWorkbook](#) object.

Usage

```
wb_set_sheet_names(wb, old = NULL, new)
```

```
wb_get_sheet_names(wb, escape = FALSE)
```

Arguments

wb	A wbWorkbook object
old	The name (or index) of the old sheet name. If NULL will assume all worksheets are to be renamed.
new	The name of the new sheet
escape	Should the xml special characters be escaped?

Details

This only changes the sheet name as shown in spreadsheet software and will not alter it elsewhere. Not in formulas, chart references, named regions, pivot tables or anywhere else.

Value

- `set_`: The `wbWorkbook` object.
- `get_`: A named character vector of sheet names in order. The names represent the original value of the worksheet prior to any character substitutions.

sheet_visibility-wb *Get/set worksheet visible state in a workbook*

Description

Get and set worksheet visible state. This allows to hide worksheets from the workbook. The visibility of a worksheet can either be "visible", "hidden", or "veryHidden". You can set this when creating a worksheet with `wb_add_worksheet(visible = FALSE)`

Usage

```
wb_get_sheet_visibility(wb)
```

```
wb_set_sheet_visibility(wb, sheet = current_sheet(), value)
```

Arguments

wb	A <code>wbWorkbook</code> object
sheet	Worksheet identifier
value	a logical/character vector the same length as <code>sheet</code> , if providing a character vector, you can provide any of "hidden", "visible", or "veryHidden"

Value

- `wb_set_sheet_visibility`: The Workbook object, invisibly.
- `wb_get_sheet_visibility()`: A character vector of the worksheet visibility value

Examples

```
wb <- wb_workbook()
wb$add_worksheet(sheet = "S1", visible = FALSE)
wb$add_worksheet(sheet = "S2", visible = TRUE)
wb$add_worksheet(sheet = "S3", visible = FALSE)

wb$get_sheet_visibility()
wb$set_sheet_visibility(1, TRUE)      ## show sheet 1
wb$set_sheet_visibility(2, FALSE)    ## hide sheet 2
wb$set_sheet_visibility(3, "hidden") ## hide sheet 3
wb$set_sheet_visibility(3, "veryHidden") ## hide sheet 3 from UI
```

`styles_on_sheet` *Get all styles on a sheet*

Description

Get all styles on a sheet

Usage

```
styles_on_sheet(wb, sheet)
```

Arguments

<code>wb</code>	workbook
<code>sheet</code>	worksheet

`temp_xlsx` *helper function to create temporary directory for testing purpose*

Description

helper function to create temporary directory for testing purpose

Usage

```
temp_xlsx(name = "temp_xlsx", macros = FALSE)
```

Arguments

name	for the temp file
macros	logical if the file extension is xlsx or xlsm

waivers	<code>openxlsx2 waivers</code>
---------	--------------------------------

Description

Waiver functions for openxlsx2 functions.

- `current_sheet()` uses `wb_get_active_sheet()` by default if performing actions on a worksheet, for example when you add data.
- `next_sheet()` is used when you add a new worksheet, a new chartsheet or when you add a pivot table

Usage

```
current_sheet()
```

```
next_sheet()
```

```
na_strings()
```

Value

An object of class `openxlsx2_waiver`

wbWorkbook	<i>Workbook class</i>
------------	-----------------------

Description

This is the class used by openxlsx2 to modify workbooks from R. You can load an existing workbook with `wb_load()` and create a new one with `wb_workbook()`.

After that, you can modify the `wbWorkbook` object through two primary methods:

Wrapper Function Method: Utilizes the `wb` family of functions that support piping to streamline operations.

```
wb <- wb_workbook(creator = "My name here") %>%
  wb_add_worksheet(sheet = "Expenditure", grid_lines = FALSE) %>%
  wb_add_data(x = USPersonalExpenditure, row_names = TRUE)
```

Chaining Method: Directly modifies the object through a series of chained function calls.

```
wb <- wb_workbook(creator = "My name here")$
  add_worksheet(sheet = "Expenditure", grid_lines = FALSE)$
  add_data(x = USPersonalExpenditure, row_names = TRUE)
```

While wrapper functions require explicit assignment of their output to reflect changes, chained functions inherently modify the input object. Both approaches are equally supported, offering flexibility to suit user preferences. The documentation mainly highlights the use of wrapper functions.

```
# Import workbooks
path <- system.file("extdata/openxlsx2_example.xlsx", package = "openxlsx2")
wb <- wb_load(path)

## or create one yourself
wb <- wb_workbook()
# add a worksheet
wb$add_worksheet("sheet")
# add some data
wb$add_data("sheet", cars)
# Add data with piping in a different location
wb <- wb %>% wb_add_data(x = cars, dims = wb_dims(from_dims = "D4"))
# open it in your default spreadsheet software
if (interactive()) wb$open()
```

Note that the documentation is more complete in each of the wrapper functions. (i.e. `?wb_add_data` rather than `?wbWorkbook`).

Public fields

```
sheet_names The names of the sheets
calcChain calcChain
charts charts
is_chartsheet A logical vector identifying if a sheet is a chartsheet.
customXml customXml
connections connections
ctrlProps ctrlProps
Content_Types Content_Types
app app
core The XML core
custom custom
drawings drawings
drawings_rels drawings_rels
embeddings embeddings
externalLinks externalLinks
externalLinksRels externalLinksRels
```


headFoot The header and footer
media media
metadata contains cell/value metadata imported on load from xl/metadata.xml
persons Persons of the workbook. to be used with [wb_add_thread\(\)](#)
pivotTables pivotTables
pivotTables.xml.rels pivotTables.xml.rels
pivotDefinitions pivotDefinitions
pivotRecords pivotRecords
pivotDefinitionsRels pivotDefinitionsRels
queryTables queryTables
richData richData
slicers slicers
slicerCaches slicerCaches
sharedStrings sharedStrings
styles_mgr styles_mgr
tables tables
tables.xml.rels tables.xml.rels
theme theme
vbaProject vbaProject
vml vml
vml_rels vml_rels
comments Comments (notes) present in the workbook.
threadComments Threaded comments
workbook workbook
workbook.xml.rels workbook.xml.rels
worksheets worksheets
worksheets_rels worksheets_rels
sheetOrder The sheet order. Controls ordering for worksheets and worksheet names.
path path

Methods

Public methods:

- [wbWorkbook\\$new\(\)](#)
- [wbWorkbook\\$append\(\)](#)
- [wbWorkbook\\$append_sheets\(\)](#)
- [wbWorkbook\\$validate_sheet\(\)](#)
- [wbWorkbook\\$add_chartsheet\(\)](#)
- [wbWorkbook\\$add_worksheet\(\)](#)

- `wbWorkbook$clone_worksheet()`
- `wbWorkbook$add_data()`
- `wbWorkbook$add_data_table()`
- `wbWorkbook$add_pivot_table()`
- `wbWorkbook$add_slicer()`
- `wbWorkbook$add_formula()`
- `wbWorkbook$add_style()`
- `wbWorkbook$to_df()`
- `wbWorkbook$load()`
- `wbWorkbook$save()`
- `wbWorkbook$open()`
- `wbWorkbook$buildTable()`
- `wbWorkbook$update_table()`
- `wbWorkbook$copy_cells()`
- `wbWorkbook$get_base_font()`
- `wbWorkbook$set_base_font()`
- `wbWorkbook$get_base_colors()`
- `wbWorkbook$get_base_colours()`
- `wbWorkbook$set_base_colors()`
- `wbWorkbook$set_base_colours()`
- `wbWorkbook$set_bookview()`
- `wbWorkbook$get_sheet_names()`
- `wbWorkbook$set_sheet_names()`
- `wbWorkbook$set_row_heights()`
- `wbWorkbook$remove_row_heights()`
- `wbWorkbook$createCols()`
- `wbWorkbook$group_cols()`
- `wbWorkbook$ungroup_cols()`
- `wbWorkbook$remove_col_widths()`
- `wbWorkbook$set_col_widths()`
- `wbWorkbook$group_rows()`
- `wbWorkbook$ungroup_rows()`
- `wbWorkbook$remove_worksheet()`
- `wbWorkbook$add_data_validation()`
- `wbWorkbook$merge_cells()`
- `wbWorkbook$unmerge_cells()`
- `wbWorkbook$freeze_pane()`
- `wbWorkbook$add_comment()`
- `wbWorkbook$get_comment()`
- `wbWorkbook$remove_comment()`
- `wbWorkbook$add_thread()`
- `wbWorkbook$get_thread()`

- wbWorkbook\$add_conditional_formatting()
- wbWorkbook\$add_image()
- wbWorkbook\$add_plot()
- wbWorkbook\$add_drawing()
- wbWorkbook\$add_chart_xml()
- wbWorkbook\$add_mschart()
- wbWorkbook\$add_form_control()
- wbWorkbook\$print()
- wbWorkbook\$protect()
- wbWorkbook\$protect_worksheet()
- wbWorkbook\$get_properties()
- wbWorkbook\$set_properties()
- wbWorkbook\$add_mips()
- wbWorkbook\$get_mips()
- wbWorkbook\$set_creators()
- wbWorkbook\$add_creators()
- wbWorkbook\$remove_creators()
- wbWorkbook\$set_last_modified_by()
- wbWorkbook\$set_page_setup()
- wbWorkbook\$page_setup()
- wbWorkbook\$set_header_footer()
- wbWorkbook\$get_tables()
- wbWorkbook\$remove_tables()
- wbWorkbook\$add_filter()
- wbWorkbook\$remove_filter()
- wbWorkbook\$set_grid_lines()
- wbWorkbook\$grid_lines()
- wbWorkbook\$add_named_region()
- wbWorkbook\$get_named_regions()
- wbWorkbook\$remove_named_region()
- wbWorkbook\$set_order()
- wbWorkbook\$get_sheet_visibility()
- wbWorkbook\$set_sheet_visibility()
- wbWorkbook\$add_page_break()
- wbWorkbook\$clean_sheet()
- wbWorkbook\$add_border()
- wbWorkbook\$add_fill()
- wbWorkbook\$add_font()
- wbWorkbook\$add_numfmt()
- wbWorkbook\$add_cell_style()
- wbWorkbook\$get_cell_style()
- wbWorkbook\$set_cell_style()

- `wbWorkbook$set_cell_style_across()`
- `wbWorkbook$add_named_style()`
- `wbWorkbook$add_dxfs_style()`
- `wbWorkbook$clone_sheet_style()`
- `wbWorkbook$add_sparklines()`
- `wbWorkbook$add_ignore_error()`
- `wbWorkbook$set_sheetview()`
- `wbWorkbook$add_person()`
- `wbWorkbook$get_person()`
- `wbWorkbook$get_active_sheet()`
- `wbWorkbook$set_active_sheet()`
- `wbWorkbook$get_selected()`
- `wbWorkbook$set_selected()`
- `wbWorkbook$clone()`

Method `new()`: Creates a new `wbWorkbook` object

Usage:

```
wbWorkbook$new(
  creator = NULL,
  title = NULL,
  subject = NULL,
  category = NULL,
  datetime_created = Sys.time(),
  theme = NULL,
  keywords = NULL,
  comments = NULL,
  manager = NULL,
  company = NULL,
  ...
)
```

Arguments:

`creator` character vector of creators. Duplicated are ignored.

`title`, `subject`, `category`, `keywords`, `comments`, `manager`, `company` workbook properties

`datetime_created` The datetime (as POSIXt) the workbook is created. Defaults to the current `Sys.time()` when the workbook object is created, not when the Excel files are saved.

`theme` Optional theme identified by string or number

... additional arguments

Returns: a `wbWorkbook` object

Method `append()`: Append a field. This method is intended for internal use

Usage:

```
wbWorkbook$append(field, value)
```

Arguments:

`field` A valid field name

value A value for the field

Method `append_sheets()`: Append to `self$workbook$sheets` This method is intended for internal use

Usage:

```
wbWorkbook$append_sheets(value)
```

Arguments:

value A value for `self$workbook$sheets`

Method `validate_sheet()`: validate sheet

Usage:

```
wbWorkbook$validate_sheet(sheet)
```

Arguments:

sheet A character sheet name or integer location

Returns: The integer position of the sheet

Method `add_chartsheet()`: Add a chart sheet to the workbook

Usage:

```
wbWorkbook$add_chartsheet(
  sheet = next_sheet(),
  tab_color = NULL,
  zoom = 100,
  visible = c("true", "false", "hidden", "visible", "veryhidden"),
  ...
)
```

Arguments:

sheet The name of the sheet

tab_color tab_color

zoom zoom

visible visible

... additional arguments

Returns: The `wbWorkbook` object, invisibly

Method `add_worksheet()`: Add worksheet to the `wbWorkbook` object

Usage:

```
wbWorkbook$add_worksheet(
  sheet = next_sheet(),
  grid_lines = TRUE,
  row_col_headers = TRUE,
  tab_color = NULL,
  zoom = 100,
  header = NULL,
  footer = NULL,
  odd_header = header,
```

```

    odd_footer = footer,
    even_header = header,
    even_footer = footer,
    first_header = header,
    first_footer = footer,
    visible = c("true", "false", "hidden", "visible", "veryhidden"),
    has_drawing = FALSE,
    paper_size = getOption("openxlsx2.paperSize", default = 9),
    orientation = getOption("openxlsx2.orientation", default = "portrait"),
    hdpi = getOption("openxlsx2.hdpi", default = getOption("openxlsx2.dpi", default = 300)),
    vdpi = getOption("openxlsx2.vdpi", default = getOption("openxlsx2.dpi", default = 300)),
    ...
)

```

Arguments:

sheet The name of the sheet
 grid_lines gridLines
 row_col_headers rowColHeaders
 tab_color tabColor
 zoom zoom
 header header
 footer footer
 odd_header oddHeader
 odd_footer oddFooter
 even_header evenHeader
 even_footer evenFooter
 first_header firstHeader
 first_footer firstFooter
 visible visible
 has_drawing hasDrawing
 paper_size paperSize
 orientation orientation
 hdpi hdpi
 vdpi vdpi
 ... additional arguments

Returns: The wbWorkbook object, invisibly

Method clone_worksheet(): Clone a worksheet to another workbook

Usage:

```

wbWorkbook$clone_worksheet(
  old = current_sheet(),
  new = next_sheet(),
  from = NULL
)

```

Arguments:

old name of worksheet to clone
 new name of new worksheet to add
 from name of new worksheet to add

Method `add_data()`: add data

Usage:

```
wbWorkbook$add_data(
  sheet = current_sheet(),
  x,
  dims = wb_dims(start_row, start_col),
  start_col = 1,
  start_row = 1,
  array = FALSE,
  col_names = TRUE,
  row_names = FALSE,
  with_filter = FALSE,
  name = NULL,
  sep = ", ",
  apply_cell_style = TRUE,
  remove_cell_style = FALSE,
  na.strings = na_strings(),
  inline_strings = TRUE,
  enforce = FALSE,
  ...
)
```

Arguments:

sheet The name of the sheet

x x

dims Cell range in a sheet

start_col startCol

start_row startRow

array array

col_names colNames

row_names rowNames

with_filter withFilter

name name

sep sep

apply_cell_style applyCellStyle

remove_cell_style if writing into existing cells, should the cell style be removed?

na.strings Value used for replacing NA values from x. Default `na_strings()` uses the special #N/A value within the workbook.

inline_strings write characters as inline strings

enforce enforce that selected dims is filled. For this to work, dims must match x

... additional arguments

return The wbWorkbook object

Method `add_data_table()`: add a data table

Usage:

```
wbWorkbook$add_data_table(
  sheet = current_sheet(),
  x,
  dims = wb_dims(start_row, start_col),
  start_col = 1,
  start_row = 1,
  col_names = TRUE,
  row_names = FALSE,
  table_style = "TableStyleLight9",
  table_name = NULL,
  with_filter = TRUE,
  sep = ", ",
  first_column = FALSE,
  last_column = FALSE,
  banded_rows = TRUE,
  banded_cols = FALSE,
  apply_cell_style = TRUE,
  remove_cell_style = FALSE,
  na.strings = na_strings(),
  inline_strings = TRUE,
  total_row = FALSE,
  ...
)
```

Arguments:

`sheet` The name of the sheet

`x` x

`dims` Cell range in a sheet

`start_col` startCol

`start_row` startRow

`col_names` colNames

`row_names` rowNames

`table_style` tableStyle

`table_name` tableName

`with_filter` withFilter

`sep` sep

`first_column` firstColumn

`last_column` lastColumn

`banded_rows` bandedRows

`banded_cols` bandedCols

`apply_cell_style` applyCellStyle

`remove_cell_style` if writing into existing cells, should the cell style be removed?

`na.strings` Value used for replacing NA values from x. Default `na_strings()` uses the special #N/A value within the workbook.

inline_strings write characters as inline strings
 total_row write total rows to table
 ... additional arguments
Returns: The wbWorkbook object

Method add_pivot_table(): add pivot table

Usage:

```
wbWorkbook$add_pivot_table(  
  x,  
  sheet = next_sheet(),  
  dims = "A3",  
  filter,  
  rows,  
  cols,  
  data,  
  fun,  
  params,  
  pivot_table,  
  slicer  
)
```

Arguments:

x a wb_data object
 sheet The name of the sheet
 dims the worksheet cell where the pivot table is placed
 filter a character object with names used to filter
 rows a character object with names used as rows
 cols a character object with names used as cols
 data a character object with names used as data
 fun a character object of functions to be used with the data
 params a list of parameters to modify pivot table creation
 pivot_table a character object with a name for the pivot table
 slicer a character object with names used as slicer

Details: fun can be either of AVERAGE, COUNT, COUNTA, MAX, MIN, PRODUCT, STDEV, STDEVP, SUM, VAR, VARP

Returns: The wbWorkbook object

Method add_slicer(): add pivot table

Usage:

```
wbWorkbook$add_slicer(  
  x,  
  dims = "A1",  
  sheet = current_sheet(),  
  pivot_table,  
  slicer,  
  params  
)
```

Arguments:

x a wb_data object
 dims the worksheet cell where the pivot table is placed
 sheet The name of the sheet
 pivot_table the name of a pivot table on the selected sheet
 slicer a variable used as slicer for the pivot table
 params a list of parameters to modify pivot table creation

Returns: The wbWorkbook object

Method add_formula(): Add formula*Usage:*

```
wbWorkbook$add_formula(
  sheet = current_sheet(),
  x,
  dims = wb_dims(start_row, start_col),
  start_col = 1,
  start_row = 1,
  array = FALSE,
  cm = FALSE,
  apply_cell_style = TRUE,
  remove_cell_style = FALSE,
  enforce = FALSE,
  ...
)
```

Arguments:

sheet The name of the sheet
 x x
 dims Cell range in a sheet
 start_col startCol
 start_row startRow
 array array
 cm cm
 apply_cell_style applyCellStyle
 remove_cell_style if writing into existing cells, should the cell style be removed?
 enforce enforce dims
 ... additional arguments

Returns: The wbWorkbook object

Method add_style(): add style*Usage:*

```
wbWorkbook$add_style(style = NULL, style_name = NULL)
```

Arguments:

style style

style_name style_name

Returns: The wbWorkbook object

Method to_df(): to_df

Usage:

```
wbWorkbook$to_df(
  sheet,
  start_row = 1,
  start_col = NULL,
  row_names = FALSE,
  col_names = TRUE,
  skip_empty_rows = FALSE,
  skip_empty_cols = FALSE,
  skip_hidden_rows = FALSE,
  skip_hidden_cols = FALSE,
  rows = NULL,
  cols = NULL,
  detect_dates = TRUE,
  na.strings = "#N/A",
  na.numbers = NA,
  fill_merged_cells = FALSE,
  dims,
  show_formula = FALSE,
  convert = TRUE,
  types,
  named_region,
  keep_attributes = FALSE,
  ...
)
```

Arguments:

sheet Either sheet name or index. When missing the first sheet in the workbook is selected.

start_row first row to begin looking for data.

start_col first column to begin looking for data.

row_names If TRUE, the first col of data will be used as row names.

col_names If TRUE, the first row of data will be used as column names.

skip_empty_rows If TRUE, empty rows are skipped.

skip_empty_cols If TRUE, empty columns are skipped.

skip_hidden_rows If TRUE, hidden rows are skipped.

skip_hidden_cols If TRUE, hidden columns are skipped.

rows A numeric vector specifying which rows in the Excel file to read. If NULL, all rows are read.

cols A numeric vector specifying which columns in the Excel file to read. If NULL, all columns are read.

detect_dates If TRUE, attempt to recognize dates and perform conversion.

na.strings A character vector of strings which are to be interpreted as NA. Blank cells will be returned as NA.

`na.numbers` A numeric vector of digits which are to be interpreted as NA. Blank cells will be returned as NA.

`fill_merged_cells` If TRUE, the value in a merged cell is given to all cells within the merge.

`dims` Character string of type "A1:B2" as optional dimensions to be imported.

`show_formula` If TRUE, the underlying Excel formulas are shown.

`convert` If TRUE, a conversion to dates and numerics is attempted.

`types` A named numeric indicating, the type of the data. 0: character, 1: numeric, 2: date, 3: posixt, 4: logical. Names must match the returned data

`named_region` Character string with a named_region (defined name or table). If no sheet is selected, the first appearance will be selected.

`keep_attributes` If TRUE additional attributes are returned. (These are used internally to define a cell type.)

... additional arguments

Returns: a data frame

Method `load()`: load workbook

Usage:

```
wbWorkbook$load(file, sheet, data_only = FALSE, ...)
```

Arguments:

`file` file

`sheet` The name of the sheet

`data_only` data_only

... additional arguments

Returns: The wbWorkbook object invisibly

Method `save()`: Save the workbook

Usage:

```
wbWorkbook$save(file = self$path, overwrite = TRUE, path = NULL)
```

Arguments:

`file` The path to save the workbook to

`overwrite` If FALSE, will not overwrite when path exists

`path` Deprecated argument previously used for file. Please use file in new code.

Returns: The wbWorkbook object invisibly

Method `open()`: open wbWorkbook in Excel.

Usage:

```
wbWorkbook$open(interactive = NA)
```

Arguments:

`interactive` If FALSE will throw a warning and not open the path. This can be manually set to TRUE, otherwise when NA (default) uses the value returned from `base::interactive()`

Details: minor helper wrapping `xl_open` which does the entire same thing

Returns: The wbWorkbook, invisibly

Method buildTable(): Build table

Usage:

```
wbWorkbook$buildTable(
  sheet = current_sheet(),
  colNames,
  ref,
  showColNames,
  tableStyle,
  tableName,
  withFilter = TRUE,
  totalsRowCount = 0,
  totalLabel = FALSE,
  showFirstColumn = 0,
  showLastColumn = 0,
  showRowStripes = 1,
  showColumnStripes = 0
)
```

Arguments:

sheet The name of the sheet

colNames colNames

ref ref

showColNames showColNames

tableStyle tableStyle

tableName tableName

withFilter withFilter

totalsRowCount totalsRowCount

totalLabel totalLabel

showFirstColumn showFirstColumn

showLastColumn showLastColumn

showRowStripes showRowStripes

showColumnStripes showColumnStripes

Returns: The wbWorksheet object, invisibly

Method update_table(): update a data_table

Usage:

```
wbWorkbook$update_table(sheet = current_sheet(), dims = "A1", tablename)
```

Arguments:

sheet The name of the sheet

dims Cell range in a sheet

tablename a tablename

Returns: The wbWorksheet object, invisibly

Method copy_cells(): copy cells around in a workbook

Usage:

```

wbWorkbook$copy_cells(
  sheet = current_sheet(),
  dims = "A1",
  data,
  as_value = FALSE,
  as_ref = FALSE,
  transpose = FALSE,
  ...
)

```

Arguments:

sheet The name of the sheet

dims Cell range in a sheet

data a wb_data object

as_value should a copy of the value be written

as_ref should references to the cell be written

transpose should the data be written transposed

... additional arguments passed to add_data() if used with as_value

Returns: The wbWorksheet object, invisibly

Method get_base_font(): Get the base font*Usage:*

```
wbWorkbook$get_base_font()
```

Returns: A list of of the font

Method set_base_font(): Set the base font*Usage:*

```

wbWorkbook$set_base_font(
  font_size = 11,
  font_color = wb_color(theme = "1"),
  font_name = "Aptos Narrow",
  ...
)

```

Arguments:

font_size fontSize

font_color font_color

font_name font_name

... additional arguments

Returns: The wbWorkbook object

Method get_base_colors(): Get the base color*Usage:*

```
wbWorkbook$get_base_colors(xml = FALSE, plot = TRUE)
```

Arguments:

```
xml xml
plot plot
```

Method `get_base_colours()`: Get the base colour

Usage:

```
wbWorkbook$get_base_colours(xml = FALSE, plot = TRUE)
```

Arguments:

```
xml xml
plot plot
```

Method `set_base_colors()`: Set the base color

Usage:

```
wbWorkbook$set_base_colors(theme = "Office", ...)
```

Arguments:

```
theme theme
... ...
```

Returns: The wbWorkbook object

Method `set_base_colours()`: Set the base colour

Usage:

```
wbWorkbook$set_base_colours(theme = "Office", ...)
```

Arguments:

```
theme theme
... ...
```

Returns: The wbWorkbook object

Method `set_bookview()`: Set the book views

Usage:

```
wbWorkbook$set_bookview(
  active_tab = NULL,
  auto_filter_date_grouping = NULL,
  first_sheet = NULL,
  minimized = NULL,
  show_horizontal_scroll = NULL,
  show_sheet_tabs = NULL,
  show_vertical_scroll = NULL,
  tab_ratio = NULL,
  visibility = NULL,
  window_height = NULL,
  window_width = NULL,
  x_window = NULL,
  y_window = NULL,
  ...
)
```

Arguments:

active_tab activeTab
 auto_filter_date_grouping autoFilterDateGrouping
 first_sheet firstSheet
 minimized minimized
 show_horizontal_scroll showHorizontalScroll
 show_sheet_tabs showSheetTabs
 show_vertical_scroll showVerticalScroll
 tab_ratio tabRatio
 visibility visibility
 window_height windowHeight
 window_width windowWidth
 x_window xWindow
 y_window yWindow
 ... additional arguments

Returns: The wbWorkbook object

Method `get_sheet_names()`: Get sheet names

Usage:

```
wbWorkbook$get_sheet_names(escape = FALSE)
```

Arguments:

escape Logical if the xml special characters are escaped

Returns: A named character vector of sheet names in their order. The names represent the original value of the worksheet prior to any character substitutions.

Method `set_sheet_names()`: Sets a sheet name

Usage:

```
wbWorkbook$set_sheet_names(old = NULL, new)
```

Arguments:

old Old sheet name
new New sheet name

Returns: The wbWorkbook object, invisibly

Method `set_row_heights()`: Sets a row height for a sheet

Usage:

```

wbWorkbook$set_row_heights(
  sheet = current_sheet(),
  rows,
  heights = NULL,
  hidden = FALSE
)

```

Arguments:

sheet The name of the sheet
rows rows
heights heights
hidden hidden

Returns: The wbWorkbook object, invisibly

Method `remove_row_heights()`: Removes a row height for a sheet

Usage:

```
wbWorkbook$remove_row_heights(sheet = current_sheet(), rows)
```

Arguments:

sheet The name of the sheet
rows rows

Returns: The wbWorkbook object, invisibly

Method `createCols()`: creates column object for worksheet

Usage:

```
wbWorkbook$createCols(sheet = current_sheet(), n, beg, end)
```

Arguments:

sheet The name of the sheet
n n
beg beg
end end

Method `group_cols()`: Group cols

Usage:

```
wbWorkbook$group_cols(  
  sheet = current_sheet(),  
  cols,  
  collapsed = FALSE,  
  levels = NULL  
)
```

Arguments:

sheet The name of the sheet
cols cols
collapsed collapsed
levels levels

Returns: The wbWorkbook object, invisibly

Method `ungroup_cols()`: ungroup cols

Usage:

```
wbWorkbook$ungroup_cols(sheet = current_sheet(), cols)
```

Arguments:

sheet The name of the sheet
 cols columns

Returns: The wbWorkbook object

Method `remove_col_widths()`: Remove row heights from a worksheet

Usage:

```
wbWorkbook$remove_col_widths(sheet = current_sheet(), cols)
```

Arguments:

sheet A name or index of a worksheet
 cols Indices of columns to remove custom width (if any) from.

Returns: The wbWorkbook object, invisibly

Method `set_col_widths()`: Set column widths

Usage:

```
wbWorkbook$set_col_widths(  
  sheet = current_sheet(),  
  cols,  
  widths = 8.43,  
  hidden = FALSE  
)
```

Arguments:

sheet The name of the sheet
 cols cols
 widths Width of columns
 hidden A logical vector to determine which cols are hidden; values are repeated across length of cols

Returns: The wbWorkbook object, invisibly

Method `group_rows()`: Group rows

Usage:

```
wbWorkbook$group_rows(  
  sheet = current_sheet(),  
  rows,  
  collapsed = FALSE,  
  levels = NULL  
)
```

Arguments:

sheet The name of the sheet
 rows rows
 collapsed collapsed
 levels levels

Returns: The wbWorkbook object, invisibly

Method `ungroup_rows()`: ungroup rows

Usage:

```
wbWorkbook$ungroup_rows(sheet = current_sheet(), rows)
```

Arguments:

sheet The name of the sheet

rows rows

Returns: The wbWorkbook object

Method `remove_worksheet()`: Remove a worksheet

Usage:

```
wbWorkbook$remove_worksheet(sheet = current_sheet())
```

Arguments:

sheet The worksheet to delete

Returns: The wbWorkbook object, invisibly

Method `add_data_validation()`: Adds data validation

Usage:

```
wbWorkbook$add_data_validation(
  sheet = current_sheet(),
  dims = "A1",
  type,
  operator,
  value,
  allow_blank = TRUE,
  show_input_msg = TRUE,
  show_error_msg = TRUE,
  error_style = NULL,
  error_title = NULL,
  error = NULL,
  prompt_title = NULL,
  prompt = NULL,
  ...
)
```

Arguments:

sheet The name of the sheet

dims Cell range in a sheet

type type

operator operator

value value

allow_blank allowBlank

show_input_msg showInputMsg

show_error_msg showErrorMsg

error_style The icon shown and the options how to deal with such inputs. Default "stop" (cancel), else "information" (prompt popup) or "warning" (prompt accept or change input)

error_title The error title

error The error text
 prompt_title The prompt title
 prompt The prompt text
 ... additional arguments

Returns: The wbWorkbook object

Method merge_cells(): Set cell merging for a sheet

Usage:

```
wbWorkbook$merge_cells(  
  sheet = current_sheet(),  
  dims = NULL,  
  solve = FALSE,  
  ...  
)
```

Arguments:

sheet The name of the sheet
 dims Cell range in a sheet
 solve logical if intersecting cells should be solved
 ... additional arguments

Returns: The wbWorkbook object, invisibly

Method unmerge_cells(): Removes cell merging for a sheet

Usage:

```
wbWorkbook$unmerge_cells(sheet = current_sheet(), dims = NULL, ...)
```

Arguments:

sheet The name of the sheet
 dims Cell range in a sheet
 ... additional arguments

Returns: The wbWorkbook object, invisibly

Method freeze_pane(): Set freeze panes for a sheet

Usage:

```
wbWorkbook$freeze_pane(  
  sheet = current_sheet(),  
  first_active_row = NULL,  
  first_active_col = NULL,  
  first_row = FALSE,  
  first_col = FALSE,  
  ...  
)
```

Arguments:

sheet The name of the sheet
 first_active_row first_active_row

```

first_active_col first_active_col
first_row first_row
first_col first_col
... additional arguments

```

Returns: The wbWorkbook object, invisibly

Method add_comment(): Add comment

Usage:

```
wbWorkbook$add_comment(sheet = current_sheet(), dims = "A1", comment, ...)
```

Arguments:

```

sheet The name of the sheet
dims row and column as spreadsheet dimension, e.g. "A1"
comment a comment to apply to the worksheet
... additional arguments

```

Returns: The wbWorkbook object

Method get_comment(): Get comments

Usage:

```
wbWorkbook$get_comment(sheet = current_sheet(), dims = NULL)
```

Arguments:

```

sheet sheet
dims dims

```

Returns: A data frame containing comments

Method remove_comment(): Remove comment

Usage:

```
wbWorkbook$remove_comment(sheet = current_sheet(), dims = "A1", ...)
```

Arguments:

```

sheet The name of the sheet
dims row and column as spreadsheet dimension, e.g. "A1"
... additional arguments

```

Returns: The wbWorkbook object

Method add_thread(): add threaded comment to worksheet

Usage:

```

wbWorkbook$add_thread(
  sheet = current_sheet(),
  dims = "A1",
  comment = NULL,
  person_id,
  reply = FALSE,
  resolve = FALSE
)

```

Arguments:

sheet The name of the sheet
 dims Cell range in a sheet
 comment the comment to add
 person_id the person Id this should be added for
 reply logical if the comment is a reply
 resolve logical if the comment should be marked as resolved

Method `get_thread()`: Get threads*Usage:*

```
wbWorkbook$get_thread(sheet = current_sheet(), dims = NULL)
```

Arguments:

sheet sheet
 dims dims

Returns: A data frame containing threads

Method `add_conditional_formatting()`: Add conditional formatting*Usage:*

```
wbWorkbook$add_conditional_formatting(
  sheet = current_sheet(),
  dims = NULL,
  rule = NULL,
  style = NULL,
  type = c("expression", "colorScale", "dataBar", "iconSet", "duplicatedValues",
    "uniqueValues", "containsErrors", "notContainsErrors", "containsBlanks",
    "notContainsBlanks", "containsText", "notContainsText", "beginsWith", "endsWith",
    "between", "topN", "bottomN"),
  params = list(showValue = TRUE, gradient = TRUE, border = TRUE, percent = FALSE, rank =
    5L),
  ...
)
```

Arguments:

sheet The name of the sheet
 dims Cell range in a sheet
 rule rule
 style style
 type type
 params Additional parameters
 ... additional arguments

Returns: The wbWorkbook object

Method `add_image()`: Insert an image into a sheet*Usage:*

```

wbWorkbook$add_image(
  sheet = current_sheet(),
  dims = "A1",
  file,
  width = 6,
  height = 3,
  row_offset = 0,
  col_offset = 0,
  units = "in",
  dpi = 300,
  ...
)

```

Arguments:

sheet The name of the sheet
 dims Cell range in a sheet
 file file
 width width
 height height
 row_offset, col_offset offsets
 units units
 dpi dpi
 ... additional arguments

Returns: The wbWorkbook object, invisibly

Method add_plot(): Add plot. A wrapper for add_image()

Usage:

```

wbWorkbook$add_plot(
  sheet = current_sheet(),
  dims = "A1",
  width = 6,
  height = 4,
  row_offset = 0,
  col_offset = 0,
  file_type = "png",
  units = "in",
  dpi = 300,
  ...
)

```

Arguments:

sheet The name of the sheet
 dims Cell range in a sheet
 width width
 height height
 row_offset, col_offset offsets
 file_type fileType

units units
 dpi dpi
 ... additional arguments

Returns: The wbWorkbook object

Method add_drawing(): Add xml drawing

Usage:

```
wbWorkbook$add_drawing(  
  sheet = current_sheet(),  
  dims = "A1",  
  xml,  
  col_offset = 0,  
  row_offset = 0,  
  ...  
)
```

Arguments:

sheet The name of the sheet
 dims Cell range in a sheet
 xml xml
 col_offset, row_offset offsets for column and row
 ... additional arguments

Returns: The wbWorkbook object

Method add_chart_xml(): Add xml chart

Usage:

```
wbWorkbook$add_chart_xml(  
  sheet = current_sheet(),  
  dims = NULL,  
  xml,  
  col_offset = 0,  
  row_offset = 0,  
  ...  
)
```

Arguments:

sheet The name of the sheet
 dims Cell range in a sheet
 xml xml
 col_offset, row_offset positioning parameters
 ... additional arguments

Returns: The wbWorkbook object

Method add_mschart(): Add mschart chart to the workbook

Usage:


```

wbWorkbook$add_mschart(
  sheet = current_sheet(),
  dims = NULL,
  graph,
  col_offset = 0,
  row_offset = 0,
  ...
)

```

Arguments:

sheet The name of the sheet
dims the dimensions where the sheet will appear
graph mschart graph
col_offset, *row_offset* offsets for column and row
 ... additional arguments

Returns: The wbWorkbook object

Method add_form_control(): Add form control to workbook*Usage:*

```

wbWorkbook$add_form_control(
  sheet = current_sheet(),
  dims = "A1",
  type = c("Checkbox", "Radio", "Drop"),
  text = NULL,
  link = NULL,
  range = NULL,
  checked = FALSE
)

```

Arguments:

sheet The name of the sheet
dims Cell range in a sheet
type type
text text
link link
range range
checked checked

Returns: The wbWorkbook object, invisibly

Method print(): Prints the wbWorkbook object*Usage:*

```
wbWorkbook$print()
```

Returns: The wbWorkbook object, invisibly; called for its side-effects

Method protect(): Protect a workbook*Usage:*

```

wbWorkbook$protect(
  protect = TRUE,
  password = NULL,
  lock_structure = FALSE,
  lock_windows = FALSE,
  type = 1,
  file_sharing = FALSE,
  username = unname(Sys.info()["user"]),
  read_only_recommended = FALSE,
  ...
)

```

Arguments:

protect protect
 password password
 lock_structure lock_structure
 lock_windows lock_windows
 type type
 file_sharing file_sharing
 username username
 read_only_recommended read_only_recommended
 ... additional arguments

Returns: The wbWorkbook object, invisibly

Method protect_worksheet(): protect worksheet*Usage:*

```

wbWorkbook$protect_worksheet(
  sheet = current_sheet(),
  protect = TRUE,
  password = NULL,
  properties = NULL
)

```

Arguments:

sheet The name of the sheet
 protect protect
 password password
 properties A character vector of properties to lock. Can be one or more of the following:
 "selectLockedCells", "selectUnlockedCells", "formatCells", "formatColumns",
 "formatRows", "insertColumns", "insertRows", "insertHyperlinks", "deleteColumns",
 "deleteRows", "sort", "autoFilter", "pivotTables", "objects", "scenarios"

Returns: The wbWorkbook object

Method get_properties(): Get properties of a workbook*Usage:*

```

wbWorkbook$get_properties()

```

Method `set_properties()`: Set a property of a workbook

Usage:

```
wbWorkbook$set_properties(  
  creator = NULL,  
  title = NULL,  
  subject = NULL,  
  category = NULL,  
  datetime_created = Sys.time(),  
  modifier = NULL,  
  keywords = NULL,  
  comments = NULL,  
  manager = NULL,  
  company = NULL,  
  custom = NULL  
)
```

Arguments:

`creator` character vector of creators. Duplicated are ignored.

`title`, `subject`, `category`, `datetime_created`, `modifier`, `keywords`, `comments`, `manager`, `company`, `custom`
A workbook property to set

Method `add_mips()`: add mips string

Usage:

```
wbWorkbook$add_mips(xml = NULL)
```

Arguments:

`xml` A mips string added to `self$custom`

Method `get_mips()`: get mips string

Usage:

```
wbWorkbook$get_mips(single_xml = TRUE, quiet = TRUE)
```

Arguments:

`single_xml` `single_xml`

`quiet` `quiet`

Method `set_creators()`: Set creator(s)

Usage:

```
wbWorkbook$set_creators(creators)
```

Arguments:

`creators` A character vector of creators to set. Duplicates are ignored.

Method `add_creators()`: Add creator(s)

Usage:

```
wbWorkbook$add_creators(creators)
```

Arguments:

`creators` A character vector of creators to add. Duplicates are ignored.

Method `remove_creators()`: Remove creator(s)

Usage:

```
wbWorkbook$remove_creators(creators)
```

Arguments:

`creators` A character vector of creators to remove. All duplicated are removed.

Method `set_last_modified_by()`: Change the last modified by

Usage:

```
wbWorkbook$set_last_modified_by(name, ...)
```

Arguments:

`name` A new value

`...` additional arguments

Returns: The wbWorkbook object, invisibly

Method `set_page_setup()`: `set_page_setup()` this function is intended to supersede `page_setup()`, but is not yet stable

Usage:

```
wbWorkbook$set_page_setup(
  sheet = current_sheet(),
  black_and_white = NULL,
  cell_comments = NULL,
  copies = NULL,
  draft = NULL,
  errors = NULL,
  first_page_number = NULL,
  id = NULL,
  page_order = NULL,
  paper_height = NULL,
  paper_width = NULL,
  hdpi = NULL,
  vdpi = NULL,
  use_first_page_number = NULL,
  use_printer_defaults = NULL,
  orientation = NULL,
  scale = NULL,
  left = 0.7,
  right = 0.7,
  top = 0.75,
  bottom = 0.75,
  header = 0.3,
  footer = 0.3,
  fit_to_width = FALSE,
  fit_to_height = FALSE,
  paper_size = NULL,
  print_title_rows = NULL,
  print_title_cols = NULL,
```

```

summary_row = NULL,
summary_col = NULL,
tab_color = NULL,
...
)

```

Arguments:

sheet The name of the sheet
black_and_white black_and_white
cell_comments cell_comment
copies copies
draft draft
errors errors
first_page_number first_page_number
id id
page_order page_order
paper_height, paper_width paper size
hdpi, vdpi horizontal and vertical dpi
use_first_page_number use_first_page_number
use_printer_defaults use_printer_defaults
orientation orientation
scale scale
left left
right right
top top
bottom bottom
header header
footer footer
fit_to_width fitToWidth
fit_to_height fitToHeight
paper_size paperSize
print_title_rows printTitleRows
print_title_cols printTitleCols
summary_row summaryRow
summary_col summaryCol
tab_color tabColor
... additional arguments

Returns: The wbWorkbook object, invisibly

Method page_setup(): page_setup()*Usage:*

```

wbWorkbook$page_setup(
  sheet = current_sheet(),
  orientation = NULL,

```

```

    scale = 100,
    left = 0.7,
    right = 0.7,
    top = 0.75,
    bottom = 0.75,
    header = 0.3,
    footer = 0.3,
    fit_to_width = FALSE,
    fit_to_height = FALSE,
    paper_size = NULL,
    print_title_rows = NULL,
    print_title_cols = NULL,
    summary_row = NULL,
    summary_col = NULL,
    ...
)

```

Arguments:

sheet The name of the sheet
 orientation orientation
 scale scale
 left left
 right right
 top top
 bottom bottom
 header header
 footer footer
 fit_to_width fitToWidth
 fit_to_height fitToHeight
 paper_size paperSize
 print_title_rows printTitleRows
 print_title_cols printTitleCols
 summary_row summaryRow
 summary_col summaryCol
 ... additional arguments

Returns: The wbWorkbook object, invisibly

Method `set_header_footer()`: Sets headers and footers

Usage:

```

wbWorkbook$set_header_footer(
  sheet = current_sheet(),
  header = NULL,
  footer = NULL,
  even_header = NULL,
  even_footer = NULL,
  first_header = NULL,

```

```

        first_footer = NULL,
        ...
    )

```

Arguments:

sheet The name of the sheet
 header header
 footer footer
 even_header evenHeader
 even_footer evenFooter
 first_header firstHeader
 first_footer firstFooter
 ... additional arguments

Returns: The wbWorkbook object, invisibly

Method get_tables(): get tables*Usage:*

```
wbWorkbook$get_tables(sheet = current_sheet())
```

Arguments:

sheet The name of the sheet

Returns: The sheet tables. character() if empty

Method remove_tables(): remove tables*Usage:*

```
wbWorkbook$remove_tables(sheet = current_sheet(), table, remove_data = TRUE)
```

Arguments:

sheet The name of the sheet

table table

remove_data removes the data as well

Returns: The wbWorkbook object

Method add_filter(): add filters*Usage:*

```
wbWorkbook$add_filter(sheet = current_sheet(), rows, cols)
```

Arguments:

sheet The name of the sheet

rows rows

cols cols

Returns: The wbWorkbook object

Method remove_filter(): remove filters*Usage:*

```
wbWorkbook$remove_filter(sheet = current_sheet())
```

Arguments:

sheet The name of the sheet

Returns: The wbWorkbook object

Method set_grid_lines(): grid lines*Usage:*

```
wbWorkbook$set_grid_lines(sheet = current_sheet(), show = FALSE, print = show)
```

Arguments:

sheet The name of the sheet

show show

print print

Returns: The wbWorkbook object

Method grid_lines(): grid lines*Usage:*

```
wbWorkbook$grid_lines(sheet = current_sheet(), show = FALSE, print = show)
```

Arguments:

sheet The name of the sheet

show show

print print

Returns: The wbWorkbook object

Method add_named_region(): add a named region*Usage:*

```
wbWorkbook$add_named_region(
  sheet = current_sheet(),
  dims = "A1",
  name,
  local_sheet = FALSE,
  overwrite = FALSE,
  comment = NULL,
  hidden = NULL,
  custom_menu = NULL,
  description = NULL,
  is_function = NULL,
  function_group_id = NULL,
  help = NULL,
  local_name = NULL,
  publish_to_server = NULL,
  status_bar = NULL,
  vb_procedure = NULL,
  workbook_parameter = NULL,
  xml = NULL,
  ...
)
```


Arguments:

sheet The name of the sheet
 dims Cell range in a sheet
 name name
 local_sheet local_sheet
 overwrite overwrite
 comment comment
 hidden hidden
 custom_menu custom_menu
 description description
 is_function function
 function_group_id function group id
 help help
 local_name localName
 publish_to_server publish to server
 status_bar status bar
 vb_procedure vb procedure
 workbook_parameter workbookParameter
 xml xml
 ... additional arguments

Returns: The wbWorkbook object

Method get_named_regions(): get named regions in a workbook

Usage:

wbWorkbook\$get_named_regions(tables = FALSE, x = NULL)

Arguments:

tables Return tables as well?
 x Not used.

Returns: A data.frame of named regions

Method remove_named_region(): remove a named region

Usage:

wbWorkbook\$remove_named_region(sheet = current_sheet(), name = NULL)

Arguments:

sheet The name of the sheet
 name name

Returns: The wbWorkbook object

Method set_order(): set worksheet order

Usage:

wbWorkbook\$set_order(sheets)

Arguments:

sheets sheets

Returns: The wbWorkbook object

Method `get_sheet_visibility()`: Get sheet visibility

Usage:

```
wbWorkbook$get_sheet_visibility()
```

Returns: Returns sheet visibility

Method `set_sheet_visibility()`: Set sheet visibility

Usage:

```
wbWorkbook$set_sheet_visibility(sheet = current_sheet(), value)
```

Arguments:

sheet The name of the sheet

value value

Returns: The wbWorkbook object

Method `add_page_break()`: Add a page break

Usage:

```
wbWorkbook$add_page_break(sheet = current_sheet(), row = NULL, col = NULL)
```

Arguments:

sheet The name of the sheet

row row

col col

Returns: The wbWorkbook object

Method `clean_sheet()`: clean sheet (remove all values)

Usage:

```
wbWorkbook$clean_sheet(  
  sheet = current_sheet(),  
  dims = NULL,  
  numbers = TRUE,  
  characters = TRUE,  
  styles = TRUE,  
  merged_cells = TRUE  
)
```

Arguments:

sheet The name of the sheet

dims Cell range in a sheet

numbers remove all numbers

characters remove all characters

styles remove all styles

merged_cells remove all merged_cells

Returns: The wbWorksheetObject, invisibly

Method `add_border()`: create borders for cell region

Usage:

```
wbWorkbook$add_border(
  sheet = current_sheet(),
  dims = "A1",
  bottom_color = wb_color(hex = "FF000000"),
  left_color = wb_color(hex = "FF000000"),
  right_color = wb_color(hex = "FF000000"),
  top_color = wb_color(hex = "FF000000"),
  bottom_border = "thin",
  left_border = "thin",
  right_border = "thin",
  top_border = "thin",
  inner_hgrid = NULL,
  inner_hcolor = NULL,
  inner_vgrid = NULL,
  inner_vcolor = NULL,
  ...
)
```

Arguments:

`sheet` The name of the sheet

`dims` dimensions on the worksheet e.g. "A1", "A1:A5", "A1:H5"

`bottom_color`, `left_color`, `right_color`, `top_color`, `inner_hcolor`, `inner_vcolor` a color, either something openxml knows or some RGB color

`left_border`, `right_border`, `top_border`, `bottom_border`, `inner_hgrid`, `inner_vgrid` the border style, if NULL no border is drawn. See `create_border` for possible border styles

... additional arguments

Returns: The wbWorkbook, invisibly

Method `add_fill()`: provide simple fill function

Usage:

```
wbWorkbook$add_fill(
  sheet = current_sheet(),
  dims = "A1",
  color = wb_color(hex = "FFFFFF00"),
  pattern = "solid",
  gradient_fill = "",
  every_nth_col = 1,
  every_nth_row = 1,
  ...
)
```

Arguments:

`sheet` The name of the sheet

`dims` Cell range in a sheet

color the colors to apply, e.g. yellow: `wb_color(hex = "FFFFFF00")`
pattern various default "none" but others are possible: "solid", "mediumGray", "darkGray",
 "lightGray", "darkHorizontal", "darkVertical", "darkDown", "darkUp", "darkGrid", "dark-
 Trellis", "lightHorizontal", "lightVertical", "lightDown", "lightUp", "lightGrid", "lightTrel-
 lis", "gray125", "gray0625"
gradient_fill a gradient fill xml pattern.
every_nth_col which col should be filled
every_nth_row which row should be filled
 ... additional arguments

Returns: The `wbWorksheetObject`, invisibly

Method `add_font()`: provide simple font function

Usage:

```

wbWorkbook$add_font(
  sheet = current_sheet(),
  dims = "A1",
  name = "Aptos Narrow",
  color = wb_color(hex = "FF000000"),
  size = "11",
  bold = "",
  italic = "",
  outline = "",
  strike = "",
  underline = "",
  charset = "",
  condense = "",
  extend = "",
  family = "",
  scheme = "",
  shadow = "",
  vert_align = "",
  ...
)

```

Arguments:

sheet The name of the sheet
dims Cell range in a sheet
name font name: default "Aptos Narrow"
color rgb color: default "FF000000"
size font size: default "11",
bold bold
italic italic
outline outline
strike strike
underline underline
charset charset

condense condense
 extend extend
 family font family
 scheme font scheme
 shadow shadow
 vert_align vertical alignment
 ... additional arguments

Returns: The wbWorkbook, invisibly

Method add_numfmt(): provide simple number format function

Usage:

```
wbWorkbook$add_numfmt(sheet = current_sheet(), dims = "A1", numfmt)
```

Arguments:

sheet The name of the sheet
 dims Cell range in a sheet
 numfmt number format id or a character of the format

Returns: The wbWorksheetObject, invisibly

Method add_cell_style(): provide simple cell style format function

Usage:

```
wbWorkbook$add_cell_style(
  sheet = current_sheet(),
  dims = "A1",
  apply_alignment = NULL,
  apply_border = NULL,
  apply_fill = NULL,
  apply_font = NULL,
  apply_number_format = NULL,
  apply_protection = NULL,
  border_id = NULL,
  ext_lst = NULL,
  fill_id = NULL,
  font_id = NULL,
  hidden = NULL,
  horizontal = NULL,
  indent = NULL,
  justify_last_line = NULL,
  locked = NULL,
  num_fmt_id = NULL,
  pivot_button = NULL,
  quote_prefix = NULL,
  reading_order = NULL,
  relative_indent = NULL,
  shrink_to_fit = NULL,
  text_rotation = NULL,
```

```

    vertical = NULL,
    wrap_text = NULL,
    xf_id = NULL,
    ...
)

```

Arguments:

sheet The name of the sheet
dims Cell range in a sheet
apply_alignment logical apply alignment
apply_border logical apply border
apply_fill logical apply fill
apply_font logical apply font
apply_number_format logical apply number format
apply_protection logical apply protection
border_id border ID to apply
ext_lst extension list something like <extLst>...</extLst>
fill_id fill ID to apply
font_id font ID to apply
hidden logical cell is hidden
horizontal align content horizontal ('left', 'center', 'right')
indent logical indent content
justify_last_line logical justify last line
locked logical cell is locked
num_fmt_id number format ID to apply
pivot_button unknown
quote_prefix unknown
reading_order reading order left to right
relative_indent relative indentation
shrink_to_fit logical shrink to fit
text_rotation degrees of text rotation
vertical vertical alignment of content ('top', 'center', 'bottom')
wrap_text wrap text in cell
xf_id xf ID to apply
 ... additional arguments

Returns: The wbWorkbook object, invisibly

Method `get_cell_style()`: get sheet style

Usage:

```
wbWorkbook$get_cell_style(sheet = current_sheet(), dims)
```

Arguments:

sheet The name of the sheet
dims Cell range in a sheet

Returns: a character vector of cell styles

Method `set_cell_style()`: set sheet style

Usage:

```
wbWorkbook$set_cell_style(sheet = current_sheet(), dims, style)
```

Arguments:

sheet The name of the sheet

dims Cell range in a sheet

style style

Returns: The wbWorksheetObject, invisibly

Method `set_cell_style_across()`: set style across columns and/or rows

Usage:

```
wbWorkbook$set_cell_style_across(
  sheet = current_sheet(),
  style,
  cols = NULL,
  rows = NULL
)
```

Arguments:

sheet sheet

style style

cols cols

rows rows

Returns: The wbWorkbook object

Method `add_named_style()`: set sheet style

Usage:

```
wbWorkbook$add_named_style(
  sheet = current_sheet(),
  dims = "A1",
  name = "Normal",
  font_name = NULL,
  font_size = NULL
)
```

Arguments:

sheet The name of the sheet

dims Cell range in a sheet

name name

font_name, font_size optional else the default of the theme

Returns: The wbWorkbook, invisibly

Method `add_dxfs_style()`: create dxfs style These styles are used with conditional formatting and custom table styles

Usage:

```

wbWorkbook$add_dxfs_style(
  name,
  font_name = NULL,
  font_size = NULL,
  font_color = NULL,
  num_fmt = NULL,
  border = NULL,
  border_color = wb_color(getOption("openxlsx2.borderColor", "black")),
  border_style = getOption("openxlsx2.borderStyle", "thin"),
  bg_fill = NULL,
  gradient_fill = NULL,
  text_bold = NULL,
  text_italic = NULL,
  text_underline = NULL,
  ...
)

```

Arguments:

name the style name
font_name the font name
font_size the font size
font_color the font color (a `wb_color()` object)
num_fmt the number format
border logical if borders are applied
border_color the border color
border_style the border style
bg_fill any background fill
gradient_fill any gradient fill
text_bold logical if text is bold
text_italic logical if text is italic
text_underline logical if text is underlined
... additional arguments passed to `create_dxfs_style()`

Returns: The `wbWorksheetObject`, invisibly

Method `clone_sheet_style()`: clone style from one sheet to another

Usage:

```
wbWorkbook$clone_sheet_style(from = current_sheet(), to)
```

Arguments:

from the worksheet you are cloning
to the worksheet the style is applied to

Method `add_sparklines()`: apply sparkline to worksheet

Usage:

```
wbWorkbook$add_sparklines(sheet = current_sheet(), sparklines)
```


Arguments:

sheet The name of the sheet
 sparklines sparkline created by create_sparkline()

Method add_ignore_error(): Ignore error on worksheet

Usage:

```
wbWorkbook$add_ignore_error(
  sheet = current_sheet(),
  dims = "A1",
  calculated_column = FALSE,
  empty_cell_reference = FALSE,
  eval_error = FALSE,
  formula = FALSE,
  formula_range = FALSE,
  list_data_validation = FALSE,
  number_stored_as_text = FALSE,
  two_digit_text_year = FALSE,
  unlocked_formula = FALSE,
  ...
)
```

Arguments:

sheet The name of the sheet
 dims Cell range in a sheet
 calculated_column calculatedColumn
 empty_cell_reference emptyCellReference
 eval_error evalError
 formula formula
 formula_range formulaRange
 list_data_validation listDataValidation
 number_stored_as_text numberStoredAsText
 two_digit_text_year twoDigitTextYear
 unlocked_formula unlockedFormula
 ... additional arguments

Method set_sheetview(): add sheetview

Usage:

```
wbWorkbook$set_sheetview(
  sheet = current_sheet(),
  color_id = NULL,
  default_grid_color = NULL,
  right_to_left = NULL,
  show_formulas = NULL,
  show_grid_lines = NULL,
  show_outline_symbols = NULL,
  show_row_col_headers = NULL,
```

```

    show_ruler = NULL,
    show_white_space = NULL,
    show_zeros = NULL,
    tab_selected = NULL,
    top_left_cell = NULL,
    view = NULL,
    window_protection = NULL,
    workbook_view_id = NULL,
    zoom_scale = NULL,
    zoom_scale_normal = NULL,
    zoom_scale_page_layout_view = NULL,
    zoom_scale_sheet_layout_view = NULL,
    ...
)

```

Arguments:

sheet The name of the sheet
color_id, default_grid_color Integer: A color, default is 64
right_to_left Logical: if TRUE column ordering is right to left
show_formulas Logical: if TRUE cell formulas are shown
show_grid_lines Logical: if TRUE the worksheet grid is shown
show_outline_symbols Logical: if TRUE outline symbols are shown
show_row_col_headers Logical: if TRUE row and column headers are shown
show_ruler Logical: if TRUE a ruler is shown in page layout view
show_white_space Logical: if TRUE margins are shown in page layout view
show_zeros Logical: if FALSE cells containing zero are shown blank if !showFormulas
tab_selected Integer: zero vector indicating the selected tab
top_left_cell Cell: the cell shown in the top left corner / or top right with rightToLeft
view View: "normal", "pageBreakPreview" or "pageLayout"
window_protection Logical: if TRUE the panes are protected
workbook_view_id integer: Pointing to some other view inside the workbook
zoom_scale, zoom_scale_normal, zoom_scale_page_layout_view, zoom_scale_sheet_layout_view
 Integer: the zoom scale should be between 10 and 400. These are values for current, normal
 etc.
 ... additional arguments

Returns: The wbWorksheetObject, invisibly

Method add_person(): add person to workbook

Usage:

```

wbWorkbook$add_person(
  name = NULL,
  id = NULL,
  user_id = NULL,
  provider_id = "None"
)

```

Arguments:

name name
id id
user_id user_id
provider_id provider_id

Method get_person(): description get person

Usage:

wbWorkbook\$get_person(name = NULL)

Arguments:

name name

Method get_active_sheet(): description get active sheet

Usage:

wbWorkbook\$get_active_sheet()

Method set_active_sheet(): description set active sheet

Usage:

wbWorkbook\$set_active_sheet(sheet = current_sheet())

Arguments:

sheet The name of the sheet

Method get_selected(): description get selected sheets

Usage:

wbWorkbook\$get_selected()

Method set_selected(): set selected sheet

Usage:

wbWorkbook\$set_selected(sheet = current_sheet())

Arguments:

sheet The name of the sheet

Method clone(): The objects of this class are cloneable with this method.

Usage:

wbWorkbook\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

wb_add_border	<i>Modify borders in a cell region of a worksheet</i>
---------------	---

Description

wb wrapper to create borders for cell regions.

Usage

```
wb_add_border(
    wb,
    sheet = current_sheet(),
    dims = "A1",
    bottom_color = wb_color(hex = "FF000000"),
    left_color = wb_color(hex = "FF000000"),
    right_color = wb_color(hex = "FF000000"),
    top_color = wb_color(hex = "FF000000"),
    bottom_border = "thin",
    left_border = "thin",
    right_border = "thin",
    top_border = "thin",
    inner_hgrid = NULL,
    inner_hcolor = NULL,
    inner_vgrid = NULL,
    inner_vcolor = NULL,
    ...
)
```

Arguments

wb	A wbWorkbook
sheet	A worksheet
dims	Cell range in the worksheet e.g. "A1", "A1:A5", "A1:H5"
bottom_color, left_color, right_color, top_color, inner_hcolor, inner_vcolor	a color, either something openxml knows or some RGB color
left_border, right_border, top_border, bottom_border, inner_hgrid, inner_vgrid	the border style, if NULL no border is drawn. See create_border() for possible border styles
...	additional arguments

See Also

[create_border\(\)](#)

Other styles: [wb_add_cell_style\(\)](#), [wb_add_fill\(\)](#), [wb_add_font\(\)](#), [wb_add_named_style\(\)](#), [wb_add_numfmt\(\)](#), [wb_cell_style](#)

Examples

```

wb <- wb_workbook() %>% wb_add_worksheet("S1") %>% wb_add_data("S1", mtcars)
wb <- wb_add_border(wb, 1, dims = "A1:K1",
  left_border = NULL, right_border = NULL,
  top_border = NULL, bottom_border = "double")
wb <- wb_add_border(wb, 1, dims = "A5",
  left_border = "dotted", right_border = "dotted",
  top_border = "hair", bottom_border = "thick")
wb <- wb_add_border(wb, 1, dims = "C2:C5")
wb <- wb_add_border(wb, 1, dims = "G2:H3")

wb <- wb_add_border(wb, 1, dims = "G12:H13",
  left_color = wb_color(hex = "FF9400D3"), right_color = wb_color(hex = "FF4B0082"),
  top_color = wb_color(hex = "FF0000FF"), bottom_color = wb_color(hex = "FF00FF00"))
wb <- wb_add_border(wb, 1, dims = "A20:C23")
wb <- wb_add_border(wb, 1, dims = "B12:D14",
  left_color = wb_color(hex = "FFFFFF00"), right_color = wb_color(hex = "FFFF7F00"),
  bottom_color = wb_color(hex = "FFFF0000"))
wb <- wb_add_border(wb, 1, dims = "D28:E28")

# With chaining

wb <- wb_workbook()
wb$add_worksheet("S1")$add_data("S1", mtcars)
wb$add_border(1, dims = "A1:K1",
  left_border = NULL, right_border = NULL,
  top_border = NULL, bottom_border = "double")
wb$add_border(1, dims = "A5",
  left_border = "dotted", right_border = "dotted",
  top_border = "hair", bottom_border = "thick")
wb$add_border(1, dims = "C2:C5")
wb$add_border(1, dims = "G2:H3")
wb$add_border(1, dims = "G12:H13",
  left_color = wb_color(hex = "FF9400D3"), right_color = wb_color(hex = "FF4B0082"),
  top_color = wb_color(hex = "FF0000FF"), bottom_color = wb_color(hex = "FF00FF00"))
wb$add_border(1, dims = "A20:C23")
wb$add_border(1, dims = "B12:D14",
  left_color = wb_color(hex = "FFFFFF00"), right_color = wb_color(hex = "FFFF7F00"),
  bottom_color = wb_color(hex = "FFFF0000"))
wb$add_border(1, dims = "D28:E28")
# if (interactive()) wb$open()

wb <- wb_workbook()
wb$add_worksheet("S1")$add_data("S1", mtcars)
wb$add_border(1, dims = "A2:K33", inner_vgrid = "thin", inner_vcolor = c(rgb="FF808080"))

```

Description

Add cell style to a cell region

Usage

```
wb_add_cell_style(
    wb,
    sheet = current_sheet(),
    dims = "A1",
    apply_alignment = NULL,
    apply_border = NULL,
    apply_fill = NULL,
    apply_font = NULL,
    apply_number_format = NULL,
    apply_protection = NULL,
    border_id = NULL,
    ext_lst = NULL,
    fill_id = NULL,
    font_id = NULL,
    hidden = NULL,
    horizontal = NULL,
    indent = NULL,
    justify_last_line = NULL,
    locked = NULL,
    num_fmt_id = NULL,
    pivot_button = NULL,
    quote_prefix = NULL,
    reading_order = NULL,
    relative_indent = NULL,
    shrink_to_fit = NULL,
    text_rotation = NULL,
    vertical = NULL,
    wrap_text = NULL,
    xf_id = NULL,
    ...
)
```

Arguments

wb	a workbook
sheet	the worksheet
dims	the cell range
apply_alignment	logical apply alignment
apply_border	logical apply border
apply_fill	logical apply fill
apply_font	logical apply font

apply_number_format	logical apply number format
apply_protection	logical apply protection
border_id	border ID to apply
ext_lst	extension list something like <extLst>...</extLst>
fill_id	fill ID to apply
font_id	font ID to apply
hidden	logical cell is hidden
horizontal	align content horizontal ('left', 'center', 'right')
indent	logical indent content
justify_last_line	logical justify last line
locked	logical cell is locked
num_fmt_id	number format ID to apply
pivot_button	unknown
quote_prefix	unknown
reading_order	reading order left to right
relative_indent	relative indentation
shrink_to_fit	logical shrink to fit
text_rotation	degrees of text rotation
vertical	vertical alignment of content ('top', 'center', 'bottom')
wrap_text	wrap text in cell
xf_id	xf ID to apply
...	additional arguments

Value

The wbWorkbook object, invisibly

See Also

Other styles: [wb_add_border\(\)](#), [wb_add_fill\(\)](#), [wb_add_font\(\)](#), [wb_add_named_style\(\)](#), [wb_add_numfmt\(\)](#), [wb_cell_style](#)

Examples

```
wb <- wb_workbook() %>%
  wb_add_worksheet("S1") %>%
  wb_add_data("S1", x = mtcars)

wb %>%
  wb_add_cell_style(
```

```

    dims = "A1:K1",
    text_rotation = "45",
    horizontal = "center",
    vertical = "center",
    wrap_text = "1"
)
# Chaining
wb <- wb_workbook()$add_worksheet("S1")$add_data(x = mtcars)
wb$add_cell_style(dims = "A1:K1",
                  text_rotation = "45",
                  horizontal = "center",
                  vertical = "center",
                  wrap_text = "1")

```

wb_add_chartsheet *Add a chartsheet to a workbook*

Description

A chartsheet is a special type of sheet that handles charts output. You must add a chart to the sheet. Otherwise, this will break the workbook.

Usage

```

wb_add_chartsheet(
  wb,
  sheet = next_sheet(),
  tab_color = NULL,
  zoom = 100,
  visible = c("true", "false", "hidden", "visible", "veryhidden"),
  ...
)

```

Arguments

wb	A Workbook object to attach the new chartsheet
sheet	A name for the new chartsheet
tab_color	Color of the sheet tab. A <code>wb_color()</code> , a valid color (belonging to <code>grDevices::colors()</code>) or a valid hex color beginning with "#".
zoom	The sheet zoom level, a numeric between 10 and 400 as a percentage. (A zoom value smaller than 10 will default to 10.)
visible	If FALSE, sheet is hidden else visible.
...	Additional arguments

See Also[wb_add_mschart\(\)](#)

Other workbook wrappers: [base_font-wb](#), [col_widths-wb](#), [creators-wb](#), [grouping-wb](#), [row_heights-wb](#), [wb_add_data\(\)](#), [wb_add_data_table\(\)](#), [wb_add_formula\(\)](#), [wb_add_pivot_table\(\)](#), [wb_add_slicer\(\)](#), [wb_add_worksheet\(\)](#), [wb_base_colors](#), [wb_clone_worksheet\(\)](#), [wb_copy_cells\(\)](#), [wb_freeze_pane\(\)](#), [wb_merge_cells\(\)](#), [wb_save\(\)](#), [wb_set_last_modified_by\(\)](#), [wb_workbook\(\)](#)

wb_add_chart_xml	<i>Add a chart XML to a worksheet</i>
------------------	---------------------------------------

Description

Add a chart XML to a worksheet

Usage

```
wb_add_chart_xml(  
    wb,  
    sheet = current_sheet(),  
    dims = NULL,  
    xml,  
    col_offset = 0,  
    row_offset = 0,  
    ...  
)
```

Arguments

wb	a workbook
sheet	the sheet on which the graph will appear
dims	the dimensions where the sheet will appear
xml	chart xml
col_offset, row_offset	positioning
...	additional arguments

See Also

[wb_add_drawing\(\)](#) [wb_add_image\(\)](#) [wb_add_mschart\(\)](#) [wb_add_plot\(\)](#)

wb_add_comment	<i>Add comment to worksheet</i>
----------------	---------------------------------

Description

Add comment to worksheet

Usage

```
wb_add_comment(wb, sheet = current_sheet(), dims = "A1", comment, ...)
```

```
wb_get_comment(wb, sheet = current_sheet(), dims = NULL)
```

```
wb_remove_comment(wb, sheet = current_sheet(), dims = "A1", ...)
```

Arguments

wb	A workbook object
sheet	A worksheet of the workbook
dims	Optional row and column as spreadsheet dimension, e.g. "A1"
comment	A comment to apply to dims created by <code>wb_comment()</code> , a string or a <code>fmt_txt()</code> object
...	additional arguments

Details

If applying a comment with a string, it will use `wb_comment()` default values. If additional background colors are applied, RGB colors should be provided, either as hex code or with builtin R colors. The alpha channel is ignored.

Value

The Workbook object, invisibly.

See Also

[wb_comment\(\)](#), [wb_add_thread\(\)](#)

Examples

```
wb <- wb_workbook()
wb$add_worksheet("Sheet 1")
# add a comment without author
c1 <- wb_comment(text = "this is a comment", author = "")
wb$add_comment(dims = "B10", comment = c1)
#' # Remove comment
wb$remove_comment(sheet = "Sheet 1", dims = "B10")
```

```

# Write another comment with author information
c2 <- wb_comment(text = "this is another comment", author = "Marco Polo", visible = TRUE)
wb$add_comment(sheet = 1, dims = "C10", comment = c2)
# Works with formatted text also.
formatted_text <- fmt_txt("bar", underline = TRUE)
wb$add_comment(dims = "B5", comment = formatted_text)
# With background color
wb$add_comment(dims = "B7", comment = formatted_text, color = wb_color("green"))
# With background image. File extension must be png or jpeg, not jpg?
tmp <- tempfile(fileext = ".png")
png(file = tmp, bg = "transparent")
plot(1:10)
rect(1, 5, 3, 7, col = "white")
dev.off()

c1 <- wb_comment(text = "this is a comment", author = "", visible = TRUE)
wb$add_comment(dims = "B12", comment = c1, file = tmp)

```

wb_add_conditional_formatting

Add conditional formatting to cells in a worksheet

Description

Add conditional formatting to cells. You can find more details in vignette("conditional-formatting").

Usage

```

wb_add_conditional_formatting(
  wb,
  sheet = current_sheet(),
  dims = NULL,
  rule = NULL,
  style = NULL,
  type = c("expression", "colorScale", "dataBar", "iconSet", "duplicatedValues",
    "uniqueValues", "containsErrors", "notContainsErrors", "containsBlanks",
    "notContainsBlanks", "containsText", "notContainsText", "beginsWith", "endsWith",
    "between", "topN", "bottomN"),
  params = list(showValue = TRUE, gradient = TRUE, border = TRUE, percent = FALSE, rank =
    5L),
  ...
)

```

Arguments

wb	A Workbook object
sheet	A name or index of a worksheet
dims	A cell or cell range like "A1" or "A1:B2"

rule	The condition under which to apply the formatting. See Examples .
style	A style to apply to those cells that satisfy the rule. Default is font_color = "FF9C0006" and bg_fill = "FFFC7CE"
type	The type of conditional formatting rule to apply. One of "expression", "colorScale" or others mentioned in Details .
params	A list of additional parameters passed. See Details for more.
...	additional arguments

Details

openxml uses the alpha channel first then RGB, whereas the usual default is RGBA.

Conditional formatting type accept different parameters. Unless noted, unlisted parameters are ignored.

expression [style]
A Style object

[rule]
An Excel expression (as a character). Valid operators are: <, <=, >, >=, ==, !=

colorScale [style]
A character vector of valid colors with length 2 or 3

[rule]
NULL or a character vector of valid colors of equal length to styles

dataBar [style]
A character vector of valid colors with length 2 or 3

[rule]
A numeric vector specifying the range of the databar colors. Must be equal length to style

[params\$showValue]
If FALSE the cell value is hidden. Default TRUE

[params\$gradient]
If FALSE color gradient is removed. Default TRUE

[params\$border]
If FALSE the border around the database is hidden. Default TRUE

duplicatedValues / uniqueValues / containsErrors [style]
A Style object

contains [style]
A Style object

[rule]
The text to look for within cells

between [style]
A Style object.

[rule]
A numeric vector of length 2 specifying lower and upper bound (Inclusive)

topN [style]
A Style object

[params\$rank]
A numeric vector of length 1 indicating number of highest values. Default 5L

[params\$percent] If TRUE, uses percentage

bottomN [style]
A Style object

[params\$rank]
A numeric vector of length 1 indicating number of lowest values. Default 5L

[params\$percent]
If TRUE, uses percentage

iconSet [params\$showValue]
If FALSE, the cell value is hidden. Default TRUE

[params\$reverse]
If TRUE, the order is reversed. Default FALSE

[params\$percent]
If TRUE, uses percentage

[params\$iconSet]
Uses one of the implemented icon sets. Values must match the length of the icons in the set 3Arrows, 3ArrowsGray, 3Flags, 3Signs, 3Symbols, 3Symbols2, 3TrafficLights1, 3TrafficLights2, 4Arrows, 4ArrowsGray, 4Rating, 4RedToBlack, 4TrafficLights, 5Arrows, 5ArrowsGray, 5Quarters, 5Rating. The default is 3TrafficLights1.

See Also

Other worksheet content functions: [col_widths-wb](#), [filter-wb](#), [grouping-wb](#), [named_region-wb](#), [row_heights-wb](#), [wb_add_data\(\)](#), [wb_add_data_table\(\)](#), [wb_add_formula\(\)](#), [wb_add_pivot_table\(\)](#), [wb_add_slicer\(\)](#), [wb_add_thread\(\)](#), [wb_freeze_pane\(\)](#), [wb_merge_cells\(\)](#)

Examples

```
wb <- wb_workbook()
wb$add_worksheet("a")
wb$add_data(x = 1:4, col_names = FALSE)
wb$add_conditional_formatting(dims = wb_dims(cols = "A", rows = 1:4), rule = ">2")
```

wb_add_data

*Add data to a worksheet***Description**

Add data to worksheet with optional styling.

Usage

```
wb_add_data(
  wb,
  sheet = current_sheet(),
  x,
  dims = wb_dims(start_row, start_col),
  start_col = 1,
  start_row = 1,
  array = FALSE,
  col_names = TRUE,
  row_names = FALSE,
  with_filter = FALSE,
  name = NULL,
  sep = ", ",
  apply_cell_style = TRUE,
  remove_cell_style = FALSE,
  na.strings = na_strings(),
  inline_strings = TRUE,
  enforce = FALSE,
  ...
)
```

Arguments

wb	A Workbook object containing a worksheet.
sheet	The worksheet to write to. Can be the worksheet index or name.
x	Object to be written. For classes supported look at the examples.
dims	Spreadsheet cell range that will determine start_col and start_row: "A1", "A1:B2", "A:B"
start_col	A vector specifying the starting column to write x to.
start_row	A vector specifying the starting row to write x to.
array	A bool if the function written is of type array
col_names	If TRUE, column names of x are written.
row_names	If TRUE, the row names of x are written.
with_filter	If TRUE, add filters to the column name row. NOTE: can only have one filter per worksheet.

name	The name of a named region if specified.
sep	Only applies to list columns. The separator used to collapse list columns to a character vector e.g. <code>sapply(x\$list_column, paste, collapse = sep)</code> .
apply_cell_style	Should we write cell styles to the workbook
remove_cell_style	keep the cell style?
na.strings	Value used for replacing NA values from x. Default looks if <code>options(openxlsx2.na.strings)</code> is set. Otherwise <code>na_strings()</code> uses the special #N/A value within the workbook.
inline_strings	write characters as inline strings
enforce	enforce that selected dims is filled. For this to work, dims must match x
...	additional arguments

Details

Formulae written using `wb_add_formula()` to a Workbook object will not get picked up by `read_xlsx()`. This is because only the formula is written and left to Excel to evaluate the formula when the file is opened in Excel. The string `"_openxlsx_NA"` is reserved for `openxlsx2`. If the data frame contains this string, the output will be broken.

Supported classes are data frames, matrices and vectors of various types and everything that can be converted into a data frame with `as.data.frame()`. Everything else that the user wants to write should either be converted into a vector or data frame or written in vector or data frame segments. This includes base classes such as `table`, which were coerced internally in the predecessor of this package.

Even vectors and data frames can consist of different classes. Many base classes are covered, though not all and far from all third-party classes. When data of an unknown class is written, it is handled with `as.character()`. It is not possible to write character nodes beginning with `<r>` or `<r/>`. Both are reserved for internal functions. If you need these. You have to wrap the input string in `fmt_txt()`.

The columns of x with class `Date/POSIXt`, `currency`, `accounting`, `hyperlink`, `percentage` are automatically styled as dates, currency, accounting, hyperlinks, percentages respectively.

Functions `wb_add_data()` and `wb_add_data_table()` behave quite similar. The distinction is that the latter creates a table in the worksheet that can be used for different kind of formulas and can be sorted independently, though is less flexible than basic cell regions.

Value

A `wbWorkbook`, invisibly.

See Also

Other workbook wrappers: `base_font-wb`, `col_widths-wb`, `creators-wb`, `grouping-wb`, `row_heights-wb`, `wb_add_chartsheet()`, `wb_add_data_table()`, `wb_add_formula()`, `wb_add_pivot_table()`, `wb_add slicer()`, `wb_add_worksheet()`, `wb_base_colors`, `wb_clone_worksheet()`, `wb_copy_cells()`, `wb_freeze_pane()`, `wb_merge_cells()`, `wb_save()`, `wb_set_last_modified_by()`, `wb_workbook()`

Other worksheet content functions: [col_widths-wb](#), [filter-wb](#), [grouping-wb](#), [named_region-wb](#), [row_heights-wb](#), [wb_add_conditional_formatting\(\)](#), [wb_add_data_table\(\)](#), [wb_add_formula\(\)](#), [wb_add_pivot_table\(\)](#), [wb_add slicer\(\)](#), [wb_add_thread\(\)](#), [wb_freeze_pane\(\)](#), [wb_merge_cells\(\)](#)

Examples

```
## See formatting vignette for further examples.

## Options for default styling (These are the defaults)
options("openxlsx2.dateFormat" = "mm/dd/yyyy")
options("openxlsx2.datetimeFormat" = "yyyy-mm-dd hh:mm:ss")
options("openxlsx2.numFmt" = NULL)

#####
## Create Workbook object and add worksheets
wb <- wb_workbook()

## Add worksheets
wb$add_worksheet("Cars")
wb$add_worksheet("Formula")

x <- mtcars[1:6, ]
wb$add_data("Cars", x, start_col = 2, start_row = 3, row_names = TRUE)

#####
## Hyperlinks
## - vectors/columns with class 'hyperlink' are written as hyperlinks'

v <- rep("https://CRAN.R-project.org/", 4)
names(v) <- paste0("Hyperlink", 1:4) # Optional: names will be used as display text
class(v) <- "hyperlink"
wb$add_data("Cars", x = v, dims = "B32")

#####
## Formulas
## - vectors/columns with class 'formula' are written as formulas'

df <- data.frame(
  x = 1:3, y = 1:3,
  z = paste(paste0("A", 1:3 + 1L), paste0("B", 1:3 + 1L), sep = "+"),
  stringsAsFactors = FALSE
)

class(df$z) <- c(class(df$z), "formula")

wb$add_data(sheet = "Formula", x = df)

#####
# update cell range and add mtcars
xlsxFile <- system.file("extdata", "openxlsx2_example.xlsx", package = "openxlsx2")
wb2 <- wb_load(xlsxFile)

# read dataset with inlinestr
```



```

wb_to_df(wb2)
wb2 <- wb2 %>% wb_add_data(sheet = 1, mtcars, dims = wb_dims(4, 4))
wb_to_df(wb2)

```

wb_add_data_table *Add a data table to a worksheet*

Description

Add data to a worksheet and format as an Excel table.

Usage

```

wb_add_data_table(
  wb,
  sheet = current_sheet(),
  x,
  dims = wb_dims(start_row, start_col),
  start_col = 1,
  start_row = 1,
  col_names = TRUE,
  row_names = FALSE,
  table_style = "TableStyleLight9",
  table_name = NULL,
  with_filter = TRUE,
  sep = ", ",
  first_column = FALSE,
  last_column = FALSE,
  banded_rows = TRUE,
  banded_cols = FALSE,
  apply_cell_style = TRUE,
  remove_cell_style = FALSE,
  na.strings = na_strings(),
  inline_strings = TRUE,
  total_row = FALSE,
  ...
)

```

Arguments

wb	A Workbook object containing a worksheet.
sheet	The worksheet to write to. Can be the worksheet index or name.
x	A data frame
dims	Spreadsheet cell range that will determine start_col and start_row: "A1", "A1:B2", "A:B"
start_col	A vector specifying the starting column to write x to.

start_row	A vector specifying the starting row to write x to.
col_names	If TRUE, column names of x are written.
row_names	If TRUE, the row names of x are written.
table_style	Any table style name or "none" (see vignette("openxlsx2_style_manual"))
table_name	Name of table in workbook. The table name must be unique.
with_filter	If TRUE, columns with have filters in the first row.
sep	Only applies to list columns. The separator used to collapse list columns to a character vector e.g. <code>sapply(x\$list_column, paste, collapse = sep)</code> .

The below options correspond to Excel table options:

- Header Row First Column Filter Button
 Total Row Last Column
 Banded Rows Banded Columns

Table Style Options

first_column	logical. If TRUE, the first column is bold.
last_column	logical. If TRUE, the last column is bold.
banded_rows	logical. If TRUE, rows are color banded.
banded_cols	logical. If TRUE, the columns are color banded.
apply_cell_style	Should we write cell styles to the workbook
remove_cell_style	keep the cell style?
na.strings	Value used for replacing NA values from x. Default looks if <code>options(openxlsx2.na.strings)</code> is set. Otherwise <code>na_strings()</code> uses the special #N/A value within the workbook.
inline_strings	write characters as inline strings
total_row	logical. With the default FALSE no total row is added.
...	additional arguments

Details

Formulae written using `wb_add_formula()` to a Workbook object will not get picked up by `read_xlsx()`. This is because only the formula is written and left to Excel to evaluate the formula when the file is opened in Excel. The string `"_openxlsx2_NA"` is reserved for `openxlsx2`. If the data frame contains this string, the output will be broken.

Supported classes are data frames, matrices and vectors of various types and everything that can be converted into a data frame with `as.data.frame()`. Everything else that the user wants to write should either be converted into a vector or data frame or written in vector or data frame segments. This includes base classes such as `table`, which were coerced internally in the predecessor of this package.

Even vectors and data frames can consist of different classes. Many base classes are covered, though not all and far from all third-party classes. When data of an unknown class is written, it is handled with `as.character()`. It is not possible to write character nodes beginning with `<r>` or `<r/>`. Both are reserved for internal functions. If you need these. You have to wrap the input string in `fmt_txt()`.

The columns of `x` with class `Date/POSIXt`, `currency`, `accounting`, `hyperlink`, `percentage` are automatically styled as dates, currency, accounting, hyperlinks, percentages respectively.

Functions `wb_add_data()` and `wb_add_data_table()` behave quite similar. The distinction is that the latter creates a table in the worksheet that can be used for different kind of formulas and can be sorted independently, though is less flexible than basic cell regions.

Modify total row argument

It is possible to further tweak the total row. In addition to the default `FALSE` possible values are `TRUE` (the `xlsx` file will create column sums each variable).

In addition it is possible to tweak this further using a character string with one of the following functions for each variable: `"average"`, `"count"`, `"countNums"`, `"max"`, `"min"`, `"stdDev"`, `"sum"`, `"var"`. It is possible to leave the cell empty `"none"` or to create a text input using a named character with name `text` like: `c(text = "Total")`. It's also possible to pass other spreadsheet software functions if they return a single value and hence `"SUM"` would work too.

See Also

Other worksheet content functions: [col_widths-wb](#), [filter-wb](#), [grouping-wb](#), [named_region-wb](#), [row_heights-wb](#), [wb_add_conditional_formatting\(\)](#), [wb_add_data\(\)](#), [wb_add_formula\(\)](#), [wb_add_pivot_table\(\)](#), [wb_add_slicer\(\)](#), [wb_add_thread\(\)](#), [wb_freeze_pane\(\)](#), [wb_merge_cells\(\)](#)

Other workbook wrappers: [base_font-wb](#), [col_widths-wb](#), [creators-wb](#), [grouping-wb](#), [row_heights-wb](#), [wb_add_chartsheet\(\)](#), [wb_add_data\(\)](#), [wb_add_formula\(\)](#), [wb_add_pivot_table\(\)](#), [wb_add_slicer\(\)](#), [wb_add_worksheet\(\)](#), [wb_base_colors](#), [wb_clone_worksheet\(\)](#), [wb_copy_cells\(\)](#), [wb_freeze_pane\(\)](#), [wb_merge_cells\(\)](#), [wb_save\(\)](#), [wb_set_last_modified_by\(\)](#), [wb_workbook\(\)](#)

Examples

```
wb <- wb_workbook()$add_worksheet()$
  add_data_table(
    x = as.data.frame(USPersonalExpenditure),
    row_names = TRUE,
    total_row = c(text = "Total", "none", "sum", "sum", "sum", "SUM")
  )
```

wb_add_data_validation

Add data validation to cells in a worksheet

Description

Add Excel data validation to cells

Usage

```

wb_add_data_validation(
  wb,
  sheet = current_sheet(),
  dims = "A1",
  type,
  operator,
  value,
  allow_blank = TRUE,
  show_input_msg = TRUE,
  show_error_msg = TRUE,
  error_style = NULL,
  error_title = NULL,
  error = NULL,
  prompt_title = NULL,
  prompt = NULL,
  ...
)

```

Arguments

wb	A Workbook object
sheet	A name or index of a worksheet
dims	A cell dimension ("A1" or "A1:B2")
type	One of 'whole', 'decimal', 'date', 'time', 'textLength', 'list' (see examples)
operator	One of 'between', 'notBetween', 'equal', 'notEqual', 'greaterThan', 'lessThan', 'greaterThanOrEqualTo', 'lessThanOrEqualTo'
value	a vector of length 1 or 2 depending on operator (see examples)
allow_blank	logical
show_input_msg	logical
show_error_msg	logical
error_style	The icon shown and the options how to deal with such inputs. Default "stop" (cancel), else "information" (prompt popup) or "warning" (prompt accept or change input)
error_title	The error title
error	The error text
prompt_title	The prompt title
prompt	The prompt text
...	additional arguments

Examples

```

wb <- wb_workbook()
wb$add_worksheet("Sheet 1")

```

```

wb$add_worksheet("Sheet 2")

wb$add_data_table(1, x = iris[1:30, ])
wb$add_data_validation(1,
  dims = "A2:C31", type = "whole",
  operator = "between", value = c(1, 9)
)
wb$add_data_validation(1,
  dims = "E2:E31", type = "textLength",
  operator = "between", value = c(4, 6)
)

## Date and Time cell validation
df <- data.frame(
  "d" = as.Date("2016-01-01") + -5:5,
  "t" = as.POSIXct("2016-01-01") + -5:5 * 10000
)
wb$add_data_table(2, x = df)
wb$add_data_validation(2, dims = "A2:A12", type = "date",
  operator = "greaterThanOrEqual", value = as.Date("2016-01-01")
)
wb$add_data_validation(2,
  dims = "B2:B12", type = "time",
  operator = "between", value = df$t[c(4, 8)]
)

#####
## If type == 'list'
# operator argument is ignored.

wb <- wb_workbook()
wb$add_worksheet("Sheet 1")
wb$add_worksheet("Sheet 2")

wb$add_data_table(sheet = 1, x = iris[1:30, ])
wb$add_data(sheet = 2, x = sample(iris$Sepal.Length, 10))

wb$add_data_validation(1, dims = "A2:A31", type = "list", value = "'Sheet 2'!$A$1:$A$10")

```

wb_add_drawing

Add drawings to a worksheet

Description

Add drawings to a worksheet. This requires the `rvg` package.

Usage

```
wb_add_drawing(
```

```

wb,
sheet = current_sheet(),
dims = "A1",
xml,
col_offset = 0,
row_offset = 0,
...
)

```

Arguments

wb	A wbWorkbook
sheet	A sheet in the workbook
dims	The dimension where the drawing is added.
xml	the drawing xml as character or file
col_offset, row_offset	offsets for column and row
...	additional arguments

See Also

[wb_add_chart_xml\(\)](#) [wb_add_image\(\)](#) [wb_add_mschart\(\)](#) [wb_add_plot\(\)](#)

Examples

```

if (requireNamespace("rvg") && interactive()) {

## rvg example
require(rvg)
tmp <- tempfile(fileext = ".xml")
dml_xlsx(file = tmp)
plot(1,1)
dev.off()

wb <- wb_workbook()$
  add_worksheet()$
  add_drawing(xml = tmp)$
  add_drawing(xml = tmp, dims = NULL)
}

```

wb_add_dxfs_style *Set a dxfs styling for the workbook*

Description

These styles are used with conditional formatting and custom table styles.

Usage

```

wb_add_dxfs_style(
    wb,
    name,
    font_name = NULL,
    font_size = NULL,
    font_color = NULL,
    num_fmt = NULL,
    border = NULL,
    border_color = wb_color(getOption("openxlsx2.borderColor", "black")),
    border_style = getOption("openxlsx2.borderStyle", "thin"),
    bg_fill = NULL,
    gradient_fill = NULL,
    text_bold = NULL,
    text_italic = NULL,
    text_underline = NULL,
    ...
)

```

Arguments

wb	A Workbook object.
name	the style name
font_name	the font name
font_size	the font size
font_color	the font color (a <code>wb_color()</code> object)
num_fmt	the number format
border	logical if borders are applied
border_color	the border color
border_style	the border style
bg_fill	any background fill
gradient_fill	any gradient fill
text_bold	logical if text is bold
text_italic	logical if text is italic
text_underline	logical if text is underlined
...	additional arguments passed to <code>create_dxfs_style()</code>

Value

The Workbook object, invisibly

See Also

Other workbook styling functions: [base_font-wb](#), [wb_add_style\(\)](#), [wb_base_colors](#)

Examples

```
wb <- wb_workbook() %>%
  wb_add_worksheet() %>%
  wb_add_dxfs_style(
    name = "nay",
    font_color = wb_color(hex = "FF9C0006"),
    bg_fill = wb_color(hex = "FFFC7CE")
  )
```

wb_add_fill

*Modify the background fill color in a cell region***Description**

Add fill to a cell region.

Usage

```
wb_add_fill(
  wb,
  sheet = current_sheet(),
  dims = "A1",
  color = wb_color(hex = "FFFFFF00"),
  pattern = "solid",
  gradient_fill = "",
  every_nth_col = 1,
  every_nth_row = 1,
  ...
)
```

Arguments

wb	a workbook
sheet	the worksheet
dims	the cell range
color	the colors to apply, e.g. yellow: <code>wb_color(hex = "FFFFFF00")</code>
pattern	various default "none" but others are possible: "solid", "mediumGray", "dark-Gray", "lightGray", "darkHorizontal", "darkVertical", "darkDown", "darkUp", "darkGrid", "darkTrellis", "lightHorizontal", "lightVertical", "lightDown", "lightUp", "lightGrid", "lightTrellis", "gray125", "gray0625"
gradient_fill	a gradient fill xml pattern.
every_nth_col	which col should be filled
every_nth_row	which row should be filled
...	...

Value

The wbWorkbook object, invisibly

See Also

Other styles: [wb_add_border\(\)](#), [wb_add_cell_style\(\)](#), [wb_add_font\(\)](#), [wb_add_named_style\(\)](#), [wb_add_numfmt\(\)](#), [wb_cell_style](#)

Examples

```
wb <- wb_workbook() %>% wb_add_worksheet("S1") %>% wb_add_data("S1", mtcars)
wb <- wb %>% wb_add_fill("S1", dims = "D5:J23", color = wb_color(hex = "FFFFFF00"))
wb <- wb %>% wb_add_fill("S1", dims = "B22:D27", color = wb_color(hex = "FF00FF00"))

wb <- wb %>% wb_add_worksheet("S2") %>% wb_add_data("S2", mtcars)

gradient_fill1 <- '<gradientFill degree="90">
<stop position="0"><color rgb="FF92D050"/></stop>
<stop position="1"><color rgb="FF0070C0"/></stop>
</gradientFill>'
wb <- wb %>% wb_add_fill("S2", dims = "A2:K5", gradient_fill = gradient_fill1)

gradient_fill2 <- '<gradientFill type="path" left="0.2" right="0.8" top="0.2" bottom="0.8">
<stop position="0"><color theme="0"/></stop>
<stop position="1"><color theme="4"/></stop>
</gradientFill>'
wb <- wb %>% wb_add_fill("S2", dims = "A7:K10", gradient_fill = gradient_fill2)
```

wb_add_font

Modify font in a cell region

Description

Modify the font in a cell region with more precision You can specify the font in a cell with other cell styling functions, but `wb_add_font()` gives you more control.

Usage

```
wb_add_font(
  wb,
  sheet = current_sheet(),
  dims = "A1",
  name = "Aptos Narrow",
  color = wb_color(hex = "FF000000"),
  size = "11",
  bold = "",
  italic = "",
  outline = "",
```

```

    strike = "",
    underline = "",
    charset = "",
    condense = "",
    extend = "",
    family = "",
    scheme = "",
    shadow = "",
    vert_align = "",
    ...
)

```

Arguments

wb	A Workbook object
sheet	the worksheet
dims	the cell range
name	Font name: default "Aptos Narrow"
color	An object created by wb_color()
size	Font size: default "11",
bold	bold, "single" or "double", default: ""
italic	italic
outline	outline
strike	strike
underline	underline
charset	charset
condense	condense
extend	extend
family	font family
scheme	font scheme
shadow	shadow
vert_align	vertical alignment
...	...

Details

wb_add_font() provides all the options openxml accepts for a font node, not all have to be set. Usually name, size and color should be what the user wants.

Value

A wbWorkbook, invisibly

See Also

Other styles: [wb_add_border\(\)](#), [wb_add_cell_style\(\)](#), [wb_add_fill\(\)](#), [wb_add_named_style\(\)](#), [wb_add_numfmt\(\)](#), [wb_cell_style](#)

Examples

```
wb <- wb_workbook() %>% wb_add_worksheet("S1") %>% wb_add_data("S1", mtcars)
wb %>% wb_add_font("S1", "A1:K1", name = "Arial", color = wb_color(theme = "4"))
# With chaining
wb <- wb_workbook()$add_worksheet("S1")$add_data("S1", mtcars)
wb$add_font("S1", "A1:K1", name = "Arial", color = wb_color(theme = "4"))
```

wb_add_formula	<i>Add a formula to a cell range in a worksheet</i>
----------------	---

Description

This function can be used to add a formula to a worksheet. In `wb_add_formula()`, you can provide the formula as a character vector.

Usage

```
wb_add_formula(
  wb,
  sheet = current_sheet(),
  x,
  dims = wb_dims(start_row, start_col),
  start_col = 1,
  start_row = 1,
  array = FALSE,
  cm = FALSE,
  apply_cell_style = TRUE,
  remove_cell_style = FALSE,
  enforce = FALSE,
  ...
)
```

Arguments

wb	A Workbook object containing a worksheet.
sheet	The worksheet to write to. (either as index or name)
x	A formula as character vector.
dims	Spreadsheet dimensions that will determine where x spans: "A1", "A1:B2", "A:B"
start_col	A vector specifying the starting column to write to.
start_row	A vector specifying the starting row to write to.

array	A bool if the function written is of type array
cm	A special kind of array function that hides the curly braces in the cell. Add this, if you see "@" inserted into your formulas.
apply_cell_style	Should we write cell styles to the workbook?
remove_cell_style	Should we keep the cell style?
enforce	enforce dims
...	additional arguments

Details

Currently, the local translations of formulas are not supported. Only the English functions work.

The examples below show a small list of possible formulas:

- SUM(B2:B4)
- AVERAGE(B2:B4)
- MIN(B2:B4)
- MAX(B2:B4)
- ...

It is possible to pass vectors to `x`. If `x` is an array formula, it will take `dims` as a reference. For some formulas, the result will span multiple cells (see the `MMULT()` example below). For this type of formula, the output range must be known a priori and passed to `dims`, otherwise only the value of the first cell will be returned. This type of formula, whose result extends over several cells, is only possible with single strings. If a vector is passed, it is only possible to return individual cells.

Value

The workbook, invisibly.

See Also

Other workbook wrappers: [base_font-wb](#), [col_widths-wb](#), [creators-wb](#), [grouping-wb](#), [row_heights-wb](#), [wb_add_chartsheet\(\)](#), [wb_add_data\(\)](#), [wb_add_data_table\(\)](#), [wb_add_pivot_table\(\)](#), [wb_add slicer\(\)](#), [wb_add_worksheet\(\)](#), [wb_base_colors](#), [wb_clone_worksheet\(\)](#), [wb_copy_cells\(\)](#), [wb_freeze_pane\(\)](#), [wb_merge_cells\(\)](#), [wb_save\(\)](#), [wb_set_last_modified_by\(\)](#), [wb_workbook\(\)](#)

Other worksheet content functions: [col_widths-wb](#), [filter-wb](#), [grouping-wb](#), [named_region-wb](#), [row_heights-wb](#), [wb_add_conditional_formatting\(\)](#), [wb_add_data\(\)](#), [wb_add_data_table\(\)](#), [wb_add_pivot_table\(\)](#), [wb_add slicer\(\)](#), [wb_add_thread\(\)](#), [wb_freeze_pane\(\)](#), [wb_merge_cells\(\)](#)

Examples

```
wb <- wb_workbook()$add_worksheet()
wb$add_data(dims = wb_dims(rows = 1, cols = 1:3), x = c(4, 5, 8))

# calculate the sum of elements.
```

```

wb$add_formula(dims = "D1", x = "SUM(A1:C1)")

# array formula with result spanning over multiple cells
mm <- matrix(1:4, 2, 2)

wb$add_worksheet()$
  add_data(x = mm, dims = "A1:B2", col_names = FALSE)$
  add_data(x = mm, dims = "A4:B5", col_names = FALSE)$
  add_formula(x = "MMULT(A1:B2, A4:B5)", dims = "A7:B8", array = TRUE)

```

wb_add_form_control *Add a checkbox, radio button or drop menu to a cell in a worksheet*

Description

You can add Form Control to a cell. The three supported types are a Checkbox, a Radio button, or a Drop menu.

Usage

```

wb_add_form_control(
  wb,
  sheet = current_sheet(),
  dims = "A1",
  type = c("Checkbox", "Radio", "Drop"),
  text = NULL,
  link = NULL,
  range = NULL,
  checked = FALSE
)

```

Arguments

wb	A Workbook object
sheet	A worksheet of the workbook
dims	A single cell as spreadsheet dimension, e.g. "A1".
type	A type "Checkbox" (the default), "Radio" a radio button or "Drop" a drop down menu
text	A text to be shown next to the Checkbox or radio button (optional)
link	A cell range to link to
range	A cell range used as input
checked	A logical indicating if the Checkbox or Radio button is checked

Value

The wbWorkbook object, invisibly.

Examples

```

wb <- wb_workbook() %>% wb_add_worksheet() %>%
  wb_add_form_control()
# Add
wb$add_form_control(dims = "C5", type = "Radio", checked = TRUE)

```

wb_add_ignore_error *Ignore error types on worksheet*

Description

This function allows to hide / ignore certain types of errors shown in a worksheet.

Usage

```

wb_add_ignore_error(
  wb,
  sheet = current_sheet(),
  dims = "A1",
  calculated_column = FALSE,
  empty_cell_reference = FALSE,
  eval_error = FALSE,
  formula = FALSE,
  formula_range = FALSE,
  list_data_validation = FALSE,
  number_stored_as_text = FALSE,
  two_digit_text_year = FALSE,
  unlocked_formula = FALSE,
  ...
)

```

Arguments

wb	A workbook
sheet	A sheet name or index.
dims	Cell range to ignore the error
calculated_column	calculatedColumn
empty_cell_reference	emptyCellReference
eval_error	evalError
formula	formula
formula_range	formulaRange
list_data_validation	listDataValidation

```

number_stored_as_text
    If TRUE, will not display the error if numbers are stored as text.
two_digit_text_year
    twoDigitTextYear
unlocked_formula
    unlockedFormula
...
    additional arguments

```

Value

The wbWorkbook object, invisibly.

wb_add_image	<i>Insert an image into a worksheet</i>
--------------	---

Description

Insert an image into a worksheet

Usage

```

wb_add_image(
  wb,
  sheet = current_sheet(),
  dims = "A1",
  file,
  width = 6,
  height = 3,
  row_offset = 0,
  col_offset = 0,
  units = "in",
  dpi = 300,
  ...
)

```

Arguments

wb	A workbook object
sheet	A name or index of a worksheet
dims	Dimensions where to plot. Default absolute anchor, single cell (eg. "A1") one-CellAnchor, cell range (eg. "A1:D4") twoCellAnchor
file	An image file. Valid file types are: "jpeg", "png", "bmp"
width	Width of figure.
height	Height of figure.
row_offset	offset vector for one or two cell anchor within cell (row)

col_offset	offset vector for one or two cell anchor within cell (column)
units	Units of width and height. Can be "in", "cm" or "px"
dpi	Image resolution used for conversion between units.
...	additional arguments

See Also

[wb_add_chart_xml\(\)](#) [wb_add_drawing\(\)](#) [wb_add_mschart\(\)](#) [wb_add_plot\(\)](#)

Examples

```
img <- system.file("extdata", "einstein.jpg", package = "openxlsx2")

wb <- wb_workbook()$
  add_worksheet()$
  add_image("Sheet 1", dims = "C5", file = img, width = 6, height = 5)$
  add_worksheet()$
  add_image(dims = "B2", file = img)$
  add_worksheet()$
  add_image(dims = "G3", file = img, width = 15, height = 12, units = "cm")
```

 wb_add_mips

wb get and apply MIP section

Description

Read sensitivity labels from files and apply them to workbooks

Usage

```
wb_add_mips(wb, xml = NULL)

wb_get_mips(wb, single_xml = TRUE, quiet = TRUE)
```

Arguments

wb	a workbook
xml	a mips string obtained from wb_get_mips() or a global option "openxlsx2.mips_xml_string"
single_xml	option to define if the string should be exported as single string. helpful if storing as option is desired.
quiet	option to print a MIP section name. This is not always a human readable string.

Details

The MIP section is a special user-defined XML section that is used to create sensitivity labels in workbooks. It consists of a series of XML property nodes that define the sensitivity label. This XML string cannot be created and it is necessary to first load a workbook with a suitable sensitivity label. Once the workbook is loaded, the string `fmips <- wb_get_mips(wb)` can be extracted. This xml string can later be assigned to an `options("openxlsx2.mips_xml_string" = fmips)` option.

The sensitivity label can then be assigned with `wb_add_mips(wb)`. If no xml string is passed, the MIP section is taken from the option. This should make it easier for users to read the section from a specific workbook, save it to a file or string and copy it to an option via the .Rprofile.

Value

the workbook invisible (`wb_add_mips()`) or the xml string (`wb_get_mips()`)

<code>wb_add_mschart</code>	<i>Add mschart object to a worksheet</i>
-----------------------------	--

Description

Add mschart object to a worksheet

Usage

```
wb_add_mschart(
  wb,
  sheet = current_sheet(),
  dims = NULL,
  graph,
  col_offset = 0,
  row_offset = 0,
  ...
)
```

Arguments

<code>wb</code>	a workbook
<code>sheet</code>	the sheet on which the graph will appear
<code>dims</code>	the dimensions where the sheet will appear
<code>graph</code>	mschart object
<code>col_offset, row_offset</code>	offsets for column and row
<code>...</code>	additional arguments

See Also

[wb_data\(\)](#) [wb_add_chart_xml\(\)](#) [wb_add_image](#) [wb_add_mschart\(\)](#) [wb_add_plot](#)

Examples

```

if (requireNamespace("mschart")) {
  require(mschart)

  ## Add mschart to worksheet (adds data and chart)
  scatter <- ms_scatterchart(data = iris, x = "Sepal.Length", y = "Sepal.Width", group = "Species")
  scatter <- chart_settings(scatter, scatterstyle = "marker")

  wb <- wb_workbook() %>%
    wb_add_worksheet() %>%
    wb_add_mschart(dims = "F4:L20", graph = scatter)

  ## Add mschart to worksheet and use available data
  wb <- wb_workbook() %>%
    wb_add_worksheet() %>%
    wb_add_data(x = mtcars, dims = "B2")

  # create wb_data object
  dat <- wb_data(wb, 1, dims = "B2:E6")

  # call ms_scatterplot
  data_plot <- ms_scatterchart(
    data = dat,
    x = "mpg",
    y = c("disp", "hp"),
    labels = c("disp", "hp")
  )

  # add the scatterplot to the data
  wb <- wb %>%
    wb_add_mschart(dims = "F4:L20", graph = data_plot)
}

```

wb_add_named_style *Apply styling to a cell region with a named style*

Description

Set the styling to a named style for a cell region. Use `wb_add_cell_style()` to style a cell region with custom parameters. A named style is the one in spreadsheet software, like "Normal", "Warning".

Usage

```

wb_add_named_style(
  wb,
  sheet = current_sheet(),
  dims = "A1",
  name = "Normal",

```

```

    font_name = NULL,
    font_size = NULL
)

```

Arguments

wb	A wbWorkbook object
sheet	A worksheet
dims	A cell range
name	The named style name.
font_name, font_size	optional else the default of the theme

Value

The wbWorkbook, invisibly

See Also

Other styles: [wb_add_border\(\)](#), [wb_add_cell_style\(\)](#), [wb_add_fill\(\)](#), [wb_add_font\(\)](#), [wb_add_numfmt\(\)](#), [wb_cell_style](#)

wb_add_numfmt	<i>Modify number formatting in a cell region</i>
---------------	--

Description

Add number formatting to a cell region. You can use a number format created by [create_numfmt\(\)](#).

Usage

```
wb_add_numfmt(wb, sheet = current_sheet(), dims = "A1", numfmt)
```

Arguments

wb	A Workbook
sheet	the worksheet
dims	the cell range
numfmt	either an id or a character

Details

The list of number formats ID is located in the **Details** section of [create_cell_style\(\)](#).

Value

The wbWorkbook object, invisibly.

See Also

Other styles: [wb_add_border\(\)](#), [wb_add_cell_style\(\)](#), [wb_add_fill\(\)](#), [wb_add_font\(\)](#), [wb_add_named_style\(\)](#), [wb_cell_style](#)

Examples

```
wb <- wb_workbook() %>% wb_add_worksheet("S1") %>% wb_add_data("S1", mtcars)
wb %>% wb_add_numfmt("S1", dims = "F1:F33", numfmt = "#.0")
# Chaining
wb <- wb_workbook()$add_worksheet("S1")$add_data("S1", mtcars)
wb$add_numfmt("S1", "A1:A33", numfmt = 1)
```

wb_add_page_break	<i>Add a page break to a worksheet</i>
-------------------	--

Description

Insert page breaks into a worksheet

Usage

```
wb_add_page_break(wb, sheet = current_sheet(), row = NULL, col = NULL)
```

Arguments

wb	A workbook object
sheet	A name or index of a worksheet
row, col	Either a row number or column number. One must be NULL

See Also

[wb_add_worksheet\(\)](#)

Examples

```
wb <- wb_workbook()
wb$add_worksheet("Sheet 1")
wb$add_data(sheet = 1, x = iris)

wb$add_page_break(sheet = 1, row = 10)
wb$add_page_break(sheet = 1, row = 20)
wb$add_page_break(sheet = 1, col = 2)

## In Excel: View tab -> Page Break Preview
```

wb_add_pivot_table *Add a pivot table to a worksheet*

Description

The data must be specified using `wb_data()` to ensure the function works. The sheet will be empty unless it is opened in spreadsheet software. Find more details in the [section about pivot tables](#) in the openxlsx2 book.

Usage

```
wb_add_pivot_table(
  wb,
  x,
  sheet = next_sheet(),
  dims = "A3",
  filter,
  rows,
  cols,
  data,
  fun,
  params,
  pivot_table,
  slicer
)
```

Arguments

wb	A Workbook object containing a #' worksheet.
x	A data.frame that inherits the <code>wb_data</code> class.
sheet	A worksheet containing a #'
dims	The worksheet cell where the pivot table is placed
filter	The column name(s) of x used for filter.
rows	The column name(s) of x used as rows
cols	The column names(s) of x used as cols
data	The column name(s) of x used as data
fun	A vector of functions to be used with data. See Details for the list of available options.
params	A list of parameters to modify pivot table creation. See Details for available options.
pivot_table	An optional name for the pivot table
slicer	Any additional column name(s) of x used as slicer

Details

The pivot table is not actually written to the worksheet, therefore the cell region has to remain empty. What is written to the workbook is something like a recipe how the spreadsheet software has to construct the pivot table when opening the file.

It is possible to add slicers to the pivot table. For this the pivot table has to be named and the variable used as slicer, must be part of the selected pivot table names (cols, rows, filter, or slicer). If these criteria are matched, a slicer can be added using `wb_add_slicer()`.

Be aware that you should always test on a copy if a param argument works with a pivot table. Not only to check if the desired effect appears, but first and foremost if the file loads. Wildly mixing params might brick the output file and cause spreadsheet software to crash.

fun can be any of AVERAGE, COUNT, COUNTA, MAX, MIN, PRODUCT, STDEV, STDEVP, SUM, VAR, VARP.

show_data_as can be any of normal, difference, percent, percentDiff, runTotal, percentOfRow, percentOfCol, percentOfTotal, index.

It is possible to calculate data fields if the formula is assigned as a variable name for the field to calculate. This would look like this: `data = c("am", "disp/cyl" = "New")`

Possible params arguments are listed below. Pivot tables accepts more parameters, but they were either not tested or misbehaved (probably because we misunderstood how the parameter should be used).

Boolean arguments:

- `apply_alignment_formats`
- `apply_number_formats`
- `apply_border_formats`
- `apply_font_formats`
- `apply_pattern_formats`
- `apply_width_height_formats`
- `no_style`
- `compact`
- `outline`
- `compact_data`
- `row_grand_totals`
- `col_grand_totals`

Table styles accepting character strings:

- `auto_format_id`: style id as character in the range of 4096 to 4117
- `table_style`: a predefined (pivot) table style "TableStyleMedium23"
- `show_data_as`: accepts character strings as listed above

Miscellaneous:

- `numfmt`: accepts vectors of the form `c(formatCode = "0.0%")`
- `choose`: select variables in the form of a named logical vector like `c(agegp = 'x > "25-34"')` for the `esoph` dataset.
- `sort_item`: named list of index or character vectors

See Also[wb_data\(\)](#)

Other workbook wrappers: [base_font-wb](#), [col_widths-wb](#), [creators-wb](#), [grouping-wb](#), [row_heights-wb](#), [wb_add_chartsheet\(\)](#), [wb_add_data\(\)](#), [wb_add_data_table\(\)](#), [wb_add_formula\(\)](#), [wb_add slicer\(\)](#), [wb_add_worksheet\(\)](#), [wb_base_colors](#), [wb_clone_worksheet\(\)](#), [wb_copy_cells\(\)](#), [wb_freeze_pane\(\)](#), [wb_merge_cells\(\)](#), [wb_save\(\)](#), [wb_set_last_modified_by\(\)](#), [wb_workbook\(\)](#)

Other worksheet content functions: [col_widths-wb](#), [filter-wb](#), [grouping-wb](#), [named_region-wb](#), [row_heights-wb](#), [wb_add_conditional_formatting\(\)](#), [wb_add_data\(\)](#), [wb_add_data_table\(\)](#), [wb_add_formula\(\)](#), [wb_add slicer\(\)](#), [wb_add_thread\(\)](#), [wb_freeze_pane\(\)](#), [wb_merge_cells\(\)](#)

Examples

```
wb <- wb_workbook() %>% wb_add_worksheet() %>% wb_add_data(x = mtcars)

df <- wb_data(wb, sheet = 1)

wb <- wb %>%
  # default pivot table
  wb_add_pivot_table(df, dims = "A3",
    filter = "am", rows = "cyl", cols = "gear", data = "disp"
  ) %>%
  # with parameters
  wb_add_pivot_table(df,
    filter = "am", rows = "cyl", cols = "gear", data = "disp",
    params = list(no_style = TRUE, numfmt = c(formatCode = "##0.0"))
  )
```

wb_add_plot*Insert the current plot into a worksheet*

Description

The current plot is saved to a temporary image file using [grDevices::dev.copy\(\)](#) This file is then written to the workbook using [wb_add_image\(\)](#).

Usage

```
wb_add_plot(
  wb,
  sheet = current_sheet(),
  dims = "A1",
  width = 6,
  height = 4,
  row_offset = 0,
  col_offset = 0,
  file_type = "png",
  units = "in",
```

```

    dpi = 300,
    ...
  )

```

Arguments

wb	A workbook object
sheet	A name or index of a worksheet
dims	Worksheet dimension, single cell ("A1") or cell range ("A1:D4")
width	Width of figure. Defaults to 6 in.
height	Height of figure . Defaults to 4 in.
row_offset, col_offset	Offset for column and row
file_type	File type of image
units	Units of width and height. Can be "in", "cm" or "px"
dpi	Image resolution
...	additional arguments

See Also

[wb_add_chart_xml\(\)](#) [wb_add_drawing\(\)](#) [wb_add_image\(\)](#) [wb_add_mschart\(\)](#)

Examples

```

if (requireNamespace("ggplot2") && interactive()) {
  ## Create a new workbook
  wb <- wb_workbook()

  ## Add a worksheet
  wb$add_worksheet("Sheet 1", grid_lines = FALSE)

  ## create plot objects
  require(ggplot2)
  p1 <- ggplot(mtcars, aes(x = mpg, fill = as.factor(gear))) +
    ggtitle("Distribution of Gas Mileage") +
    geom_density(alpha = 0.5)
  p2 <- ggplot(Orange, aes(x = age, y = circumference, color = Tree)) +
    geom_point() + geom_line()

  ## Insert currently displayed plot to sheet 1, row 1, column 1
  print(p1) # plot needs to be showing
  wb$add_plot(1, width = 5, height = 3.5, file_type = "png", units = "in")

  ## Insert plot 2
  print(p2)
  wb$add_plot(1, dims = "J2", width = 16, height = 10, file_type = "png", units = "cm")
}

```

wb_add_slicer	<i>Add a slicer to a pivot table</i>
---------------	--------------------------------------

Description

Add a slicer to a previously created pivot table. This function is still experimental and might be changed/improved in upcoming releases.

Usage

```
wb_add_slicer(
  wb,
  x,
  dims = "A1",
  sheet = current_sheet(),
  pivot_table,
  slicer,
  params
)
```

Arguments

wb	A Workbook object containing a #' worksheet.
x	A data.frame that inherits the wb_data class.
dims	The worksheet cell where the pivot table is placed
sheet	A worksheet containing a #'
pivot_table	The name of a pivot table on the selected sheet
slicer	A variable used as slicer for the pivot table
params	A list of parameters to modify pivot table creation. See Details for available options.

Details

This assumes that the slicer variable initialization has happened before. Unfortunately, it is unlikely that we can guarantee this for loaded workbooks, and we *strictly* discourage users from attempting this. If the variable has not been initialized properly, this may cause the spreadsheet software to crash.

Possible params arguments are listed below.

- edit_as: "twoCell" to place the slicer into the cells
- style: "SlicerStyleLight2"
- column_count: integer used as column count
- caption: string used for a caption
- sort_order: "descending" / "ascending"
- choose: select variables in the form of a named logical vector like `c(agegp = 'x > "25-34"')` for the esoph dataset.

See Also

Other workbook wrappers: [base_font-wb](#), [col_widths-wb](#), [creators-wb](#), [grouping-wb](#), [row_heights-wb](#), [wb_add_chartsheet\(\)](#), [wb_add_data\(\)](#), [wb_add_data_table\(\)](#), [wb_add_formula\(\)](#), [wb_add_pivot_table\(\)](#), [wb_add_worksheet\(\)](#), [wb_base_colors](#), [wb_clone_worksheet\(\)](#), [wb_copy_cells\(\)](#), [wb_freeze_pane\(\)](#), [wb_merge_cells\(\)](#), [wb_save\(\)](#), [wb_set_last_modified_by\(\)](#), [wb_workbook\(\)](#)

Other worksheet content functions: [col_widths-wb](#), [filter-wb](#), [grouping-wb](#), [named_region-wb](#), [row_heights-wb](#), [wb_add_conditional_formatting\(\)](#), [wb_add_data\(\)](#), [wb_add_data_table\(\)](#), [wb_add_formula\(\)](#), [wb_add_pivot_table\(\)](#), [wb_add_thread\(\)](#), [wb_freeze_pane\(\)](#), [wb_merge_cells\(\)](#)

Examples

```
wb <- wb_workbook() %>%
  wb_add_worksheet() %>% wb_add_data(x = mtcars)

df <- wb_data(wb, sheet = 1)

wb <- wb %>%
  wb_add_pivot_table(
    df, dims = "A3", slicer = "vs", rows = "cyl", cols = "gear", data = "disp",
    pivot_table = "mtcars"
  ) %>%
  wb_add_slicer(x = df, slicer = "vs", pivot_table = "mtcars")
```

wb_add_sparklines *Add sparklines to a worksheet*

Description

Add sparklines to a worksheet

Usage

```
wb_add_sparklines(wb, sheet = current_sheet(), sparklines)
```

Arguments

wb	A wbWorkbook
sheet	sheet to add the sparklines to
sparklines	sparklines object created with create_sparklines()

See Also

[create_sparklines\(\)](#)

Examples

```
s1 <- create_sparklines("Sheet 1", dims = "A3:K3", sqref = "L3")
wb <- wb_workbook() %>%
  wb_add_worksheet() %>%
  wb_add_data(x = mtcars) %>%
  wb_add_sparklines(sparklines = s1)
```

wb_add_style	<i>Set the default style in a workbook</i>
--------------	--

Description

wb wrapper to add style to workbook

Usage

```
wb_add_style(wb, style = NULL, style_name = NULL)
```

Arguments

wb	A workbook
style	style xml character, created by a create_*(<i>)</i> function.
style_name	style name used optional argument

Value

The wbWorkbook object, invisibly.

See Also

- [create_border\(\)](#)
- [create_cell_style\(\)](#)
- [create_dxfs_style\(\)](#)
- [create_fill\(\)](#)
- [create_font\(\)](#)
- [create_numfmt\(\)](#)

Other workbook styling functions: [base_font-wb](#), [wb_add_dxfs_style\(\)](#), [wb_base_colors](#)

Examples

```
yellow_f <- wb_color(hex = "FF9C6500")
yellow_b <- wb_color(hex = "FFFFEB9C")

yellow <- create_dxfs_style(font_color = yellow_f, bg_fill = yellow_b)
wb <- wb_workbook() %>% wb_add_style(yellow)
```

wb_add_thread	<i>Add threaded comments to a cell in a worksheet</i>
---------------	---

Description

These functions allow adding thread comments to spreadsheets. This is not yet supported by all spreadsheet software. A threaded comment must be tied to a person created by [wb_add_person\(\)](#).

Usage

```
wb_add_thread(
    wb,
    sheet = current_sheet(),
    dims = "A1",
    comment = NULL,
    person_id,
    reply = FALSE,
    resolve = FALSE
)

wb_get_thread(wb, sheet = current_sheet(), dims = NULL)
```

Arguments

wb	A workbook
sheet	A worksheet
dims	A cell
comment	The text to add, a character vector.
person_id	the person Id this should be added. The default is <code>getOption("openxlsx2.thread_id")</code> if set.
reply	Is the comment a reply? (default FALSE)
resolve	Should the comment be resolved? (default FALSE)

Details

If a threaded comment is added, it needs a person attached to it. The default is to create a person with provider id "None". Other providers are possible with specific values for id and user_id. If you require the following, create a workbook via spreadsheet software load it and get the values with [wb_get_person\(\)](#)

See Also

[wb_add_comment\(\)](#) [person-wb](#)

Other worksheet content functions: [col_widths-wb](#), [filter-wb](#), [grouping-wb](#), [named_region-wb](#), [row_heights-wb](#), [wb_add_conditional_formatting\(\)](#), [wb_add_data\(\)](#), [wb_add_data_table\(\)](#), [wb_add_formula\(\)](#), [wb_add_pivot_table\(\)](#), [wb_add_slicer\(\)](#), [wb_freeze_pane\(\)](#), [wb_merge_cells\(\)](#)

Examples

```

wb <- wb_workbook()$add_worksheet()
# Add a person to the workbook.
wb$add_person(name = "someone who likes to edit workbooks")

pid <- wb$get_person(name = "someone who likes to edit workbooks")$id

# write a comment to a thread, reply to one and solve some
wb <- wb %>%
  wb_add_thread(dims = "A1", comment = "wow it works!", person_id = pid) %>%
  wb_add_thread(dims = "A2", comment = "indeed", person_id = pid, resolve = TRUE) %>%
  wb_add_thread(dims = "A1", comment = "so cool", person_id = pid, reply = TRUE)

```

wb_add_worksheet	<i>Add a worksheet to a workbook</i>
------------------	--------------------------------------

Description

Add a worksheet to a [wbWorkbook](#) is the first step to build a workbook. With the function, you can also set the sheet view with zoom, set headers and footers as well as other features. See the function arguments.

Usage

```

wb_add_worksheet(
  wb,
  sheet = next_sheet(),
  grid_lines = TRUE,
  row_col_headers = TRUE,
  tab_color = NULL,
  zoom = 100,
  header = NULL,
  footer = NULL,
  odd_header = header,
  odd_footer = footer,
  even_header = header,
  even_footer = footer,
  first_header = header,
  first_footer = footer,
  visible = c("true", "false", "hidden", "visible", "veryhidden"),
  has_drawing = FALSE,
  paper_size = getOption("openxlsx2.paperSize", default = 9),
  orientation = getOption("openxlsx2.orientation", default = "portrait"),
  hdpi = getOption("openxlsx2.hdpi", default = getOption("openxlsx2.dpi", default = 300)),
  vdpi = getOption("openxlsx2.vdpi", default = getOption("openxlsx2.dpi", default = 300)),
  ...
)

```

Arguments

wb	A wbWorkbook object to attach the new worksheet
sheet	A name for the new worksheet
grid_lines	A logical. If FALSE, the worksheet grid lines will be hidden.
row_col_headers	A logical. If FALSE, the worksheet colname and rowname will be hidden.
tab_color	Color of the sheet tab. A <code>wb_color()</code> , a valid color (belonging to <code>grDevices::colors()</code>) or a valid hex color beginning with "#".
zoom	The sheet zoom level, a numeric between 10 and 400 as a percentage. (A zoom value smaller than 10 will default to 10.)
header, odd_header, even_header, first_header, footer, odd_footer, even_footer, first_footer	Character vector of length 3 corresponding to positions left, center, right. header and footer are used to default additional arguments. Setting even, odd, or first, overrides header/footer. Use NA to skip a position.
visible	If FALSE, sheet is hidden else visible.
has_drawing	If TRUE prepare a drawing output (TODO does this work?)
paper_size	An integer corresponding to a paper size. See <code>wb_page_setup()</code> for details.
orientation	One of "portrait" or "landscape"
hdpi, vdpi	Horizontal and vertical DPI. Can be set with <code>options("openxlsx2.dpi" = X)</code> , <code>options("openxlsx2.hdpi" = X)</code> or <code>options("openxlsx2.vdpi" = X)</code>
...	Additional arguments

Details

Headers and footers can contain special tags

- **&[Page]** Page number
- **&[Pages]** Number of pages
- **&[Date]** Current date
- **&[Time]** Current time
- **&[Path]** File path
- **&[File]** File name
- **&[Tab]** Worksheet name

Value

The wbWorkbook object, invisibly.

See Also

Other workbook wrappers: `base_font-wb`, `col_widths-wb`, `creators-wb`, `grouping-wb`, `row_heights-wb`, `wb_add_chartsheet()`, `wb_add_data()`, `wb_add_data_table()`, `wb_add_formula()`, `wb_add_pivot_table()`, `wb_add_slicer()`, `wb_base_colors`, `wb_clone_worksheet()`, `wb_copy_cells()`, `wb_freeze_pane()`, `wb_merge_cells()`, `wb_save()`, `wb_set_last_modified_by()`, `wb_workbook()`

Examples

```

## Create a new workbook
wb <- wb_workbook()

## Add a worksheet
wb$add_worksheet("Sheet 1")
## No grid lines
wb$add_worksheet("Sheet 2", grid_lines = FALSE)
## A red tab color
wb$add_worksheet("Sheet 3", tab_color = wb_color("red"))
## All options combined with a zoom of 40%
wb$add_worksheet("Sheet 4", grid_lines = FALSE, tab_color = wb_color(hex = "#4F81BD"), zoom = 40)

## Headers and Footers
wb$add_worksheet("Sheet 5",
  header = c("ODD HEAD LEFT", "ODD HEAD CENTER", "ODD HEAD RIGHT"),
  footer = c("ODD FOOT RIGHT", "ODD FOOT CENTER", "ODD FOOT LEFT"),
  even_header = c("EVEN HEAD LEFT", "EVEN HEAD CENTER", "EVEN HEAD RIGHT"),
  even_footer = c("EVEN FOOT RIGHT", "EVEN FOOT CENTER", "EVEN FOOT LEFT"),
  first_header = c("TOP", "OF FIRST", "PAGE"),
  first_footer = c("BOTTOM", "OF FIRST", "PAGE")
)

wb$add_worksheet("Sheet 6",
  header = c("&[Date]", "ALL HEAD CENTER 2", "&[Page] / &[Pages]"),
  footer = c("&[Path]&[File]", NA, "&[Tab]"),
  first_header = c(NA, "Center Header of First Page", NA),
  first_footer = c(NA, "Center Footer of First Page", NA)
)

wb$add_worksheet("Sheet 7",
  header = c("ALL HEAD LEFT 2", "ALL HEAD CENTER 2", "ALL HEAD RIGHT 2"),
  footer = c("ALL FOOT RIGHT 2", "ALL FOOT CENTER 2", "ALL FOOT LEFT 2")
)

wb$add_worksheet("Sheet 8",
  first_header = c("FIRST ONLY L", NA, "FIRST ONLY R"),
  first_footer = c("FIRST ONLY L", NA, "FIRST ONLY R")
)

## Need data on worksheet to see all headers and footers
wb$add_data(sheet = 5, 1:400)
wb$add_data(sheet = 6, 1:400)
wb$add_data(sheet = 7, 1:400)
wb$add_data(sheet = 8, 1:400)

```

Description

Modify / get the default colors of the workbook.

Usage

```
wb_set_base_colors(wb, theme = "Office", ...)
```

```
wb_get_base_colors(wb, xml = FALSE, plot = TRUE)
```

Arguments

wb	A workbook object
theme	a predefined color theme
...	optional parameters
xml	Logical if xml string should be returned
plot	Logical if a barplot of the colors should be returned

Details

Theme must be any of the following: "Aspect", "Blue", "Blue II", "Blue Green", "Blue Warm", "Greyscale", "Green", "Green Yellow", "Marquee", "Median", "Office", "Office 2007 - 2010", "Office 2013 - 2022", "Orange", "Orange Red", "Paper", "Red", "Red Orange", "Red Violet", "Slipstream", "Violet", "Violet II", "Yellow", "Yellow Orange"

See Also

Other workbook styling functions: [base_font-wb](#), [wb_add_dxfs_style\(\)](#), [wb_add_style\(\)](#)

Other workbook wrappers: [base_font-wb](#), [col_widths-wb](#), [creators-wb](#), [grouping-wb](#), [row_heights-wb](#), [wb_add_chartsheet\(\)](#), [wb_add_data\(\)](#), [wb_add_data_table\(\)](#), [wb_add_formula\(\)](#), [wb_add_pivot_table\(\)](#), [wb_add_slicer\(\)](#), [wb_add_worksheet\(\)](#), [wb_clone_worksheet\(\)](#), [wb_copy_cells\(\)](#), [wb_freeze_pane\(\)](#), [wb_merge_cells\(\)](#), [wb_save\(\)](#), [wb_set_last_modified_by\(\)](#), [wb_workbook\(\)](#)

Examples

```
wb <- wb_workbook()
wb$get_base_colors()
wb$set_base_colors(theme = 3)
wb$set_base_colors(theme = "Violet II")
wb$get_base_colours()
```

wb_cell_style	<i>Apply styling to a cell region</i>
---------------	---------------------------------------

Description

Setting a style across only impacts cells that are not yet part of a workbook. The effect is similar to setting the cell style for all cells in a row independently, though much quicker and less memory consuming.

Usage

```
wb_get_cell_style(wb, sheet = current_sheet(), dims)
```

```
wb_set_cell_style(wb, sheet = current_sheet(), dims, style)
```

```
wb_set_cell_style_across(  
  wb,  
  sheet = current_sheet(),  
  style,  
  cols = NULL,  
  rows = NULL  
)
```

Arguments

wb	A wbWorkbook object
sheet	sheet
dims	A cell range in the worksheet
style	A style or a cell with a certain style
cols	The columns the style will be applied to, either "A:D" or 1:4
rows	The rows the style will be applied to

Value

A Workbook object

See Also

Other styles: [wb_add_border\(\)](#), [wb_add_cell_style\(\)](#), [wb_add_fill\(\)](#), [wb_add_font\(\)](#), [wb_add_named_style\(\)](#), [wb_add_numfmt\(\)](#)

Examples

```
# set a style in b1
wb <- wb_workbook()$add_worksheet()$
  add_numfmt(dims = "B1", numfmt = "#,0")

# get style from b1 to assign it to a1
numfmt <- wb$get_cell_style(dims = "B1")

# assign style to a1
wb$set_cell_style(dims = "A1", style = numfmt)
wb <- wb_workbook() %>%
  wb_add_worksheet() %>%
  wb_add_fill(dims = "C3", color = wb_color("yellow")) %>%
  wb_set_cell_style_across(style = "C3", cols = "C:D", rows = 3:4)
```

wb_clean_sheet	<i>Remove all values in a worksheet</i>
----------------	---

Description

Remove content of a worksheet completely, or a region if specifying dims.

Usage

```
wb_clean_sheet(
  wb,
  sheet = current_sheet(),
  dims = NULL,
  numbers = TRUE,
  characters = TRUE,
  styles = TRUE,
  merged_cells = TRUE
)
```

Arguments

wb	A Workbook object
sheet	sheet to clean
dims	spreadsheet dimensions (optional)
numbers	remove all numbers
characters	remove all characters
styles	remove all styles
merged_cells	remove all merged_cells

Value

A Workbook object

wb_clone_sheet_style *Apply styling from a sheet to another within a workbook*

Description

This function can be used to apply styling from a cell range, and apply it to another cell range.

Usage

```
wb_clone_sheet_style(wb, from = current_sheet(), to)
```

Arguments

wb	A workbook
from	sheet we select the style from
to	sheet to apply the style to

wb_clone_worksheet *Create copies of a worksheet within a workbook*

Description

Create a copy of a worksheet in the same wbWorkbook object.

Cloning is possible only to a limited extent. References to sheet names in formulas, charts, pivot tables, etc. may not be updated. Some elements like named ranges and slicers cannot be cloned yet.

Cloning from another workbook is still an experimental feature and might not work reliably. Cloning data, media, charts and tables should work. Slicers and pivot tables as well as everything everything relying on dxfs styles (e.g. custom table styles and conditional formatting) is currently not implemented. Formula references are not updated to reflect interactions between workbooks.

Usage

```
wb_clone_worksheet(wb, old = current_sheet(), new = next_sheet(), from = NULL)
```

Arguments

wb	A wbWorkbook object
old	Name of existing worksheet to copy
new	Name of the new worksheet to create
from	(optional) Workbook to clone old from

Value

The wbWorkbook object, invisibly.

See Also

Other workbook wrappers: [base_font-wb](#), [col_widths-wb](#), [creators-wb](#), [grouping-wb](#), [row_heights-wb](#), [wb_add_chartsheet\(\)](#), [wb_add_data\(\)](#), [wb_add_data_table\(\)](#), [wb_add_formula\(\)](#), [wb_add_pivot_table\(\)](#), [wb_add slicer\(\)](#), [wb_add_worksheet\(\)](#), [wb_base_colors](#), [wb_copy_cells\(\)](#), [wb_freeze_pane\(\)](#), [wb_merge_cells\(\)](#), [wb_save\(\)](#), [wb_set_last_modified_by\(\)](#), [wb_workbook\(\)](#)

Examples

```
# Create a new workbook
wb <- wb_workbook()

# Add worksheets
wb$add_worksheet("Sheet 1")
wb$clone_worksheet("Sheet 1", new = "Sheet 2")
# Take advantage of waiver functions
wb$clone_worksheet(old = "Sheet 1")

## cloning from another workbook

# create a workbook
wb <- wb_workbook()$
add_worksheet("NOT_SUM")$
  add_data(x = head(iris))$
  add_fill(dims = "A1:B2", color = wb_color("yellow"))$
  add_border(dims = "B2:C3")

# we will clone this styled chart into another workbook
f1 <- system.file("extdata", "xlsx2_sheet.xlsx", package = "openxlsx2")
wb_from <- wb_load(f1)

# clone styles and shared strings
wb$clone_worksheet(old = "SUM", new = "SUM", from = wb_from)
```

wb_color

Helper to create a color

Description

Creates a wbColour object.

Usage

```
wb_color(
  name = NULL,
  auto = NULL,
  indexed = NULL,
  hex = NULL,
  theme = NULL,
```

```

    tint = NULL
  )

```

Arguments

name	A name of a color known to R either as name or RGB/ARGB value.
auto	A boolean.
indexed	An indexed color value. This color has to be provided by the workbook.
hex	A rgb color either a ARGB hex value or RGB hex value With or without leading "#".
theme	A zero based index referencing a value in the theme.
tint	A tint value applied. Range from -1 (dark) to 1 (light).

Value

a wbColour object

See Also

[wb_get_base_colors\(\)](#) [grDevices::colors\(\)](#)

wb_comment

Helper to create a comment object

Description

Creates a wbComment object. Use with [wb_add_comment\(\)](#) to add to a worksheet location.

Usage

```

wb_comment(
  text = NULL,
  style = NULL,
  visible = FALSE,
  author = getOption("openxlsx2.creator"),
  width = 2,
  height = 4
)

```

Arguments

text	Comment text. Character vector. or a fmt_txt() string.
style	A Style object or list of style objects the same length as comment vector.
visible	Is comment visible? Default: FALSE.
author	Author of comment. A string. By default, will look at <code>options("openxlsx2.creator")</code> . Otherwise, will check the system username.
width	Textbox integer width in number of cells
height	Textbox integer height in number of cells

Value

A wbComment object

Examples

```

wb <- wb_workbook()
wb$add_worksheet("Sheet 1")

# write comment without author
c1 <- wb_comment(text = "this is a comment", author = "", visible = TRUE)
wb$add_comment(dims = "B10", comment = c1)

# Write another comment with author information
c2 <- wb_comment(text = "this is another comment", author = "Marco Polo")
wb$add_comment(sheet = 1, dims = "C10", comment = c2)

# write a styled comment with system author
s1 <- create_font(b = "true", color = wb_color(hex = "FFFF0000"), sz = "12")
s2 <- create_font(color = wb_color(hex = "FF000000"), sz = "9")
c3 <- wb_comment(text = c("This Part Bold red\n\n", "This part black"), style = c(s1, s2))

wb$add_comment(sheet = 1, dims = wb_dims(3, 6), comment = c3)

```

wb_copy_cells

Copy cells around within a worksheet

Description

Copy cells around within a worksheet

Usage

```

wb_copy_cells(
  wb,
  sheet = current_sheet(),
  dims = "A1",
  data,
  as_value = FALSE,
  as_ref = FALSE,
  transpose = FALSE,
  ...
)

```

Arguments

wb	A workbook
sheet	a worksheet
dims	A cell where to place the copy

data	A wb_data object containing cells to copy
as_value	Should a copy of the value be written?
as_ref	Should references to the cell be written?
transpose	Should the data be written transposed?
...	additional arguments passed to <code>add_data()</code> if used with <code>as_value</code>

Value

the `wbWorkbook` invisibly

See Also

[wb_data\(\)](#)

Other workbook wrappers: [base_font-wb](#), [col_widths-wb](#), [creators-wb](#), [grouping-wb](#), [row_heights-wb](#), [wb_add_chartsheet\(\)](#), [wb_add_data\(\)](#), [wb_add_data_table\(\)](#), [wb_add_formula\(\)](#), [wb_add_pivot_table\(\)](#), [wb_add_slicer\(\)](#), [wb_add_worksheet\(\)](#), [wb_base_colors](#), [wb_clone_worksheet\(\)](#), [wb_freeze_pane\(\)](#), [wb_merge_cells\(\)](#), [wb_save\(\)](#), [wb_set_last_modified_by\(\)](#), [wb_workbook\(\)](#)

Examples

```
wb <- wb_workbook()$
add_worksheet()$
  add_data(x = mtcars)$
  add_fill(dims = "A1:F1", color = wb_color("yellow"))

dat <- wb_data(wb, dims = "A1:D4", col_names = FALSE)
# 1:1 copy to M2
wb$
  clone_worksheet(old = 1, new = "Clone1")$
  copy_cells(data = dat, dims = "M2")
```

wb_data

Add the wb_data attribute to a data frame in a worksheet

Description

provide `wb_data` object as `mschart` input

Usage

```
wb_data(wb, sheet = current_sheet(), dims, ...)
```

```
## S3 method for class 'wb_data'
```

```
x[
i,
j,
```

```

    drop = ifelse((missing(j) && length(i) > 1) || (!missing(i) && length(j) > 1), FALSE,
                  TRUE)
  ]

```

Arguments

wb	a workbook
sheet	a sheet in the workbook either name or index
dims	the dimensions
...	additional arguments for <code>wb_to_df()</code> . Be aware that not every argument is valid.
x	x
i	i
j	j
drop	drop

Value

A data frame of class `wb_data`.

See Also

[wb_to_df\(\)](#) [wb_add_mschart\(\)](#), [wb_add_pivot_table\(\)](#)

Examples

```

wb <- wb_workbook() %>%
  wb_add_worksheet() %>%
  wb_add_data(x = mtcars, dims = "B2")

wb_data(wb, 1, dims = "B2:E6")

```

wb_dims

Helper to specify the dims argument

Description

`wb_dims()` can be used to help provide the `dims` argument, in the `wb_add_*` functions. It returns a A1 spreadsheet range ("A1:B1" or "A2"). It can be very useful as you can specify many parameters that interact together. In general, you must provide named arguments. `wb_dims()` will only accept unnamed arguments if they are rows, cols, for example `wb_dims(1:4, 1:2)`, that will return "A1:B4".

`wb_dims()` can also be used with an object (a data frame or a matrix for example.) All parameters are numeric unless stated otherwise.

Usage

```
wb_dims(..., select = NULL)
```

Arguments

`...` construct dims arguments, from rows/cols vectors or objects that can be coerced to data frame. `x`, `rows`, `cols`, `from_row`, `from_col`, `from_dims` `row_names`, and `col_names` are accepted.

`select` A string, one of the followings. it improves the selection of various parts of `x` One of "x", "data", "col_names", or "row_names". "data" will only select the data part, excluding row names and column names (default if cols or rows are specified) "x" Includes the data, column and row names if they are present. (default if none of rows and cols are provided) "col_names" will only return column names "row_names" Will only return row names.

Details

When using `wb_dims()` with an object, the default behavior is to select only the data / row or columns in `x` If you need another behavior, use `wb_dims()` without supplying `x`.

- `x` An object (typically a matrix or a data.frame, but a vector is also accepted.)
- `from_row` / `from_col` / `from_dims` the starting position of `x` (The dims returned will assume that the top left corner of `x` is at `from_row` / `from_col`)
- `rows` Optional Which row span in `x` should this apply to. If `rows = 0`, only column names will be affected.
- `cols` a range of columns id in `x`, or one of the column names of `x` (length 1 only accepted for column names of `x`.)
- `row_names` A logical, this is to let `wb_dims()` know that `x` has row names or not. If `row_names = TRUE`, `wb_dims()` will increment `from_col` by 1.
- `col_names` `wb_dims()` assumes that if `x` has column names, then trying to find the dims.

`wb_dims()` tries to support most possible cases with `row_names = TRUE` and `col_names = FALSE`, but it works best if `x` has named dimensions (`data.frame`, `matrix`), and those parameters are not specified. data with column names, and without row names. as the code is more clean.

In the `add_data()` / `add_font()` example, if writing the data with row names

Value

A dims string

Using `wb_dims()` without an `x` object

- `rows` / `cols` (if you want to specify a single one, use `from_row` / `from_col`)
- `from_row` / `from_col` the starting position of the dims (similar to `start_row` / `start_col`, but with a clearer name.)

Using wb_dims() with an x object

wb_dims() with an object has 8 use-cases (they work with any position values of from_row / from_col), from_col/from_row correspond to the coordinates at the top left of x including column and row names if present.

These use cases are provided without from_row / from_col, but they work also with from_row / from_col.

1. provide the full grid with wb_dims(x = mtcars)
2. provide the data grid wb_dims(x = mtcars, select = "data")
3. provide the dims of column names wb_dims(x = mtcars, select = "col_names")
4. provide the dims of row names wb_dims(x = mtcars, row_names = TRUE, select = "row_names")
5. provide the dims of a row span wb_dims(x = mtcars, rows = 1:10) selects the first 10 data rows of mtcars (ignoring column names)
6. provide the dims of the data in a column span wb_dims(x = mtcars, cols = 1:5) select the data first 5 columns of mtcars
7. provide a column span (including column names) wb_dims(x = mtcars, cols = 4:7, select = "x") select the data columns 4, 5, 6, 7 of mtcars + column names
8. provide the position of a single column by name wb_dims(x = mtcars, cols = "mpg").
9. provide a row span with a column. wb_dims(x = mtcars, cols = "mpg", rows = 5:22)

To reuse, a good trick is to create a wrapper function, so that styling can be performed seamlessly.

```
wb_dims_cars <- function(...) {
  wb_dims(x = mtcars, from_row = 2, from_col = "B", ...)
}
# using this function
wb_dims_cars()           # full grid (data + column names)
wb_dims_cars(select = "data") # data only
wb_dims_cars(select = "col_names") # select column names
wb_dims_cars(cols = "vs")      # select the `vs` column
```

It can be very useful to apply many rounds of styling sequentially.

Examples

```
# Provide coordinates
wb_dims(1, 4)
wb_dims(rows = 1, cols = 4)
wb_dims(from_row = 4)
wb_dims(from_col = 2)
wb_dims(from_col = "B")
wb_dims(1:4, 6:9, from_row = 5)
# Provide vectors
wb_dims(1:10, c("A", "B", "C"))
wb_dims(rows = 1:10, cols = 1:10)
# provide `from_col` / `from_row`
wb_dims(rows = 1:10, cols = c("A", "B", "C"), from_row = 2)
```

```

wb_dims(rows = 1:10, cols = 1:10, from_col = 2)
wb_dims(rows = 1:10, cols = 1:10, from_dims = "B1")
# or objects
wb_dims(x = mtcars, col_names = TRUE)

# select all data
wb_dims(x = mtcars, select = "data")

# column names of an object (with the special select = "col_names")
wb_dims(x = mtcars, select = "col_names")

# dims of the column names of an object
wb_dims(x = mtcars, select = "col_names", col_names = TRUE)

## add formatting to `mtcars` using `wb_dims()`----
wb <- wb_workbook()
wb$add_worksheet("test wb_dims() with an object")
dims_mtcars_and_col_names <- wb_dims(x = mtcars)
wb$add_data(x = mtcars, dims = dims_mtcars_and_col_names)

# Put the font as Arial for the data
dims_mtcars_data <- wb_dims(x = mtcars, select = "data")
wb$add_font(dims = dims_mtcars_data, name = "Arial")

# Style col names as bold using the special `select = "col_names"` with `x` provided.
dims_column_names <- wb_dims(x = mtcars, select = "col_names")
wb$add_font(dims = dims_column_names, bold = TRUE, size = 13)

# Finally, to add styling to column "cyl" (the 4th column) (only the data)
# there are many options, but here is the preferred one
# if you know the column index, wb_dims(x = mtcars, cols = 4) also works.
dims_cyl <- wb_dims(x = mtcars, cols = "cyl")
wb$add_fill(dims = dims_cyl, color = wb_color("pink"))

# Mark a full column as important(with the column name too)
wb_dims_vs <- wb_dims(x = mtcars, cols = "vs", select = "x")
wb$add_fill(dims = wb_dims_vs, fill = wb_color("yellow"))
wb$add_conditional_formatting(dims = wb_dims(x = mtcars, cols = "mpg"), type = "dataBar")
# wb_open(wb)

```

wb_freeze_pane

Freeze pane of a worksheet

Description

Add a Freeze pane in a worksheet.

Usage

```
wb_freeze_pane(
  wb,
  sheet = current_sheet(),
  first_active_row = NULL,
  first_active_col = NULL,
  first_row = FALSE,
  first_col = FALSE,
  ...
)
```

Arguments

wb	A workbook object
sheet	A name or index of a worksheet
first_active_row	Top row of active region
first_active_col	Furthest left column of active region
first_row	If TRUE, freezes the first row (equivalent to first_active_row = 2)
first_col	If TRUE, freezes the first column (equivalent to first_active_col = 2)
...	additional arguments

See Also

Other workbook wrappers: [base_font-wb](#), [col_widths-wb](#), [creators-wb](#), [grouping-wb](#), [row_heights-wb](#), [wb_add_chartsheet\(\)](#), [wb_add_data\(\)](#), [wb_add_data_table\(\)](#), [wb_add_formula\(\)](#), [wb_add_pivot_table\(\)](#), [wb_add_slicer\(\)](#), [wb_add_worksheet\(\)](#), [wb_base_colors](#), [wb_clone_worksheet\(\)](#), [wb_copy_cells\(\)](#), [wb_merge_cells\(\)](#), [wb_save\(\)](#), [wb_set_last_modified_by\(\)](#), [wb_workbook\(\)](#)

Other worksheet content functions: [col_widths-wb](#), [filter-wb](#), [grouping-wb](#), [named_region-wb](#), [row_heights-wb](#), [wb_add_conditional_formatting\(\)](#), [wb_add_data\(\)](#), [wb_add_data_table\(\)](#), [wb_add_formula\(\)](#), [wb_add_pivot_table\(\)](#), [wb_add_slicer\(\)](#), [wb_add_thread\(\)](#), [wb_merge_cells\(\)](#)

Examples

```
## Create a new workbook
wb <- wb_workbook("Kenshin")

## Add some worksheets
wb$add_worksheet("Sheet 1")
wb$add_worksheet("Sheet 2")
wb$add_worksheet("Sheet 3")
wb$add_worksheet("Sheet 4")

## Freeze Panes
wb$freeze_pane("Sheet 1", first_active_row = 5, first_active_col = 3)
wb$freeze_pane("Sheet 2", first_col = TRUE) ## shortcut to first_active_col = 2
wb$freeze_pane(3, first_row = TRUE) ## shortcut to first_active_row = 2
wb$freeze_pane(4, first_active_row = 1, first_active_col = "D")
```

wb_get_tables	<i>List Excel tables in a worksheet</i>
---------------	---

Description

List Excel tables in a worksheet

Usage

```
wb_get_tables(wb, sheet = current_sheet())
```

Arguments

wb	A workbook object
sheet	A name or index of a worksheet

Value

A character vector of table names on the specified sheet

Examples

```
wb <- wb_workbook()
wb$add_worksheet(sheet = "Sheet 1")
wb$add_data_table(x = iris)
wb$add_data_table(x = mtcars, table_name = "mtcars", start_col = 10)

wb$get_tables(sheet = "Sheet 1")
```

wb_load	<i>Load an existing .xlsx, .xlsm or .xlsb file</i>
---------	--

Description

wb_load() returns a [wbWorkbook](#) object conserving the content of the original input file, including data, styles, media. This workbook can be modified, read from, and be written back into a xlsx file.

Usage

```
wb_load(file, sheet, data_only = FALSE, ...)
```

Arguments

file	A path to an existing .xlsx, .xlsm or .xlsb file
sheet	optional sheet parameter. if this is applied, only the selected sheet will be loaded. This can be a numeric, a string or NULL.
data_only	mode to import if only a data frame should be returned. This strips the wbWorkbook to a bare minimum.
...	additional arguments

Details

If a specific sheet is selected, the workbook will still contain sheets for all worksheets. The argument `sheet` and `data_only` are used internally by `wb_to_df()` to read from a file with minimal changes. They are not specifically designed to create rudimentary but otherwise fully functional workbooks. It is possible to import with `wb_load(data_only = TRUE, sheet = NULL)`. In this way, only a workbook framework is loaded without worksheets or data. This can be useful if only some workbook properties are of interest.

There are some internal arguments that can be passed to `wb_load`, which are used for development. The `debug` argument allows debugging of `xlsb` files in particular. With `calc_chain` it is possible to maintain the calculation chain. The calculation chain is used by spreadsheet software to determine the order in which formulas are evaluated. Removing the calculation chain has no known effect. The calculation chain is created the next time the worksheet is loaded into the spreadsheet. Keeping the calculation chain could only shorten the loading time in said software. Unfortunately, if a cell is added to the worksheet, the calculation chain may block the worksheet as the formulas will not be evaluated again until each individual cell with a formula is selected in the spreadsheet software and the Enter key is pressed manually. It is therefore strongly recommended not to activate this function.

In rare cases, a warning is issued when loading an `xlsx` file that an `xml` namespace has been removed from `xml` files. This refers to the internal structure of the loaded `xlsx` file. Certain `xlsx` files created by third-party applications contain a namespace (usually `x`). This namespace is not required for the file to work in spreadsheet software and is not expected by `openxlsx2`. It is therefore removed when the file is loaded into a workbook. Removal is generally considered safe, but the feature is still not commonly observed, hence the warning.

Initial support for binary `openxml` files (`xlsb`) has been added to the package. We parse the binary file format into pseudo-`openxml` files that we can import. Therefore, once imported, it is possible to interact with the file as if it had been provided in `xlsx` file format in the first place. This parsing into pseudo `xml` files is of course slower than reading directly from the binary file. Our implementation is also still missing some functions: some array formulas are not yet correct, conditional formatting and data validation are not implemented, nor are pivot tables and slicers.

Value

A Workbook object.

Examples

```
## load existing workbook
f1 <- system.file("extdata", "openxlsx2_example.xlsx", package = "openxlsx2")
```

```
wb <- wb_load(file = fl)
```

wb_merge_cells	<i>Merge cells within a worksheet</i>
----------------	---------------------------------------

Description

Worksheet cell merging

Usage

```
wb_merge_cells(wb, sheet = current_sheet(), dims = NULL, solve = FALSE, ...)
```

```
wb_unmerge_cells(wb, sheet = current_sheet(), dims = NULL, ...)
```

Arguments

wb	A Workbook object
sheet	A name or index of a worksheet
dims	worksheet cells
solve	logical if intersecting merges should be solved
...	additional arguments

Details

If using the deprecated arguments rows and cols with a merged region must be rectangular, only min and max of cols and rows are used.

See Also

Other workbook wrappers: [base_font-wb](#), [col_widths-wb](#), [creators-wb](#), [grouping-wb](#), [row_heights-wb](#), [wb_add_chartsheet\(\)](#), [wb_add_data\(\)](#), [wb_add_data_table\(\)](#), [wb_add_formula\(\)](#), [wb_add_pivot_table\(\)](#), [wb_add slicer\(\)](#), [wb_add_worksheet\(\)](#), [wb_base_colors](#), [wb_clone_worksheet\(\)](#), [wb_copy_cells\(\)](#), [wb_freeze_pane\(\)](#), [wb_save\(\)](#), [wb_set_last_modified_by\(\)](#), [wb_workbook\(\)](#)

Other worksheet content functions: [col_widths-wb](#), [filter-wb](#), [grouping-wb](#), [named_region-wb](#), [row_heights-wb](#), [wb_add_conditional_formatting\(\)](#), [wb_add_data\(\)](#), [wb_add_data_table\(\)](#), [wb_add_formula\(\)](#), [wb_add_pivot_table\(\)](#), [wb_add slicer\(\)](#), [wb_add_thread\(\)](#), [wb_freeze_pane\(\)](#)

Examples

```
# Create a new workbook
wb <- wb_workbook()$add_worksheet()

# Merge cells: Row 2 column C to F (3:6)
wb <- wb_merge_cells(wb, dims = "C3:F6")

# Merge cells: Rows 10 to 20 columns A to J (1:10)
```

```

wb <- wb_merge_cells(wb, dims = wb_dims(rows = 10:20, cols = 1:10))

wb$add_worksheet()

## Intersecting merges
wb <- wb_merge_cells(wb, dims = wb_dims(cols = 1:10, rows = 1))
wb <- wb_merge_cells(wb, dims = wb_dims(cols = 5:10, rows = 2))
wb <- wb_merge_cells(wb, dims = wb_dims(cols = 1:10, rows = 12))
try(wb_merge_cells(wb, dims = "A1:A10"))

## remove merged cells
# removes any intersecting merges
wb <- wb_unmerge_cells(wb, dims = wb_dims(cols = 1, rows = 1))
wb <- wb_merge_cells(wb, dims = "A1:A10")

# or let us decide how to solve this
wb <- wb_merge_cells(wb, dims = "A1:A10", solve = TRUE)

```

wb_open

Preview a workbook in a spreadsheet software

Description

You can also use the shorter `wb$open()` as a replacement. To open `xlsx` files, see [xl_open\(\)](#).

Usage

```
wb_open(wb)
```

Arguments

`wb` a `wbWorkbook` object

wb_order

Order worksheets in a workbook

Description

Get/set order of worksheets in a Workbook object

Usage

```
wb_get_order(wb)
```

```
wb_set_order(wb, sheets)
```


Arguments

wb	A wbWorkbook object
sheets	Sheet order

Details

This function does not reorder the worksheets within the workbook object, it simply shuffles the order when writing to file.

Examples

```
## setup a workbook with 3 worksheets
wb <- wb_workbook()
wb$add_worksheet("Sheet 1", grid_lines = FALSE)
wb$add_data_table(x = iris)

wb$add_worksheet("mtcars (Sheet 2)", grid_lines = FALSE)
wb$add_data(x = mtcars)

wb$add_worksheet("Sheet 3", grid_lines = FALSE)
wb$add_data(x = Formaldehyde)

wb_get_order(wb)
wb$get_sheet_na
wb$set_order(c(1, 3, 2)) # switch position of sheets 2 & 3
wb$add_data(2, 'This is still the "mtcars" worksheet', start_col = 15)
wb_get_order(wb)
wb$get_sheet_names() ## ordering within workbook is not changed
wb$set_order(3:1)
```

wb_page_setup

Set page margins, orientation and print scaling of a worksheet

Description

Set page margins, orientation and print scaling.

Usage

```
wb_page_setup(
  wb,
  sheet = current_sheet(),
  orientation = NULL,
  scale = 100,
  left = 0.7,
  right = 0.7,
  top = 0.75,
  bottom = 0.75,
```

```

header = 0.3,
footer = 0.3,
fit_to_width = FALSE,
fit_to_height = FALSE,
paper_size = NULL,
print_title_rows = NULL,
print_title_cols = NULL,
summary_row = NULL,
summary_col = NULL,
...
)

```

Arguments

wb	A workbook object
sheet	A name or index of a worksheet
orientation	Page orientation. One of "portrait" or "landscape"
scale	Print scaling. Numeric value between 10 and 400
left, right, top, bottom	Page margin in inches
header, footer	Margin in inches
fit_to_width, fit_to_height	An integer that tells the spreadsheet software on how many pages the scaling should fit. This does not actually scale the sheet.
paper_size	See details. Default value is 9 (A4 paper).
print_title_rows, print_title_cols	Rows / columns to repeat at top of page when printing. Integer vector.
summary_row	Location of summary rows in groupings. One of "Above" or "Below".
summary_col	Location of summary columns in groupings. One of "Right" or "Left".
...	additional arguments

Details

When adding fitting to width and height manual adjustment of the scaling factor is required. Setting `fit_to_width` and `fit_to_height` only tells spreadsheet software that the scaling was applied, but not which scaling was applied.

`paper_size` is an integer corresponding to:

size	"paper type"
1	Letter paper (8.5 in. by 11 in.)
2	Letter small paper (8.5 in. by 11 in.)
3	Tabloid paper (11 in. by 17 in.)
4	Ledger paper (17 in. by 11 in.)
5	Legal paper (8.5 in. by 14 in.)
6	Statement paper (5.5 in. by 8.5 in.)
7	Executive paper (7.25 in. by 10.5 in.)

- 8 A3 paper (297 mm by 420 mm)
- 9 A4 paper (210 mm by 297 mm)
- 10 A4 small paper (210 mm by 297 mm)
- 11 A5 paper (148 mm by 210 mm)
- 12 B4 paper (250 mm by 353 mm)
- 13 B5 paper (176 mm by 250 mm)
- 14 Folio paper (8.5 in. by 13 in.)
- 15 Quarto paper (215 mm by 275 mm)
- 16 Standard paper (10 in. by 14 in.)
- 17 Standard paper (11 in. by 17 in.)
- 18 Note paper (8.5 in. by 11 in.)
- 19 #9 envelope (3.875 in. by 8.875 in.)
- 20 #10 envelope (4.125 in. by 9.5 in.)
- 21 #11 envelope (4.5 in. by 10.375 in.)
- 22 #12 envelope (4.75 in. by 11 in.)
- 23 #14 envelope (5 in. by 11.5 in.)
- 24 C paper (17 in. by 22 in.)
- 25 D paper (22 in. by 34 in.)
- 26 E paper (34 in. by 44 in.)
- 27 DL envelope (110 mm by 220 mm)
- 28 C5 envelope (162 mm by 229 mm)
- 29 C3 envelope (324 mm by 458 mm)
- 30 C4 envelope (229 mm by 324 mm)
- 31 C6 envelope (114 mm by 162 mm)
- 32 C65 envelope (114 mm by 229 mm)
- 33 B4 envelope (250 mm by 353 mm)
- 34 B5 envelope (176 mm by 250 mm)
- 35 B6 envelope (176 mm by 125 mm)
- 36 Italy envelope (110 mm by 230 mm)
- 37 Monarch envelope (3.875 in. by 7.5 in.)
- 38 6 3/4 envelope (3.625 in. by 6.5 in.)
- 39 US standard fanfold (14.875 in. by 11 in.)
- 40 German standard fanfold (8.5 in. by 12 in.)
- 41 German legal fanfold (8.5 in. by 13 in.)
- 42 ISO B4 (250 mm by 353 mm)
- 43 Japanese double postcard (200 mm by 148 mm)
- 44 Standard paper (9 in. by 11 in.)
- 45 Standard paper (10 in. by 11 in.)
- 46 Standard paper (15 in. by 11 in.)
- 47 Invite envelope (220 mm by 220 mm)
- 50 Letter extra paper (9.275 in. by 12 in.)
- 51 Legal extra paper (9.275 in. by 15 in.)
- 52 Tabloid extra paper (11.69 in. by 18 in.)
- 53 A4 extra paper (236 mm by 322 mm)
- 54 Letter transverse paper (8.275 in. by 11 in.)
- 55 A4 transverse paper (210 mm by 297 mm)
- 56 Letter extra transverse paper (9.275 in. by 12 in.)
- 57 SuperA/SuperA/A4 paper (227 mm by 356 mm)

- 58 SuperB/SuperB/A3 paper (305 mm by 487 mm)
- 59 Letter plus paper (8.5 in. by 12.69 in.)
- 60 A4 plus paper (210 mm by 330 mm)
- 61 A5 transverse paper (148 mm by 210 mm)
- 62 JIS B5 transverse paper (182 mm by 257 mm)
- 63 A3 extra paper (322 mm by 445 mm)
- 64 A5 extra paper (174 mm by 235 mm)
- 65 ISO B5 extra paper (201 mm by 276 mm)
- 66 A2 paper (420 mm by 594 mm)
- 67 A3 transverse paper (297 mm by 420 mm)
- 68 A3 extra transverse paper (322 mm by 445 mm)
- 69 Japanese Double Postcard (200 mm x 148 mm) 70=A6(105mm x 148mm)
- 71 Japanese Envelope Kaku #2
- 72 Japanese Envelope Kaku #3
- 73 Japanese Envelope Chou #3
- 74 Japanese Envelope Chou #4
- 75 Letter Rotated (11in x 8 1/2 11 in)
- 76 A3 Rotated (420 mm x 297 mm)
- 77 A4 Rotated (297 mm x 210 mm)
- 78 A5 Rotated (210 mm x 148 mm)
- 79 B4 (JIS) Rotated (364 mm x 257 mm)
- 80 B5 (JIS) Rotated (257 mm x 182 mm)
- 81 Japanese Postcard Rotated (148 mm x 100 mm)
- 82 Double Japanese Postcard Rotated (148 mm x 200 mm) 83 = A6 Rotated (148 mm x 105 mm)
- 84 Japanese Envelope Kaku #2 Rotated
- 85 Japanese Envelope Kaku #3 Rotated
- 86 Japanese Envelope Chou #3 Rotated
- 87 Japanese Envelope Chou #4 Rotated 88=B6(JIS)(128mm x 182mm)
- 89 B6 (JIS) Rotated (182 mm x 128 mm)
- 90 (12 in x 11 in)
- 91 Japanese Envelope You #4
- 92 Japanese Envelope You #4 Rotated 93=PRC16K(146mm x 215mm) 94=PRC32K(97mm x 151mm)
- 95 PRC 32K(Big) (97 mm x 151 mm)
- 96 PRC Envelope #1 (102 mm x 165 mm)
- 97 PRC Envelope #2 (102 mm x 176 mm)
- 98 PRC Envelope #3 (125 mm x 176 mm)
- 99 PRC Envelope #4 (110 mm x 208 mm)
- 100 PRC Envelope #5 (110 mm x 220 mm)
- 101 PRC Envelope #6 (120 mm x 230 mm)
- 102 PRC Envelope #7 (160 mm x 230 mm)
- 103 PRC Envelope #8 (120 mm x 309 mm)
- 104 PRC Envelope #9 (229 mm x 324 mm)
- 105 PRC Envelope #10 (324 mm x 458 mm)
- 106 PRC 16K Rotated
- 107 PRC 32K Rotated
- 108 PRC 32K(Big) Rotated
- 109 PRC Envelope #1 Rotated (165 mm x 102 mm)
- 110 PRC Envelope #2 Rotated (176 mm x 102 mm)

- 111 PRC Envelope #3 Rotated (176 mm x 125 mm)
- 112 PRC Envelope #4 Rotated (208 mm x 110 mm)
- 113 PRC Envelope #5 Rotated (220 mm x 110 mm)
- 114 PRC Envelope #6 Rotated (230 mm x 120 mm)
- 115 PRC Envelope #7 Rotated (230 mm x 160 mm)
- 116 PRC Envelope #8 Rotated (309 mm x 120 mm)
- 117 PRC Envelope #9 Rotated (324 mm x 229 mm)
- 118 PRC Envelope #10 Rotated (458 mm x 324 mm)

Examples

```

wb <- wb_workbook()
wb$add_worksheet("S1")
wb$add_worksheet("S2")
wb$add_data_table(1, x = iris[1:30, ])
wb$add_data_table(2, x = iris[1:30, ], dims = c("C5"))

## landscape page scaled to 50%
wb$page_setup(sheet = 1, orientation = "landscape", scale = 50)

## portrait page scales to 300% with 0.5in left and right margins
wb$page_setup(sheet = 2, orientation = "portrait", scale = 300, left = 0.5, right = 0.5)

## print titles
wb$add_worksheet("print_title_rows")
wb$add_worksheet("print_title_cols")

wb$add_data("print_title_rows", rbind(iris, iris, iris, iris))
wb$add_data("print_title_cols", x = rbind(mtcars, mtcars, mtcars), row_names = TRUE)

wb$page_setup(sheet = "print_title_rows", print_title_rows = 1) ## first row
wb$page_setup(sheet = "print_title_cols", print_title_cols = 1, print_title_rows = 1)

```

wb_protect

Protect a workbook from modifications

Description

Protect or unprotect a workbook from modifications by the user in the graphical user interface. Replaces an existing protection.

Usage

```

wb_protect(
  wb,
  protect = TRUE,
  password = NULL,

```

```

lock_structure = FALSE,
lock_windows = FALSE,
type = 1,
file_sharing = FALSE,
username = unname(Sys.info()["user"]),
read_only_recommended = FALSE,
...
)

```

Arguments

wb	A Workbook object
protect	Whether to protect or unprotect the sheet (default TRUE)
password	(optional) password required to unprotect the workbook
lock_structure	Whether the workbook structure should be locked
lock_windows	Whether the window position of the spreadsheet should be locked
type	Lock type (see Details)
file_sharing	Whether to enable a popup requesting the unlock password is prompted
username	The username for the file_sharing popup
read_only_recommended	Whether or not a post unlock message appears stating that the workbook is recommended to be opened in read-only mode.
...	additional arguments

Details

Lock types:

- 1 xlsx with password (default)
- 2 xlsx recommends read-only
- 4 xlsx enforces read-only
- 8 xlsx is locked for annotation

Examples

```

wb <- wb_workbook()
wb$add_worksheet("S1")
wb_protect(wb, protect = TRUE, password = "Password", lock_structure = TRUE)

# Remove the protection
wb_protect(wb, protect = FALSE)

wb <- wb_protect(
  wb,
  protect = TRUE,
  password = "Password",
  lock_structure = TRUE,

```

```

    type = 2L,
    file_sharing = TRUE,
    username = "Test",
    read_only_recommended = TRUE
  )

```

wb_protect_worksheet *Protect a worksheet from modifications*

Description

Protect or unprotect a worksheet from modifications by the user in the graphical user interface. Replaces an existing protection. Certain features require applying unlocking of initialized cells in the worksheet and across columns and/or rows.

Usage

```

wb_protect_worksheet(
  wb,
  sheet = current_sheet(),
  protect = TRUE,
  password = NULL,
  properties = NULL
)

```

Arguments

wb	A workbook object
sheet	A name or index of a worksheet
protect	Whether to protect or unprotect the sheet (default=TRUE)
password	(optional) password required to unprotect the worksheet
properties	A character vector of properties to lock. Can be one or more of the following: "selectLockedCells", "selectUnlockedCells", "formatCells", "formatColumns", "formatRows", "insertColumns", "insertRows", "insertHyperlinks", "deleteColumns", "deleteRows", "sort", "autoFilter", "pivotTables", "objects", "scenarios"

Examples

```

wb <- wb_workbook()
wb$add_worksheet("S1")
wb$add_data_table(1, x = iris[1:30, ])

wb$protect_worksheet(
  "S1",
  protect = TRUE,
  properties = c("formatCells", "formatColumns", "insertColumns", "deleteColumns")
)

```

```

)

# Formatting cells / columns is allowed , but inserting / deleting columns is protected:
wb$protect_worksheet(
  "S1",
  protect = TRUE,
  c(formatCells = FALSE, formatColumns = FALSE,
     insertColumns = TRUE, deleteColumns = TRUE)
)

# Remove the protection
wb$protect_worksheet("S1", protect = FALSE)

```

wb_remove_tables	<i>Remove a data table from a worksheet</i>
------------------	---

Description

Remove Excel tables in a workbook using its name.

Usage

```
wb_remove_tables(wb, sheet = current_sheet(), table, remove_data = TRUE)
```

Arguments

wb	A Workbook object
sheet	A name or index of a worksheet
table	Name of table to remove. Use wb_get_tables() to view the tables present in the worksheet.
remove_data	Default TRUE. If FALSE, will only remove the data table attributes but will keep the data in the worksheet.

Value

The wbWorkbook, invisibly

Examples

```

wb <- wb_workbook()
wb$add_worksheet(sheet = "Sheet 1")
wb$add_worksheet(sheet = "Sheet 2")
wb$add_data_table(sheet = "Sheet 1", x = iris, table_name = "iris")
wb$add_data_table(sheet = 1, x = mtcars, table_name = "mtcars", start_col = 10)

## delete worksheet removes table objects
wb <- wb_remove_worksheet(wb, sheet = 1)

```



```
wb$add_data_table(sheet = 1, x = iris, table_name = "iris")
wb$add_data_table(sheet = 1, x = mtcars, table_name = "mtcars", start_col = 10)

## wb_remove_tables() deletes table object and all data
wb_get_tables(wb, sheet = 1)
wb$remove_tables(sheet = 1, table = "iris")
wb$add_data_table(sheet = 1, x = iris, table_name = "iris")

wb_get_tables(wb, sheet = 1)
wb$remove_tables(sheet = 1, table = "iris")
```

wb_remove_worksheet *Remove a worksheet from a workbook*

Description

Remove a worksheet from a workbook

Usage

```
wb_remove_worksheet(wb, sheet = current_sheet())
```

Arguments

wb	A wbWorkbook object
sheet	The sheet name or index to remove

Value

The wbWorkbook object, invisibly.

Examples

```
## load a workbook
wb <- wb_load(file = system.file("extdata", "openxlsx2_example.xlsx", package = "openxlsx2"))

## Remove sheet 2
wb <- wb_remove_worksheet(wb, 2)
```

wb_save	<i>Save a workbook to file</i>
---------	--------------------------------

Description

Save a workbook to file

Usage

```
wb_save(wb, file = NULL, overwrite = TRUE, path = NULL)
```

Arguments

wb	A wbWorkbook object to write to file
file	A path to save the workbook to
overwrite	If FALSE, will not overwrite when file already exists.
path	Deprecated argument. Please use file in new code.

Value

the wbWorkbook object, invisibly

See Also

Other workbook wrappers: [base_font-wb](#), [col_widths-wb](#), [creators-wb](#), [grouping-wb](#), [row_heights-wb](#), [wb_add_chartsheet\(\)](#), [wb_add_data\(\)](#), [wb_add_data_table\(\)](#), [wb_add_formula\(\)](#), [wb_add_pivot_table\(\)](#), [wb_add_slicer\(\)](#), [wb_add_worksheet\(\)](#), [wb_base_colors](#), [wb_clone_worksheet\(\)](#), [wb_copy_cells\(\)](#), [wb_freeze_pane\(\)](#), [wb_merge_cells\(\)](#), [wb_set_last_modified_by\(\)](#), [wb_workbook\(\)](#)

Examples

```
## Create a new workbook and add a worksheet
wb <- wb_workbook("Creator of workbook")
wb$add_worksheet(sheet = "My first worksheet")

## Save workbook to working directory

wb_save(wb, file = temp_xlsx(), overwrite = TRUE)
```

wb_set_bookview	<i>Set the workbook position, size and filter</i>
-----------------	---

Description

Set the workbook position, size and filter

Usage

```
wb_set_bookview(
    wb,
    active_tab = NULL,
    auto_filter_date_grouping = NULL,
    first_sheet = NULL,
    minimized = NULL,
    show_horizontal_scroll = NULL,
    show_sheet_tabs = NULL,
    show_vertical_scroll = NULL,
    tab_ratio = NULL,
    visibility = NULL,
    window_height = NULL,
    window_width = NULL,
    x_window = NULL,
    y_window = NULL,
    ...
)
```

Arguments

wb	A wbWorkbook object
active_tab	activeTab
auto_filter_date_grouping	autoFilterDateGrouping
first_sheet	The first sheet to be displayed
minimized	minimized
show_horizontal_scroll	showHorizontalScroll
show_sheet_tabs	showSheetTabs
show_vertical_scroll	showVerticalScroll
tab_ratio	tabRatio
visibility	visibility
window_height	windowHeight
window_width	windowWidth

x_window	xWindow
y_window	yWindow
...	additional arguments

Value

The Workbook object

wb_set_grid_lines	<i>Modify grid lines visibility in a worksheet</i>
-------------------	--

Description

Set worksheet grid lines to show or hide. You can also add / remove grid lines when creating a worksheet with [wb_add_worksheet\(grid_lines = FALSE\)](#)

Usage

```
wb_set_grid_lines(wb, sheet = current_sheet(), show = FALSE, print = show)
```

```
wb_grid_lines(wb, sheet = current_sheet(), show = FALSE, print = show)
```

Arguments

wb	A workbook object
sheet	A name or index of a worksheet
show	A logical. If FALSE, grid lines are hidden.
print	A logical. If FALSE, grid lines are not printed.

Examples

```
wb <- wb_workbook()$add_worksheet()$add_worksheet()
wb$get_sheet_names() ## list worksheets in workbook
wb$set_grid_lines(1, show = FALSE)
wb$set_grid_lines("Sheet 2", show = FALSE)
```

wb_set_header_footer *Set headers and footers of a worksheet*

Description

Set document headers and footers. You can also do this when adding a worksheet with [wb_add_worksheet\(\)](#) with the header, footer arguments and friends. These will show up when printing an xlsx file.

Usage

```
wb_set_header_footer(
  wb,
  sheet = current_sheet(),
  header = NULL,
  footer = NULL,
  even_header = NULL,
  even_footer = NULL,
  first_header = NULL,
  first_footer = NULL,
  ...
)
```

Arguments

wb	A Workbook object
sheet	A name or index of a worksheet
header, even_header, first_header, footer, even_footer, first_footer	Character vector of length 3 corresponding to positions left, center, right. header and footer are used to default additional arguments. Setting even, odd, or first, overrides header/footer. Use NA to skip a position.
...	additional arguments

Details

Headers and footers can contain special tags

- **&[Page]** Page number
- **&[Pages]** Number of pages
- **&[Date]** Current date
- **&[Time]** Current time
- **&[Path]** File path
- **&[File]** File name
- **&[Tab]** Worksheet name

Examples

```

wb <- wb_workbook()

# Add example data
wb$add_worksheet("S1")$add_data(x = 1:400)
wb$add_worksheet("S2")$add_data(x = 1:400)
wb$add_worksheet("S3")$add_data(x = 3:400)
wb$add_worksheet("S4")$add_data(x = 3:400)

wb$set_header_footer(
  sheet = "S1",
  header = c("ODD HEAD LEFT", "ODD HEAD CENTER", "ODD HEAD RIGHT"),
  footer = c("ODD FOOT RIGHT", "ODD FOOT CENTER", "ODD FOOT LEFT"),
  even_header = c("EVEN HEAD LEFT", "EVEN HEAD CENTER", "EVEN HEAD RIGHT"),
  even_footer = c("EVEN FOOT RIGHT", "EVEN FOOT CENTER", "EVEN FOOT LEFT"),
  first_header = c("TOP", "OF FIRST", "PAGE"),
  first_footer = c("BOTTOM", "OF FIRST", "PAGE")
)

wb$set_header_footer(
  sheet = 2,
  header = c("&[Date]", "ALL HEAD CENTER 2", "&[Page] / &[Pages]"),
  footer = c("&[Path]&[File]", NA, "&[Tab]"),
  first_header = c(NA, "Center Header of First Page", NA),
  first_footer = c(NA, "Center Footer of First Page", NA)
)

wb$set_header_footer(
  sheet = 3,
  header = c("ALL HEAD LEFT 2", "ALL HEAD CENTER 2", "ALL HEAD RIGHT 2"),
  footer = c("ALL FOOT RIGHT 2", "ALL FOOT CENTER 2", "ALL FOOT LEFT 2")
)

wb$set_header_footer(
  sheet = 4,
  first_header = c("FIRST ONLY L", NA, "FIRST ONLY R"),
  first_footer = c("FIRST ONLY L", NA, "FIRST ONLY R")
)

```

wb_set_last_modified_by

Modify author in the metadata of a workbook

Description

Just a wrapper of `wb$set_last_modified_by()`

Usage

```
wb_set_last_modified_by(wb, name, ...)
```

Arguments

wb	A workbook object
name	A string object with the name of the LastModifiedBy-User
...	additional arguments

See Also

Other workbook wrappers: [base_font-wb](#), [col_widths-wb](#), [creators-wb](#), [grouping-wb](#), [row_heights-wb](#), [wb_add_chartsheet\(\)](#), [wb_add_data\(\)](#), [wb_add_data_table\(\)](#), [wb_add_formula\(\)](#), [wb_add_pivot_table\(\)](#), [wb_add slicer\(\)](#), [wb_add_worksheet\(\)](#), [wb_base_colors](#), [wb_clone_worksheet\(\)](#), [wb_copy_cells\(\)](#), [wb_freeze_pane\(\)](#), [wb_merge_cells\(\)](#), [wb_save\(\)](#), [wb_workbook\(\)](#)

Examples

```
wb <- wb_workbook()
wb_set_last_modified_by(wb, "test")
```

wb_set_sheetview	<i>Modify the default view of a worksheet</i>
------------------	---

Description

This helps set a worksheet's appearance, such as the zoom, whether to show grid lines

Usage

```
wb_set_sheetview(
  wb,
  sheet = current_sheet(),
  color_id = NULL,
  default_grid_color = NULL,
  right_to_left = NULL,
  show_formulas = NULL,
  show_grid_lines = NULL,
  show_outline_symbols = NULL,
  show_row_col_headers = NULL,
  show_ruler = NULL,
  show_white_space = NULL,
  show_zeros = NULL,
  tab_selected = NULL,
  top_left_cell = NULL,
  view = NULL,
  window_protection = NULL,
  workbook_view_id = NULL,
  zoom_scale = NULL,
  zoom_scale_normal = NULL,
```

```

    zoom_scale_page_layout_view = NULL,
    zoom_scale_sheet_layout_view = NULL,
    ...
)

```

Arguments

wb	A Workbook object
sheet	sheet
color_id, default_grid_color	Integer: A color, default is 64
right_to_left	Logical: if TRUE column ordering is right to left
show_formulas	Logical: if TRUE cell formulas are shown
show_grid_lines	Logical: if TRUE the worksheet grid is shown
show_outline_symbols	Logical: if TRUE outline symbols are shown
show_row_col_headers	Logical: if TRUE row and column headers are shown
show_ruler	Logical: if TRUE a ruler is shown in page layout view
show_white_space	Logical: if TRUE margins are shown in page layout view
show_zeros	Logical: if FALSE cells containing zero are shown blank if show_formulas = FALSE
tab_selected	Integer: zero vector indicating the selected tab
top_left_cell	Cell: the cell shown in the top left corner / or top right with rightToLeft
view	View: "normal", "pageBreakPreview" or "pageLayout"
window_protection	Logical: if TRUE the panes are protected
workbook_view_id	integer: Pointing to some other view inside the workbook
zoom_scale, zoom_scale_normal, zoom_scale_page_layout_view, zoom_scale_sheet_layout_view	Integer: the zoom scale should be between 10 and 400. These are values for current, normal etc.
...	additional arguments

Value

The wbWorkbook object, invisibly

Examples

```
wb <- wb_workbook()$add_worksheet()

wb$set_sheetview(
  zoom_scale = 75,
  right_to_left = FALSE,
  show_formulas = TRUE,
  show_grid_lines = TRUE,
  show_outline_symbols = FALSE,
  show_row_col_headers = TRUE,
  show_ruler = TRUE,
  show_white_space = FALSE,
  tab_selected = 1,
  top_left_cell = "B1",
  view = "normal",
  window_protection = TRUE
)
```

wb_to_df

Create a data frame from a Workbook

Description

Simple function to create a data.frame from a sheet in workbook. Simple as in it was simply written down. read_xlsx() and wb_read() are just internal wrappers of wb_to_df() intended for people coming from other packages.

Usage

```
wb_to_df(
  file,
  sheet,
  start_row = 1,
  start_col = NULL,
  row_names = FALSE,
  col_names = TRUE,
  skip_empty_rows = FALSE,
  skip_empty_cols = FALSE,
  skip_hidden_rows = FALSE,
  skip_hidden_cols = FALSE,
  rows = NULL,
  cols = NULL,
  detect_dates = TRUE,
  na.strings = "#N/A",
  na.numbers = NA,
  fill_merged_cells = FALSE,
  dims,
  show_formula = FALSE,
```

```
    convert = TRUE,  
    types,  
    named_region,  
    keep_attributes = FALSE,  
    ...  
  )  
  
read_xlsx(  
  file,  
  sheet,  
  start_row = 1,  
  start_col = NULL,  
  row_names = FALSE,  
  col_names = TRUE,  
  skip_empty_rows = FALSE,  
  skip_empty_cols = FALSE,  
  rows = NULL,  
  cols = NULL,  
  detect_dates = TRUE,  
  named_region,  
  na.strings = "#N/A",  
  na.numbers = NA,  
  fill_merged_cells = FALSE,  
  ...  
)  
  
wb_read(  
  file,  
  sheet = 1,  
  start_row = 1,  
  start_col = NULL,  
  row_names = FALSE,  
  col_names = TRUE,  
  skip_empty_rows = FALSE,  
  skip_empty_cols = FALSE,  
  rows = NULL,  
  cols = NULL,  
  detect_dates = TRUE,  
  named_region,  
  na.strings = "NA",  
  na.numbers = NA,  
  ...  
)
```

Arguments

file	An xlsx file, wbWorkbook object or URL to xlsx file.
sheet	Either sheet name or index. When missing the first sheet in the workbook is

	selected.
start_row	first row to begin looking for data.
start_col	first column to begin looking for data.
row_names	If TRUE, the first col of data will be used as row names.
col_names	If TRUE, the first row of data will be used as column names.
skip_empty_rows	If TRUE, empty rows are skipped.
skip_empty_cols	If TRUE, empty columns are skipped.
skip_hidden_rows	If TRUE, hidden rows are skipped.
skip_hidden_cols	If TRUE, hidden columns are skipped.
rows	A numeric vector specifying which rows in the xlsx file to read. If NULL, all rows are read.
cols	A numeric vector specifying which columns in the xlsx file to read. If NULL, all columns are read.
detect_dates	If TRUE, attempt to recognize dates and perform conversion.
na.strings	A character vector of strings which are to be interpreted as NA. Blank cells will be returned as NA.
na.numbers	A numeric vector of digits which are to be interpreted as NA. Blank cells will be returned as NA.
fill_merged_cells	If TRUE, the value in a merged cell is given to all cells within the merge.
dims	Character string of type "A1:B2" as optional dimensions to be imported.
show_formula	If TRUE, the underlying Excel formulas are shown.
convert	If TRUE, a conversion to dates and numerics is attempted.
types	A named numeric indicating, the type of the data. Names must match the returned data. See Details for more.
named_region	Character string with a named_region (defined name or table). If no sheet is selected, the first appearance will be selected. See wb_get_named_regions()
keep_attributes	If TRUE additional attributes are returned. (These are used internally to define a cell type.)
...	additional arguments

Details

The returned data frame will have named rows matching the rows of the worksheet. With `col_names = FALSE` the returned data frame will have column names matching the columns of the worksheet. Otherwise the first row is selected as column name.

Depending if the R package `hms` is loaded, `wb_to_df()` returns `hms` variables or string variables in the `hh:mm:ss` format.

The `types` argument must be a named numeric.

- 0: character
- 1: numeric
- 2: date
- 3: posixt (datetime)
- 4: logical

`wb_to_df()` will not pick up formulas added to a workbook object via `wb_add_formula()`. This is because only the formula is written and left to be evaluated when the file is opened in a spreadsheet software. Opening, saving and closing the file in a spreadsheet software will resolve this.

See Also

[wb_get_named_regions\(\)](#)

Examples

```
#####
# numerics, dates, missings, bool and string
example_file <- system.file("extdata", "openxlsx2_example.xlsx", package = "openxlsx2")
wb1 <- wb_load(example_file)

# import workbook
wb_to_df(wb1)

# do not convert first row to column names
wb_to_df(wb1, col_names = FALSE)

# do not try to identify dates in the data
wb_to_df(wb1, detect_dates = FALSE)

# return the underlying Excel formula instead of their values
wb_to_df(wb1, show_formula = TRUE)

# read dimension without colNames
wb_to_df(wb1, dims = "A2:C5", col_names = FALSE)

# read selected cols
wb_to_df(wb1, cols = c("A:B", "G"))

# read selected rows
wb_to_df(wb1, rows = c(2, 4, 6))

# convert characters to numerics and date (logical too?)
wb_to_df(wb1, convert = FALSE)

# erase empty rows from dataset
wb_to_df(wb1, skip_empty_rows = TRUE)

# erase empty columns from dataset
wb_to_df(wb1, skip_empty_cols = TRUE)
```

```

# convert first row to rownames
wb_to_df(wb1, sheet = 2, dims = "C6:G9", row_names = TRUE)

# define type of the data.frame
wb_to_df(wb1, cols = c(2, 5), types = c("Var1" = 0, "Var3" = 1))

# start in row 5
wb_to_df(wb1, start_row = 5, col_names = FALSE)

# na string
wb_to_df(wb1, na.strings = "a")

#####
# Named regions
file_named_region <- system.file("extdata", "namedRegions3.xlsx", package = "openxlsx2")
wb2 <- wb_load(file_named_region)

# read dataset with named_region (returns global first)
wb_to_df(wb2, named_region = "MyRange", col_names = FALSE)

# read named_region from sheet
wb_to_df(wb2, named_region = "MyRange", sheet = 4, col_names = FALSE)

# read_xlsx() and wb_read()
example_file <- system.file("extdata", "openxlsx2_example.xlsx", package = "openxlsx2")
read_xlsx(file = example_file)
df1 <- wb_read(file = example_file, sheet = 1)
df2 <- wb_read(file = example_file, sheet = 1, rows = c(1, 3, 5), cols = 1:3)

```

wb_update_table

Update a data table position in a worksheet

Description

Update the position of a data table, possibly written using [wb_add_data_table\(\)](#)

Usage

```
wb_update_table(wb, sheet = current_sheet(), dims = "A1", tabname)
```

Arguments

wb	A workbook
sheet	A worksheet
dims	Cell range used for new data table.
tabname	A table name

Details

Be aware that this function does not alter any filter. Excluding or adding rows does not make rows appear nor will it hide them.

Examples

```
wb <- wb_workbook()$add_worksheet()$add_data_table(x = mtcars)
wb$update_table(tabname = "Table1", dims = "A1:J4")
```

 wb_workbook

Create a new Workbook object

Description

Initialize a [wbWorkbook](#) object. You can set workbook properties as well.

Usage

```
wb_workbook(
  creator = NULL,
  title = NULL,
  subject = NULL,
  category = NULL,
  datetime_created = Sys.time(),
  theme = NULL,
  keywords = NULL,
  comments = NULL,
  manager = NULL,
  company = NULL,
  ...
)
```

Arguments

creator	Creator of the workbook (your name). Defaults to login username or options("openxlsx2.creator") if set.
title, subject, category, keywords, comments, manager, company	Workbook property, a string.
datetime_created	The time of the workbook is created
theme	Optional theme identified by string or number. See Details for options.
...	additional arguments

Details

theme can be one of "Atlas", "Badge", "Berlin", "Celestial", "Crop", "Depth", "Droplet", "Facet", "Feathered", "Gallery", "Headlines", "Integral", "Ion", "Ion Boardroom", "LibreOffice", "Madison", "Main Event", "Mesh", "Office 2007 - 2010 Theme", "Office 2013 - 2022 Theme", "Office Theme", "Old Office Theme", "Organic", "Parallax", "Parcel", "Retrospect", "Savon", "Slice", "Vapor Trail", "View", "Wisp", "Wood Type"

Value

A wbWorkbook object

See Also

Other workbook wrappers: [base_font-wb](#), [col_widths-wb](#), [creators-wb](#), [grouping-wb](#), [row_heights-wb](#), [wb_add_chartsheet\(\)](#), [wb_add_data\(\)](#), [wb_add_data_table\(\)](#), [wb_add_formula\(\)](#), [wb_add_pivot_table\(\)](#), [wb_add slicer\(\)](#), [wb_add_worksheet\(\)](#), [wb_base_colors](#), [wb_clone_worksheet\(\)](#), [wb_copy_cells\(\)](#), [wb_freeze_pane\(\)](#), [wb_merge_cells\(\)](#), [wb_save\(\)](#), [wb_set_last_modified_by\(\)](#)

Examples

```
## Create a new workbook
wb <- wb_workbook()

## Set Workbook properties
wb <- wb_workbook(
  creator = "Me",
  title   = "Expense Report",
  subject = "Expense Report - 2022 Q1",
  category = "sales"
)
```

write_xlsx

Write data to an xlsx file

Description

Write a data frame or list of data frames to an xlsx file.

Usage

```
write_xlsx(x, file, as_table = FALSE, ...)
```

Arguments

x	An object or a list of objects that can be handled by wb_add_data() to write to file.
file	An optional xlsx file name. If no file is passed, the object is not written to disk and only a workbook object is returned.

as_table If TRUE, will write as a data table, instead of data.
... Arguments passed on to `wb_workbook`, `wb_add_worksheet`, `wb_add_data_table`, `wb_add_data`, `wb_freeze_pane`, `wb_set_col_widths`, `wb_save`
creator Creator of the workbook (your name). Defaults to login username or `options("openxlsx2.creator")` if set.
sheet A name for the new worksheet
grid_lines A logical. If FALSE, the worksheet grid lines will be hidden.
tab_color Color of the sheet tab. A `wb_color()`, a valid color (belonging to `grDevices::colors()`) or a valid hex color beginning with "#".
zoom The sheet zoom level, a numeric between 10 and 400 as a percentage. (A zoom value smaller than 10 will default to 10.)
total_row logical. With the default FALSE no total row is added.
start_col A vector specifying the starting column to write x to.
start_row A vector specifying the starting row to write x to.
col_names If TRUE, column names of x are written.
row_names If TRUE, the row names of x are written.
na.strings Value used for replacing NA values from x. Default looks if `options(openxlsx2.na.strings)` is set. Otherwise `na.strings()` uses the special #N/A value within the workbook.
first_active_row Top row of active region
first_active_col Furthest left column of active region
first_row If TRUE, freezes the first row (equivalent to `first_active_row = 2`)
first_col If TRUE, freezes the first column (equivalent to `first_active_col = 2`)
widths Width to set cols to specified column width or "auto" for automatic sizing. widths is recycled to the length of cols. openxlsx2 sets the default width is 8.43, as this is the standard in some spreadsheet software. See **Details** for general information on column widths.
overwrite If FALSE, will not overwrite when file already exists.

Details

columns of x with class Date or POSIXt are automatically styled as dates and datetimes respectively.

Value

A workbook object

Examples

```
## write to working directory
write_xlsx(iris, file = temp_xlsx(), col_names = TRUE)

write_xlsx(iris,
  file = temp_xlsx(),
```



```

    col_names = TRUE
  )

  ## Lists elements are written to individual worksheets, using list names as sheet names if available
  l <- list("IRIS" = iris, "MTCARS" = mtcars, matrix(runif(1000), ncol = 5))
  write_xlsx(l, temp_xlsx(), col_widths = c(NA, "auto", "auto"))

  ## different sheets can be given different parameters
  write_xlsx(l, temp_xlsx(),
    start_col = c(1, 2, 3), start_row = 2,
    as_table = c(TRUE, TRUE, FALSE), with_filter = c(TRUE, FALSE, FALSE)
  )

  # specify column widths for multiple sheets
  write_xlsx(l, temp_xlsx(), col_widths = 20)
  write_xlsx(l, temp_xlsx(), col_widths = list(100, 200, 300))
  write_xlsx(l, temp_xlsx(), col_widths = list(rep(10, 5), rep(8, 11), rep(5, 5)))

```

xl_open

*Open an xlsx file or a wbWorkbook object***Description**

This function tries to open a Microsoft Excel (xls/xlsx) file or, an [wbWorkbook](#) with the proper application, in a portable manner.

On Windows it uses `base::shell.exec()` (Windows only function) to determine the appropriate program.

On Mac, (c) it uses system default handlers, given the file type.

On Linux, it searches (via `which`) for available xls/xlsx reader applications (unless `options('openxlsx2.excelApp')` is set to the app bin path), and if it finds anything, sets `options('openxlsx2.excelApp')` to the program chosen by the user via a menu (if many are present, otherwise it will set the only available). Currently searched for apps are Libreoffice/Openoffice (`soffice bin`), Gnumeric (`gnumeric`) and Calligra Sheets (`calligrasheets`).

Usage

```

xl_open(x, interactive = NA)

## S3 method for class 'wbWorkbook'
xl_open(x, interactive = NA)

## Default S3 method:
xl_open(x, interactive = NA)

```

Arguments

`x` A path to the Excel (xls/xlsx) file or `wbWorkbook` object.

`interactive` If `FALSE` will throw a warning and not open the path. This can be manually set to `TRUE`, otherwise when `NA` (default) uses the value returned from `base::interactive()`

Examples

```

if (interactive()) {
  xlsx_file <- system.file("extdata", "openxlsx2_example.xlsx", package = "openxlsx2")
  xl_open(xlsx_file)

  # (not yet saved) Workbook example
  wb <- wb_workbook()
  x <- mtcars[1:6, ]
  wb$add_worksheet("Cars")
  wb$add_data("Cars", x, start_col = 2, start_row = 3, row_names = TRUE)
  xl_open(wb)
}

```

xml_add_child	<i>append xml child to node</i>
---------------	---------------------------------

Description

append xml child to node

Usage

```
xml_add_child(xml_node, xml_child, level, pointer = FALSE, ...)
```

Arguments

xml_node	xml_node
xml_child	xml_child
level	optional level, if missing the first child is picked
pointer	pointer
...	additional arguments passed to read_xml()

Examples

```

xml_node <- "<a><b/></a>"
xml_child <- "<c/>"

# add child to first level node
xml_add_child(xml_node, xml_child)

# add child to second level node as request
xml_node <- xml_add_child(xml_node, xml_child, level = c("b"))

# add child to third level node as request
xml_node <- xml_add_child(xml_node, "<d/>", level = c("b", "c"))

```

xml_attr_mod	<i>adds or updates attribute(s) in existing xml node</i>
--------------	--

Description

Needs xml node and named character vector as input. Modifies the arguments of each first child found in the xml node and adds or updates the attribute vector.

Usage

```
xml_attr_mod(
  xml_content,
  xml_attributes,
  escapes = FALSE,
  declaration = FALSE,
  remove_empty_attr = TRUE
)
```

Arguments

xml_content	some valid xml_node
xml_attributes	R vector of named attributes
escapes	bool if escapes should be used
declaration	bool if declaration should be imported
remove_empty_attr	bool remove empty attributes or ignore them

Details

If a named attribute in `xml_attributes` is "" remove the attribute from the node. If `xml_attributes` contains a named entry found in the xml node, it is updated else it is added as attribute.

Examples

```
# add single node
xml_node <- "<a foo=\"bar\">open1sx2</a><b />"
xml_attr <- c(qux = "quux")
# "<a foo=\"bar\" qux=\"quux\">open1sx2</a><b qux=\"quux\"/>"
xml_attr_mod(xml_node, xml_attr)

# update node and add node
xml_node <- "<a foo=\"bar\">open1sx2</a><b />"
xml_attr <- c(foo = "baz", qux = "quux")
# "<a foo=\"baz\" qux=\"quux\">open1sx2</a><b foo=\"baz\" qux=\"quux\"/>"
xml_attr_mod(xml_node, xml_attr)

# remove node and add node
```

```
xml_node <- "<a foo=\"bar\">openxlsx2</a><b />"
xml_attr <- c(foo = "", qux = "quux")
# "<a qux=\"quux\">openxlsx2</a><b qux=\"quux\" />"
xml_attr_mod(xml_node, xml_attr)
```

xml_node_create	<i>create xml_node from R objects</i>
-----------------	---------------------------------------

Description

takes `xml_name`, `xml_children` and `xml_attributes` to create a new `xml_node`.

Usage

```
xml_node_create(
  xml_name,
  xml_children = NULL,
  xml_attributes = NULL,
  escapes = FALSE,
  declaration = FALSE
)
```

Arguments

<code>xml_name</code>	the name of the new <code>xml_node</code>
<code>xml_children</code>	character vector children attached to the <code>xml_node</code>
<code>xml_attributes</code>	named character vector of attributes for the <code>xml_node</code>
<code>escapes</code>	bool if escapes should be used
<code>declaration</code>	bool if declaration should be imported

Details

if `xml_children` or `xml_attributes` should be empty, use `NULL`

Examples

```
xml_name <- "a"
# "<a/>"
xml_node_create(xml_name)

xml_child <- "openxlsx"
# "<a>openxlsx</a>"
xml_node_create(xml_name, xml_children = xml_child)

xml_attr <- c(foo = "baz", qux = "quux")
# "<a foo=\"baz\" qux=\"quux\" />"
xml_node_create(xml_name, xml_attributes = xml_attr)
```

```
# "<a foo=\"baz\" qux=\"quux\">openxlsx</a>"
xml_node_create(xml_name, xml_children = xml_child, xml_attributes = xml_attr)
```

xml_rm_child	<i>remove xml child to node</i>
--------------	---------------------------------

Description

remove xml child to node

Usage

```
xml_rm_child(xml_node, xml_child, level, which = 0, pointer = FALSE, ...)
```

Arguments

xml_node	xml_node
xml_child	xml_child
level	optional level, if missing the first child is picked
which	optional index which node to remove, if multiple are available. Default disabled all will be removed
pointer	pointer
...	additional arguments passed to read_xml()

Examples

```
xml_node <- "<a><b><c><d/></c></b><c/></a>"
xml_child <- "c"

xml_rm_child(xml_node, xml_child)

xml_rm_child(xml_node, xml_child, level = c("b"))

xml_rm_child(xml_node, "d", level = c("b", "c"))
```

Index

- * **comments**
 - person-wb, 38
 - wb_add_comment, 98
- * **style creating functions**
 - create_border, 12
 - create_cell_style, 13
 - create_colors_xml, 15
 - create_dxfs_style, 16
 - create_fill, 18
 - create_font, 18
 - create_numfmt, 21
 - create_tablestyle, 24
- * **styles**
 - wb_add_border, 92
 - wb_add_cell_style, 93
 - wb_add_fill, 112
 - wb_add_font, 113
 - wb_add_named_style, 122
 - wb_add_numfmt, 123
 - wb_cell_style, 137
- * **workbook styling functions**
 - base_font-wb, 6
 - wb_add_dxfs_style, 110
 - wb_add_style, 131
 - wb_base_colors, 135
- * **workbook wrappers**
 - base_font-wb, 6
 - col_widths-wb, 8
 - creators-wb, 26
 - grouping-wb, 31
 - row_heights-wb, 43
 - wb_add_chartsheet, 96
 - wb_add_data, 102
 - wb_add_data_table, 105
 - wb_add_formula, 115
 - wb_add_pivot_table, 125
 - wb_add slicer, 129
 - wb_add_worksheet, 133
 - wb_base_colors, 135
 - wb_clone_worksheet, 139
 - wb_copy_cells, 142
 - wb_freeze_pane, 147
 - wb_merge_cells, 151
 - wb_save, 162
 - wb_set_last_modified_by, 166
 - wb_workbook, 174
- * **worksheet content functions**
 - col_widths-wb, 8
 - filter-wb, 28
 - grouping-wb, 31
 - named_region-wb, 34
 - row_heights-wb, 43
 - wb_add_conditional_formatting, 99
 - wb_add_data, 102
 - wb_add_data_table, 105
 - wb_add_formula, 115
 - wb_add_pivot_table, 125
 - wb_add slicer, 129
 - wb_add_thread, 132
 - wb_freeze_pane, 147
 - wb_merge_cells, 151
 - + .fmt_txt (fmt_txt), 29
 - .Deprecated, 37
 - [.wb_data (wb_data), 143
 - active_sheet-wb, 4
 - as.character.fmt_txt (fmt_txt), 29
 - as_xml, 5
 - base::as.Date.character, 10
 - base::interactive(), 60, 177
 - base_font-wb, 6
 - character, 10
 - clean_worksheet_name, 7
 - col2int, 8
 - col_widths-wb, 8
 - convert_date, 10
 - convert_datetime (convert_date), 10

- convert_hms (convert_date), 10
- convert_to_excel_date, 11
- convert_to_excel_date(), 37
- convertToExcelDate(), 37
- create_border, 12, 15–19, 21, 26
- create_border(), 92, 131
- create_cell_style, 13, 13, 16–19, 21, 26
- create_cell_style(), 21, 123, 131
- create_colors_xml, 13, 15, 15, 17–19, 21, 26
- create_colours_xml (create_colors_xml), 15
- create_comment(), 37
- create_dxfs_style, 13, 15, 16, 16, 18, 19, 21, 26
- create_dxfs_style(), 111, 131
- create_fill, 13, 15–17, 18, 19, 21, 26
- create_fill(), 131
- create_font, 13, 15–18, 18, 21, 26
- create_font(), 131
- create_hyperlink, 20
- create_numfmt, 13, 15–19, 21, 26
- create_numfmt(), 123, 131
- create_pivottablestyle (create_tablestyle), 24
- create_sparklines, 22
- create_sparklines(), 130
- create_tablestyle, 13, 15–19, 21, 24
- creators-wb, 26
- current_sheet (waivers), 47
- delete_data(), 36
- dims_helper, 27
- dims_to_rowcol (dims_helper), 27
- filter-wb, 28
- fmt_txt, 29
- fmt_txt(), 98, 141
- grDevices::colors(), 15, 141
- grDevices::dev.copy(), 127
- grDevices::palette(), 15
- grouping-wb, 31
- int2col, 33
- logical, 10
- na_strings (waivers), 47
- na_strings(), 103, 106, 176
- named_region-wb, 34
- next_sheet (waivers), 47
- openxlsx2-deprecated, 36
- openxlsx2_options, 37
- person-wb, 38
- print.fmt_txt (fmt_txt), 29
- print.pugi_xml, 39
- properties-wb, 39
- pugixml, 41
- read_xlsx (wb_to_df), 169
- read_xml, 42
- remove_comment(), 36
- row_heights-wb, 43
- rowcol_to_dims (dims_helper), 27
- rowcol_to_dims(), 27
- sheet_names-wb, 44
- sheet_visibility-wb, 45
- strptime, 10
- styles_on_sheet, 46
- temp_xlsx, 46
- waivers, 47
- wb_add_border, 92, 95, 113, 115, 123, 124, 137
- wb_add_border(), 13
- wb_add_cell_style, 92, 93, 113, 115, 123, 124, 137
- wb_add_cell_style(), 15, 122
- wb_add_cell_style(wrap_text = TRUE), 9
- wb_add_chart_xml, 97
- wb_add_chart_xml(), 110, 120, 121, 128
- wb_add_chartsheet, 6, 9, 27, 32, 44, 96, 103, 107, 116, 127, 130, 134, 136, 140, 143, 148, 151, 162, 167, 175
- wb_add_comment, 98
- wb_add_comment(), 36, 38, 132, 141
- wb_add_conditional_formatting, 9, 28, 32, 35, 44, 99, 104, 107, 116, 127, 130, 132, 148, 151
- wb_add_creators (creators-wb), 26
- wb_add_data, 6, 9, 27, 28, 32, 35, 44, 97, 101, 102, 107, 116, 127, 130, 132, 134, 136, 140, 143, 148, 151, 162, 167, 175, 176
- wb_add_data(), 11, 28, 36, 103, 107, 175

- `wb_add_data_table`, [6](#), [9](#), [27](#), [28](#), [32](#), [35](#), [44](#), [97](#), [101](#), [103](#), [104](#), [105](#), [116](#), [127](#), [130](#), [132](#), [134](#), [136](#), [140](#), [143](#), [148](#), [151](#), [162](#), [167](#), [175](#), [176](#)
- `wb_add_data_table()`, [28](#), [36](#), [103](#), [107](#), [173](#)
- `wb_add_data_validation`, [107](#)
- `wb_add_drawing`, [109](#)
- `wb_add_drawing()`, [97](#), [120](#), [128](#)
- `wb_add_dxfs_style`, [6](#), [110](#), [131](#), [136](#)
- `wb_add_dxfs_style()`, [17](#)
- `wb_add_fill`, [92](#), [95](#), [112](#), [115](#), [123](#), [124](#), [137](#)
- `wb_add_fill()`, [18](#)
- `wb_add_filter (filter-wb)`, [28](#)
- `wb_add_font`, [92](#), [95](#), [113](#), [113](#), [123](#), [124](#), [137](#)
- `wb_add_font()`, [19](#)
- `wb_add_form_control`, [117](#)
- `wb_add_formula`, [6](#), [9](#), [27](#), [28](#), [32](#), [35](#), [44](#), [97](#), [101](#), [103](#), [104](#), [107](#), [115](#), [127](#), [130](#), [132](#), [134](#), [136](#), [140](#), [143](#), [148](#), [151](#), [162](#), [167](#), [175](#)
- `wb_add_formula()`, [20](#), [36](#), [103](#), [106](#), [172](#)
- `wb_add_ignore_error`, [118](#)
- `wb_add_image`, [119](#), [121](#)
- `wb_add_image()`, [97](#), [110](#), [127](#), [128](#)
- `wb_add_mips`, [120](#)
- `wb_add_mips()`, [121](#)
- `wb_add_mschart`, [121](#)
- `wb_add_mschart()`, [97](#), [110](#), [120](#), [121](#), [128](#), [144](#)
- `wb_add_named_region (named_region-wb)`, [34](#)
- `wb_add_named_style`, [92](#), [95](#), [113](#), [115](#), [122](#), [124](#), [137](#)
- `wb_add_numfmt`, [92](#), [95](#), [113](#), [115](#), [123](#), [123](#), [137](#)
- `wb_add_numfmt()`, [21](#)
- `wb_add_page_break`, [124](#)
- `wb_add_person (person-wb)`, [38](#)
- `wb_add_person()`, [132](#)
- `wb_add_pivot_table`, [6](#), [9](#), [27](#), [28](#), [32](#), [35](#), [44](#), [97](#), [101](#), [103](#), [104](#), [107](#), [116](#), [125](#), [130](#), [132](#), [134](#), [136](#), [140](#), [143](#), [148](#), [151](#), [162](#), [167](#), [175](#)
- `wb_add_pivot_table()`, [144](#)
- `wb_add_plot`, [121](#), [127](#)
- `wb_add_plot()`, [97](#), [110](#), [120](#)
- `wb_add_slicer`, [6](#), [9](#), [27](#), [28](#), [32](#), [35](#), [44](#), [97](#), [101](#), [103](#), [104](#), [107](#), [116](#), [127](#), [129](#), [132](#), [134](#), [136](#), [140](#), [143](#), [148](#), [151](#), [162](#), [167](#), [175](#)
- `wb_add_slicer()`, [126](#)
- `wb_add_sparklines`, [130](#)
- `wb_add_sparklines()`, [22](#)
- `wb_add_style`, [6](#), [111](#), [131](#), [136](#)
- `wb_add_style()`, [17](#)
- `wb_add_thread`, [9](#), [28](#), [32](#), [35](#), [44](#), [101](#), [104](#), [107](#), [116](#), [127](#), [130](#), [132](#), [148](#), [151](#)
- `wb_add_thread()`, [38](#), [49](#), [98](#)
- `wb_add_worksheet`, [6](#), [9](#), [27](#), [32](#), [44](#), [97](#), [103](#), [107](#), [116](#), [127](#), [130](#), [133](#), [136](#), [140](#), [143](#), [148](#), [151](#), [162](#), [167](#), [175](#), [176](#)
- `wb_add_worksheet()`, [124](#), [165](#)
- `wb_base_colors`, [6](#), [9](#), [27](#), [32](#), [44](#), [97](#), [103](#), [107](#), [111](#), [116](#), [127](#), [130](#), [131](#), [134](#), [135](#), [140](#), [143](#), [148](#), [151](#), [162](#), [167](#), [175](#)
- `wb_cell_style`, [92](#), [95](#), [113](#), [115](#), [123](#), [124](#), [137](#)
- `wb_clean_sheet`, [138](#)
- `wb_clean_sheet()`, [36](#)
- `wb_clone_sheet_style`, [139](#)
- `wb_clone_worksheet`, [6](#), [9](#), [27](#), [32](#), [44](#), [97](#), [103](#), [107](#), [116](#), [127](#), [130](#), [134](#), [136](#), [139](#), [143](#), [148](#), [151](#), [162](#), [167](#), [175](#)
- `wb_color`, [140](#)
- `wb_color()`, [12](#), [15](#), [96](#), [114](#), [134](#), [176](#)
- `wb_colour (wb_color)`, [140](#)
- `wb_comment`, [141](#)
- `wb_comment()`, [37](#), [98](#)
- `wb_copy_cells`, [6](#), [9](#), [27](#), [32](#), [44](#), [97](#), [103](#), [107](#), [116](#), [127](#), [130](#), [134](#), [136](#), [140](#), [142](#), [148](#), [151](#), [162](#), [167](#), [175](#)
- `wb_data`, [125](#), [129](#), [143](#), [143](#)
- `wb_data()`, [121](#), [125](#), [127](#), [143](#)
- `wb_dims`, [144](#)
- `wb_dims()`, [28](#), [35](#), [36](#)
- `wb_freeze_pane`, [6](#), [9](#), [27](#), [28](#), [32](#), [35](#), [44](#), [97](#), [101](#), [103](#), [104](#), [107](#), [116](#), [127](#), [130](#), [132](#), [134](#), [136](#), [140](#), [143](#), [147](#), [151](#), [162](#), [167](#), [175](#), [176](#)
- `wb_get_active_sheet (active_sheet-wb)`, [4](#)
- `wb_get_active_sheet()`, [47](#)
- `wb_get_base_colors (wb_base_colors)`, [135](#)
- `wb_get_base_colors()`, [141](#)
- `wb_get_base_colours (wb_base_colors)`, [135](#)

- wb_get_base_font (base_font-wb), 6
- wb_get_base_font(), 6, 16
- wb_get_cell_style (wb_cell_style), 137
- wb_get_comment (wb_add_comment), 98
- wb_get_creators (creators-wb), 26
- wb_get_mips (wb_add_mips), 120
- wb_get_mips(), 120, 121
- wb_get_named_regions (named_region-wb), 34
- wb_get_named_regions(), 171, 172
- wb_get_order (wb_order), 152
- wb_get_person (person-wb), 38
- wb_get_person(), 132
- wb_get_properties (properties-wb), 39
- wb_get_selected (active_sheet-wb), 4
- wb_get_sheet_names (sheet_names-wb), 44
- wb_get_sheet_visibility (sheet_visibility-wb), 45
- wb_get_tables, 149
- wb_get_tables(), 35, 160
- wb_get_thread (wb_add_thread), 132
- wb_grid_lines (wb_set_grid_lines), 164
- wb_grid_lines(), 37
- wb_group_cols (grouping-wb), 31
- wb_group_cols(), 9
- wb_group_rows (grouping-wb), 31
- wb_load, 149
- wb_load(), 35, 47
- wb_merge_cells, 6, 9, 27, 28, 32, 35, 44, 97, 101, 103, 104, 107, 116, 127, 130, 132, 134, 136, 140, 143, 148, 151, 162, 167, 175
- wb_open, 152
- wb_order, 152
- wb_page_setup, 153
- wb_page_setup(), 134
- wb_protect, 157
- wb_protect_worksheet, 159
- wb_read (wb_to_df), 169
- wb_remove_col_widths (col_widths-wb), 8
- wb_remove_comment (wb_add_comment), 98
- wb_remove_comment(), 36
- wb_remove_creators (creators-wb), 26
- wb_remove_filter (filter-wb), 28
- wb_remove_named_region (named_region-wb), 34
- wb_remove_row_heights (row_heights-wb), 43
- wb_remove_tables, 160
- wb_remove_worksheet, 161
- wb_save, 6, 9, 27, 32, 44, 97, 103, 107, 116, 127, 130, 134, 136, 140, 143, 148, 151, 162, 167, 175, 176
- wb_set_active_sheet (active_sheet-wb), 4
- wb_set_base_colors (wb_base_colors), 135
- wb_set_base_colors(), 15
- wb_set_base_colours (wb_base_colors), 135
- wb_set_base_font (base_font-wb), 6
- wb_set_bookview, 163
- wb_set_cell_style (wb_cell_style), 137
- wb_set_cell_style_across (wb_cell_style), 137
- wb_set_col_widths, 176
- wb_set_col_widths (col_widths-wb), 8
- wb_set_creators (creators-wb), 26
- wb_set_grid_lines, 164
- wb_set_grid_lines(), 37
- wb_set_header_footer, 165
- wb_set_last_modified_by, 6, 9, 27, 32, 44, 97, 103, 107, 116, 127, 130, 134, 136, 140, 143, 148, 151, 162, 166, 175
- wb_set_order (wb_order), 152
- wb_set_properties (properties-wb), 39
- wb_set_row_heights (row_heights-wb), 43
- wb_set_selected (active_sheet-wb), 4
- wb_set_sheet_names (sheet_names-wb), 44
- wb_set_sheet_visibility (sheet_visibility-wb), 45
- wb_set_sheetview, 167
- wb_to_df, 169
- wb_to_df(), 144, 150
- wb_ungroup_cols (grouping-wb), 31
- wb_ungroup_rows (grouping-wb), 31
- wb_unmerge_cells (wb_merge_cells), 151
- wb_update_table, 173
- wb_workbook, 6, 9, 27, 32, 44, 97, 103, 107, 116, 127, 130, 134, 136, 140, 143, 148, 151, 162, 167, 174, 176
- wb_workbook(), 38–40, 47
- wbWorkbook, 44, 45, 47, 133, 149, 152, 163, 170, 174, 177
- write_comment(), 36
- write_data(), 36
- write_datatable(), 36

`write_formula()`, 36
`write_xlsx`, 175

`xl_open`, 177
`xl_open()`, 152
`xml_add_child`, 178
`xml_attr (pugixml)`, 41
`xml_attr_mod`, 179
`xml_node (pugixml)`, 41
`xml_node_create`, 180
`xml_node_name (pugixml)`, 41
`xml_rm_child`, 181
`xml_value (pugixml)`, 41